SAMPLE QUESTION PAPER (THEORY) CLASS: XII SESSION: 2024-25 COMPUTER SCIENCE (083)

Time allowed: 3 Hours Maximum Marks: 70

General Instructions:

- This question paper contains 37 questions.
- All questions are compulsory. However, internal choices have been provided in some questions. Attempt only one of the choices in such questions
- The paper is divided into 5 Sections- A, B, C, D and E.
- Section A consists of 21 questions (1 to 21). Each question carries 1 Mark.
- Section B consists of 7 questions (22 to 28). Each question carries 2 Marks.
- Section C consists of 3 questions (29 to 31). Each question carries 3 Marks.
- Section D consists of 4 questions (32 to 35). Each question carries 4 Marks.
- Section E consists of 2 questions (36 to 37). Each question carries 5 Marks.
- All programming questions are to be answered using Python Language only.
- In case of MCQ, text of the correct answer should also be written.

Q No.	Section-A (21 x 1 = 21 Marks) State True or False: The Python interpreter handles logical errors during code execution.					
1.						
2.	<pre>Identify the output of the following code snippet: text = "PYTHONPROGRAM" text=text.replace('PY','#') print(text) (A) #THONPROGRAM</pre>	(1)				
	(B) ##THON#ROGRAM (C) #THON#ROGRAM (D) #YTHON#ROGRAM					
3.	Which of the following expressions evaluates to False? (A) not(True) and False (B) True or False (C) not(False and True) (D) True and not(False)	(1)				
4.	What is the output of the expression? country='International' print(country.split("n")) (A) ('I', 'ter', 'atio', 'al') (B) ['I', 'ter', 'atio', 'al'] (C) ['I', 'n', 'ter', 'n', 'atio', 'n', 'al'] (D) Error	(1)				

Page: 1/11

5.	What will be the output of the following code snippet? message= "World Peace" print(message[-2::-2])	(1)
6.	<pre>What will be the output of the following code? tuple1 = (1, 2, 3) tuple2 = tuple1 tuple1 += (4,) print(tuple1 == tuple2) (A) True (B) False (C) tuple1 (D) Error</pre>	(1)
7.	<pre>If my_dict is a dictionary as defined below, then which of the following statements will raise an exception? my_dict = {'apple': 10, 'banana': 20, 'orange': 30} (A) my_dict.get('orange') (B) print(my_dict['apple', 'banana']) (C) my_dict['apple']=20 (D) print(str(my_dict))</pre>	(1)
8.	What does the list.remove(x) method do in Python? (A) Removes the element at index x from the list (B) Removes the first occurrence of value x from the list (C) Removes all occurrences of value x from the list (D) Removes the last occurrence of value x from the list	(1)
9.	If a table which has one Primary key and two alternate keys. How many Candidate keys will this table have? (A) 1 (B) 2 (C) 3 (D) 4	(1)
10.	<pre>Write the missing statement to complete the following code: file = open("example.txt", "r") data = file.read(100)</pre>	(1)
11.	State whether the following statement is True or False: The finally block in Python is executed only if no exception occurs in the try block.	(1)

12.	<pre>What will be the output of the following code? c = 10 def add(): global c c = c + 2 print(c,end='#') add() c=15 print(c,end='%') (A) 12%15# (B) 15#12% (C) 12#15% (D) 12%15#</pre>	(1)
13.	Which SQL command can change the degree of an existing relation?	(1)
14.	What will be the output of the query? SELECT * FROM products WHERE product_name LIKE 'App%'; (A) Details of all products whose names start with 'App' (B) Details of all products whose names end with 'App' (C) Names of all products whose names start with 'App' (D) Names of all products whose names end with 'App'	(1)
15.	In which datatype the value stored is padded with spaces to fit the specified length. (A) DATE (B) VARCHAR (C) FLOAT (D) CHAR	(1)
16.	Which aggregate function can be used to find the cardinality of a table? (A) sum() (B) count() (C) avg() (D) max()	(1)
17.	Which protocol is used to transfer files over the Internet? (A) HTTP (B) FTP (C) PPP (D) HTTPS	(1)

18.	Which network device is used to connect two networks that use different protocols? (A) Modem (B) Gateway (C) Switch (D) Repeater					
19.	Which switching technique breaks data into smaller packets for transmission, allowing multiple packets to share the same network resources.	(1)				
	Q20 and Q21 are Assertion(A) and Reason(R) based questions. Mark the correct choice as: (A) Both A and R are true and R is the correct explanation for A (B) Both A and R are true and R is not the correct explanation for A (C) A is True but R is False (D) A is False but R is True					
20.	Assertion (A): Positional arguments in Python functions must be passed in the exact order in which they are defined in the function signature. Reasoning (R): This is because Python functions automatically assign default values to positional arguments.	(1)				
21.	Assertion (A): A SELECT command in SQL can have both WHERE and HAVING clauses. Reasoning (R): WHERE and HAVING clauses are used to check conditions, therefore, these can be used interchangeably.	(1)				
Q No	Section-B (7 x 2=14 Marks)	Marks				
22.	How is a mutable object different from an immutable object in Python? Identify one mutable object and one immutable object from the following: (1,2), [1,2], {1:1,2:2}, '123'	(2)				
23.	Give two examples of each of the following: (I) Arithmetic operators (II) Relational operators	(2)				
24.	If L1=[1,2,3,2,1,2,4,2,], and L2=[10,20,30,], then (Answer using builtin functions only) (I) A) Write a statement to count the occurrences of 4 in L1. OR B) Write a statement to sort the elements of list L1 in ascending order.	(2)				

	(II) A) Write a statement to insert all the elements of L2 at the end of L1. OR B) Write a statement to reverse the elements of list L2.				
25.	<pre>Identify the correct output(s) of the following code. Also write the minimum and the maximum possible values of the variable b. import random a="Wisdom" b=random.randint(1,6) for i in range(0,b,2): print(a[i],end='#')</pre>				
	(A) W#	(B) W#i#			
	(C) W#s#	(D) W#i#s#			
26.	The code provided below is intended to swap the first and last elements of a given tuple. However, there are syntax and logical errors in the code. Rewrite it after removing all errors. Underline all the corrections made. def swap_first_last(tup) if len(tup) < 2: return tup new_tup = (tup[-1],) + tup[1:-1] + (tup[0]) return new_tup result = swap_first_last((1, 2, 3, 4)) print("Swapped tuple: " result)				
27.	duplicate values are not allo allowed. B) What constraint should be a	applied on a table column so that owed in that column, but NULL is OR applied on a table column so that column, but duplicate values are	(2)		

	(II) A) Write an SQL command to remove the Primary Key constraint from a table, named MOBILE. M_ID is the primary key of the table.	
	OR	
	B) Write an SQL command to make the column M_ID the Primary Key of an already existing table, named MOBILE.	
28.	A) List one advantage and one disadvantage of star topology.	
	OR	(2)
	B) Expand the term SMTP. What is the use of SMTP?	

Q No.	Section-C (3 x 3 = 9 Marks)	Marks			
29.	A) Write a Python function that displays all the words containing @cmail from a text file "Emails.txt". OR B) Write a Python function that finds and displays all the words longer than 5 characters from a text file "Words.txt".				
30.	A) You have a stack named BooksStack that contains records of books. Each book record is represented as a list containing book_title , author_name , and publication_year . Write the following user-defined functions in Python to perform the specified operations on the stack BooksStack : (I) push_book(BooksStack, new_book): This function takes the stack BooksStack and a new book record new_book as arguments and pushes the new book record onto the stack. (II) pop_book(BooksStack): This function pops the topmost book record from the stack and returns it. If the stack is already empty, the function should display "Underflow". (III) peep(BookStack): This function displays the topmost element of the stack without deleting it. If the stack is empty, the function should display 'None'.	(3)			
	OR				
	(B) Write the definition of a user-defined function `push_even(N)` which accepts a list of integers in a parameter `N` and pushes all those integers which are even from the list `N` into a Stack named `EvenNumbers`. Write function pop_even() to pop the topmost number from the stack and returns it. If the stack is already empty, the function should display "Empty". Write function Disp_even() to display all element of the stack without deleting them. If the stack is empty, the function should display 'None'.				


	For example: If the integers input into the list `VALUES` are: [10, 5, 8, 3, 12] Then the stack `EvenNumbers` should store: [10, 8, 12]	
31.	Predict the output of the following code:	
	d = {"apple": 15, "banana": 7, "cherry": 9}	
	str1 = ""	
	for key in d:	
	$str1 = str1 + str(d[key]) + "@" + "\n"$	
	str2 = str1[:-1]	
	print(str2)	(2)
	OR	(3)
	Predict the output of the following code:	
	line=[4,9,12,6,20]	
	for I in line:	
	for j in range(1,1%5):	
	print(j,'#',end="")	
	print()	

Q No.	Section-D (4 x 4 = 16 Marks)						Marks	
32.	Consider	Consider the table ORDERS as given below						
		O_ld	C_Name	Product	Quantity	Price		
		1001	Jitendra	Laptop	1	12000		
		1002	Mustafa	Smartphone	2	10000		
		1003	Dhwani	Headphone	1	1500		
	Not	e: The ta	ble contains	s many more re	ecords tha	n shown h	ere.	
	A) Write the following queries:						(4)	
	(I) To display the total Quantity for each Product, excluding Products with total Quantity less than 5.							
	(II) To display the orders table sorted by total price in descending order.							
	(III)) To di	splay the di	stinct custome	r names fr	om the Or	ders table.	

	, ,		the sum	of Price of a	ll the order	s for which	the quantity	
		s null.		OR				
	B) Write th	ne outpu	ıt	OIX				
	,	•		sum (quant	itv) as	total o	uantity	
		_		y c_name;		_4	-	
	(II) Sel		from	orders who	ere prod	uct like	e	
	(III) Select o_id, c_name, product, quantity, price from orders where price between 1500 and 12000;							
	(IV) Sel	ect ma	ax (pri	ce) from	orders;			
33.	A csv file "Ha file contains the Name	he follov	wing da		ta of a surv	/ey. Each	record of the	
	Popula			•				
	•	•	Numbe	r of persons	who partic	ipated in	the survey in	
	that co	• ,	er of ne	rsons who ac	cented the	ot they we	re Hanny)	
	Парру	(IVUITIO	ei oi pe	isons who at	cepted the	it tiley wei	е парру)	(4)
	For example, a sample record of the file may be:							(1)
				00, 3426]				
	Write the follo	wing Py	ython fu	nctions to pe	rform the s	specified c	perations on	
	this file: (I) Rea	ad all th	o data f	rom tha fila i	n tha form	of a list a	nd display all	
	` '			vhich the pop				
				of records in				
34.	Saman has	been e	entruste	d with the	manageme	ent of La	w University	
J-1.	Database. He	e needs	s to ac	cess some	information	from FA	CULTY and	
	COURSES to				•		•	
	information by	y writing	the de	sired SQL qu	eries as m	entioned b	pelow.	
			Table:	FACULTY				
	F_ID	FNa		LName	Hire_D	ate Sa	lary	
	102	Amit		Mishra	12-10-1		000	
	103	Nitin		Vyas O	24-12-1		00	(4)
	104	Raks		Soni Malhetre	18-5-20		000	
	105 106	Rash Sulek		Malhotra Srivastava	11-9-20 5-6-20		000	
	100			J	1 0020			
	_		1	Table: COUF		T	7	
		C_ID	F_ID		ame	Fees	_	
	-	C21	102	Grid Com		40000	-	
		C22	106	System D	<i>า</i> ธอเนูเา	16000	J	

							1
	C23	104	Computer S	ecurity	8000		
	C24	106	Human Biolo	ogy	15000		
	C25	102	Computer N		20000		
	C26	105	Visual Basic		6000		
			etails (from bot			se Faculties	
	whose salary				, , , , ,		
	(II) To display the details of courses whose fees is in the range of 20000						
	to 50000 (both					.gc cccc	
	(III) To increase the		•	v 500 w	hich have	"Computer"	
	in their Course			y 300 w	illoit Have	Compater	
				Jama) a	f foculty to	king Systom	
	. , , , ,	names (FName and LN	varrie) U	i iacuity ta	King System	
	Design.		OD				
	(D) T !! !		OR				
	(B) To display	the Carte	sian Product o	of these	two tables).	
35.	A table, named STAT	TONERY	, in ITEMDB d	latabase	, has the f	following	
	structure:						
		F:		T			
		Field	_	Type			
		itemNoritemNar		int(11)	<u>-\</u>		
		price	ile va	archar(15 float)		
		qty		int(11)			
		419		(11)			
	Write the following Py	thon fun	ction to perfor	m the sp	ecified on	eration:	(4)
	AddAndDisplay(): To		•	-	-		
	STATIONERY. The f	-					
	from the STATIONER						
		(I lable	where the rinc	e is give	iter triair i	20.	
	Assume the following	for Dyth	on Database s	onnocti	rity r:		
	Host: localhost, Use	•			/ity.		
	Host. localilost, Ost	ει. 100ι,	Password. Pe	BIICII			
Q.No.		SECTIO	N E (2 X 5 = 1	0 Marks)		Marks
26	Surya is a manager v	vorkina ir	n a recruitment	agency	. He need	s to manage	
36.	the records of various						
	information of each c					<u> </u>	
	- Candidate_ID – integer						
	- Candidate_Name – string						
	- Designation – string						4
	- Experience – float						(5)
	Volume a programmer of the company, have been assigned to do this ich						
	You, as a programmer of the company, have been assigned to do this job for Surya.						
	13. 23.75.						
	(I) Write a function	to input	the data of a c	andidate	and app	end it in a	
	(I) Write a function to input the data of a candidate and append it in a binary file.						

- (II) Write a function to update the data of candidates whose experience is more than 10 years and change their designation to "Senior Manager".
- (III) Write a function to read the data from the binary file and display the data of all those candidates who are not "Senior Manager".
- Event Horizon Enterprises is an event planning organization. It is planning to set up its India campus in Mumbai with its head office in Delhi. The Mumbai campus will have four blocks/buildings ADMIN, FOOD, MEDIA, DECORATORS. You, as a network expert, need to suggest the best network-related solutions for them to resolve the issues/problems mentioned in points (I) to (V), keeping in mind the distances between various blocks/buildings and other given parameters.



Block to Block distances (in Mtrs.)

		· · · · · · · · · · · · · · · · · · ·
From	То	Distance
ADMIN	FOOD	42 m
ADMIN	MEDIA	96 m
ADMIN	DECORATORS	48 m
FOOD	MEDIA	58 m
FOOD	DECORATORS	46 m
MEDIA	DECORATORS	42 m

Distance of Delhi Head Office from Mumbai Campus = 1500 km Number of computers in each of the blocks/Center is as follows:

ADMIN	30
FOOD	18
MEDIA	25
DECORATORS	20
DELHI HEAD	
OFFICE	18

(5)

- (I) Suggest the most appropriate location of the server inside the MUMBAI campus. Justify your choice.
- (II) Which hardware device will you suggest to connect all the computers within each building?
- (III) Draw the cable layout to efficiently connect various buildings within the MUMBAI campus. Which cable would you suggest for the most efficient data transfer over the network?
- (IV) Is there a requirement of a repeater in the given cable layout? Why/ Why not?
- (V) A) What would be your recommendation for enabling live visual communication between the Admin Office at the Mumbai campus and the DELHI Head Office from the following options:
 - a) Video Conferencing
 - b) Email
 - c) Telephony
 - d) Instant Messaging

OR

B) What type of network (PAN, LAN, MAN, or WAN) will be set up among the computers connected in the MUMBAI campus?

MARKING SCHEME

Class: XII Session: 2024-25 Computer Science (083)

Time allowed: 3 Hours Maximum Marks: 70

Q No.	SECTION A (21X1=21)	Marks
1.	False	(1)
	(1 mark for correct answer)	
2.	(A) #THONPROGRAM	(1)
	(1 mark for correct answer)	(1)
3.	(A) not (True) and False	(1)
	(1 mark for correct answer)	(1)
4.	(B) ['I', 'ter', 'atio', 'al']	(4)
	(1 mark for correct answer)	(1)
5.	ce lo	(4)
	(1 mark for correct answer)	(1)
6.	(B) False	(1)
	(1 mark for correct answer)	(1)
7.	(B) print(my_dict['apple', 'banana'])	(4)
	(1 mark for correct answer)	(1)
8.	(B) Removes the first occurrence of value x from the list	(1)
	(1 mark for correct answer)	(1)
9.	(C) 3	(4)
	(1 mark for correct answer)	(1)
10.	file.seek(0) (OR file.seek(0,0))	(1)
	(1 mark for correct answer)	(1)
11.	False	(4)
	(1 mark for correct answer)	(1)
12.	(C) 12#15%	(4)
	(1 mark for correct answer)	(1)
13.	Alter (or Alter Table)	(1)
	(1 mark for correct answer)	

14.	(A) Details of all products whose names start with 'App' (1 mark for correct answer)	(1)
15.	(D) CHAR (1 mark for correct answer)	(1)
16.	(B) count() (1 mark for correct answer)	(1)
17.	(B) FTP (1 mark for correct answer)	(1)
18.	(B) Gateway (1 mark for correct answer)	(1)
19.	(B) Packet Switching (1 mark for correct answer)	(1)
20.	(C) A is True but R is False. (1 mark for correct answer)	(1)
21.	(C) A is True but R is False. (1 mark for correct answer)	(1)

Q No.	SECTION B (7 X 2 =14)	Marks
22.	A mutable object can be updated whereas an immutable object cannot be updated. Mutable object: [1,2] or {1:1,2:2} (Any one)	(2)
	Immutable object: (1,2) or '123' (Any one) (1 mark for correct difference) (½ x 2 = 1 Mark for selecting correct objects)	
23.	 (I) Arithmetic operators: +,- (II) Relational operators: >, >= (½ x 4 = 2 Marks for each correct operator) 	(2)
24.	(I) A) L1.count(4) OR B) L1.sort() (1 mark for correct answer)	(2)

	(II) A) L1.extend(L2) OR B) L2.reverse() (1 mark for correct answer) (A), (C)	
	OR B) L2.reverse() (1 mark for correct answer)	
	(1 mark for correct answer)	
	,	
	(A), (C)	+
25.		
	$(\frac{1}{2} \times 2 = 1 Mark)$	(2)
	Minimum and maximum possible values of the variable b: 1,6	(=)
	$(\frac{1}{2} \times 2 = 1 \text{ Mark})$	
26.	def swap_first_last(tup <u>):</u>	
	if len(tup) < 2:	
	return tup	
	new_tup = (tup[-1],) + tup[1:-1] + (tup [0],)	
	return new_tup	
		(2)
	result = swap_first_last((1, 2, 3, 4))	
	print("Swapped <u>tuple:", result)</u>	
	(½ mark each for correcting 4 mistakes)	
	(72 mark each for correcting 4 mistakes)	
27.	(I)	
	A) UNIQUE	
	OR	
	B) NOT NULL (1 mark for correct answer)	
	(II)	(2)
	A) ALTER TABLE MOBILE DROP PRIMARY KEY;	
	OR	
	B) ALTER TABLE MOBILE ADD PRIMARY KEY (M_ID);	
	(1 mark for correct answer)	
28.	A) Advantage: Network extension is easy.	
	Disadvantage: Failure of switch/hub results in failure of the network.	
	(1 mark for correct Advantage)	
	(1 mark for correct Disadvantage)	(2)
	OR	

```
B) SMTP: Simple Mail Transfer Protocol.

SMTP is used for sending e-mails from client to server.

(1 mark for correct expansion)

(1 mark for correct usage)
```

Q No.	SECTION C (3 X 3 = 9)	Marks
29.	(A)	
	def show():	
	f=open("Email.txt",'r')	
	data=f.read()	
	words=data.split()	
	for word in words:	
	if '@cmail' in word:	
	print(word,end=' ')	
	f.close()	
	(½ mark for correct function header)	
	(½ mark for correctly opening the file)	
	(½ mark for correctly reading from the file)	
	(½ mark for splitting the text into words)	
	(1 mark for correctly displaying the desired words)	(3)
	OR (B)	
	def display_long_words(): with open("Words.txt", 'r') as file:	
	data=file.read()	
	words=data.split()	
	for word in words:	
	if len(word)>5: print(word,end=' ')	
	(½ mark for correct function header)	
	(½ mark for correctly opening the file)	
	(½ mark for correctly reading from the file)	
	(½ mark for splitting the text into words)	
	(1 mark for correctly displaying the desired words)	

```
30.
      (A)
       (l)
         def push_book(BooksStack, new_book):
              BooksStack.append(new_book)
       (II)
          def pop_book(BooksStack):
             if not BooksStack:
               print("Underflow")
            else:
               return(BookStack.pop())
       (III)
          def peep(BooksStack):
             if not BooksStack:
               print("None")
             else:
               print(BookStack[-1])
      (3x1 mark for correct function body; No marks for any function header as it
      was a part of the question)
                                          OR
      (B)
      def push_even(N):
                                                                                    (3)
             EvenNumbers = []
             for num in N:
                 if num % 2 == 0:
                   EvenNumbers.append(num)
             return EvenNumbers
      VALUES = []
      for i in range(5):
         VALUES.append(int(input("Enter an integer: ")))
      EvenNumbers = push_even(VALUES)
      def pop_even():
            if not EvenNumbers:
               print("Underflow")
            else:
               print(EvenNumbers.pop())
      pop_even()
```

```
def Disp_even():
             if not EvenNumbers:
               print("None")
             else:
               print(EvenNumbers[-1])
      Disp_even()
      (1/2 for identifying even numbers)
      (1/2 mark for correctly adding data to stack)
       (1/2 mark for correctly poping data on the stack and 1/2 mark for checking
      condition)
       (1/2 mark for correctly displaying the data with none)
       (1/2 mark for function call statements)
31.
          (A) 15@
             7@
             9
          OR
                                                                                        (3)
          (B) 1 #2 #3#
             1 #2 #3 #
             1#
       (1 mark for each correct line of output)
       (deduct ½ mark for not printing @/#)
```

Q No.	SECTION D (4 X 4 = 16)	Marks
32.	(A) (I) select Product, sum(Quantity) from orders group by product having sum(Quantity)>=5; (II) select * from orders order by Price desc; (III) select distinct C_Name from orders; (IV) select sum(price) as total_price from orders where Quantity IS NULL; (4 x 1 mark for each correct query) OR (B) (I)	(4)
	C_Name Total_Quantity Jitendra 1 Mustafa 2 Dhwani 1	


```
(II)
      O_Id | C_Name | Product
                                   | Quantity | Price
      ---- |-----
                                   |-----
      1002 | Mustafa | Smartphone | 2
                                             | 10000
      1003 | Dhwani | Headphone | 1
                                             1 1500
      (III) O_Id | C_Name | Product
                                       | Quantity | Price
               |----
                          |----
                                        |-----
                                       | 1
      1001
               | Jitendra | Laptop
                                                  12000
      1002
               | Mustafa | Smartphone | 2
                                                  | 10000
               | Dhwani | Headphone | 1
      1003
                                                  | 1500
      (IV)
         MAX(Price)
         12000
      (4 x 1 mark for each correct output)
33.
      (I)
          def show():
            import csv
            f=open("happiness.csv",'r')
            records=csv.reader(f)
            next(records, None) #To skip the Header row
            for i in records:
               if int(i[1])>5000000:
                 print(i)
            f.close()
      (½ mark for opening in the file in right mode)
      (1/2 mark for correctly creating the reader object)
      (1/2 mark for correctly checking the condition)
                                                                                   (4)
      (1/2 mark for correctly displaying the records)
      (II)
          def Count_records():
            import csv
            f=open("happiness.csv",'r')
            records=csv.reader(f)
            next(records, None) #To skip the Header row
            count=0
            for i in records:
                 count+=1
            print(count)
            f.close()
```

(½ ma	ark for opening in the file in right mode) ark for correctly creating the reader object) ark for correct use of counter)	
(½ ma	ark for correctly displaying the counter)	
No	ote (for both parts (I) and (II)): (i) Ignore import csv as it may be considered the part of the complete program, and there is no need to import it in individual functions.	
	(ii) Ignore next(records, None) as the file may or may not have the Header Row.	
34. (I) (II) (III) (IV)	Select * from FACULTY natural join COURSES where Salary<12000; Or Select * from FACULTY, COURSES where Salary<12000 and facuty.f_id=courses.f_id; Select * from courses where fees between 20000 and 50000; Update courses set fees=fees+500 where CName like '%Computer%'; (A) Select FName, LName from faculty natural join courses where Came="System Design"; Or Select FName, LName from faculty, courses where Came="System Design" and facuty.f_id=courses.f_id; OR (B) Select * from FACULTY, COURSES;	(4)
(4x1 n	nark for each correct query)	
imp myd no= nm= pr=1 qty= que que myd myd for i	ort mysql.connector as mycon db=mycon.connect(host="localhost",user="root",	(4)

```
(½ mark for correctly importing the connector object)
(½ mark for correctly creating the connection object)
(½ mark for correctly creating the cursor object)
(½ mark for correctly inputting the data)
(½ mark for correct creation of first query)
(½ mark for correctly executing the first query with commit)
(½ mark for correctly executing the second query)
(½ mark for correctly displaying the data)
```

Q No.	SECTION E (2 X 5 = 10)	Marks
36.	(I) import pickle	(5)
	def input_candidates(): candidates = [] n = int(input("Enter the number of candidates you want to add: ")) for i in range(n): candidate_id = int(input("Enter Candidate ID: ")) candidate_name = input("Enter Candidate Name: ") designation = input("Enter Designation: ") experience = float(input("Enter Experience (in years): ")) candidates.append([candidate_id, candidate_name, designation, experience]) return candidates candidates_list = input_candidates() def append_candidate_data(candidates):	
	with open('candidates.bin', 'ab') as file: for candidate in candidates: pickle.dump(candidate, file) print("Candidate data appended successfully.")	
	append_candidate_data(candidates_list)	
	(II) import pickle	
	<pre>def update_senior_manager(): updated_candidates = [] try:</pre>	
	with open('candidates.bin', 'rb') as file: while True: try:	
	candidate = pickle.load(file) if candidate[3] > 10: # If experience > 10 years candidate[2] = 'Senior Manager' updated_candidates.append(candidate) except EOFError:	

```
break # End of file reached
         except FileNotFoundError:
            print("No candidate data found. Please add candidates first.")
         with open('candidates.bin', 'wb') as file:
            for candidate in updated candidates:
              pickle.dump(candidate, file)
         print("Candidates updated to Senior Manager where applicable.")
       update_senior_manager()
      (III)
      import pickle
      def display_non_senior_managers():
         try:
            with open('candidates.bin', 'rb') as file:
              while True:
                try:
                   candidate = pickle.load(file)
                   if candidate[2] != 'Senior Manager': # Check if not Senior
       Manager
                      print(f"Candidate ID: {candidate[0]}")
                      print(f"Candidate Name: {candidate[1]}")
                      print(f"Designation: {candidate[2]}")
                      print(f"Experience: {candidate[3]}")
                      print("----")
                 except EOFError:
                   break # End of file reached
         except FileNotFoundError:
            print("No candidate data found. Please add candidates first.")
       display_non_senior_managers()
       (1/2 mark of import pickle)
       (1/2 mark for input)
      (1/2 mark for opening file in append mode and 1/2 mark for using dump)
      (1/2 mark for opening file in read mode and 1/2 mark for using load)
       (1 mark for checking the condition and updating the value)
       (1 mark for checking the condition and displaying data correctly)
37.
      (I) ADMIN Block as it has maximum number of computers.
                                                                                        (5)
       (1 mark for correct answer)
      (II) Switch
       (1 mark for correct answer)
       (III)
```



(or Any other correct layout)

Cable: Coaxial cable

(½ mark for correct layout + ½ mark for correct table type)

(IV) There is no requirement of the Repeat as the optical fibre cable used for the network can carry the data to much longer distances than within the campus.

(1 mark for correct answer)

(V) (A) a) Video Conferencing

OR

(B) LAN

(1 mark for correct answer)

Class: XII Session: 2023-24

Computer Science (083)

Sample Question Paper (Theory)

Time allowed: 3 Hours Maximum Marks: 70

General Instructions:

- Please check this question paper contains 35 questions.
- The paper is divided into 4 Sections- A, B, C, D and E.
- Section A, consists of 18 questions (1 to 18). Each question carries 1 Mark.
- Section B, consists of 7 questions (19 to 25). Each question carries 2 Marks.
- Section C, consists of 5 questions (26 to 30). Each question carries 3 Marks.
- Section D, consists of 2 questions (31 to 32). Each question carries 4 Marks.
- Section E, consists of 3 questions (33 to 35). Each question carries 5 Marks.
- All programming questions are to be answered using Python Language only.

Que s No	Quest	ion	Marks
5110	SECTI	ON A	
1	State True or False:		1
	"In a Python program, if a break state terminates the execution of all loops in o		
2	In a table in MYSQL database, an attrib	ute A of datatype varchar (20)	1
	has the value "Keshav". The attribute	B of datatype char (20) has value	
	"Meenakshi". How many characters a	are occupied by attribute A and	
	attribute B?		
	a. 20,6	o. 6,20	
	c. 9,6	1. 6,9	
3	What will be the output of the following	statement:	1
	print(3-2**2**3+99/11)		
	a. 244	o. 244.0	
	c244.0	l. Error	
4	Select the correct output of the code:		1

```
s = "Python is fun"
     l = s.split()
     s new = "-".join([1[0].upper(), 1[1], 1[2].capitalize()])
     print(s new)
     Options:
        a. PYTHON-IS-Fun
        b. PYTHON-is-Fun
        c. Python-is-fun
        d. PYTHON-Is -Fun
5
     In MYSQL database, if a table, Alpha has degree 5 and cardinality 3, and
                                                                               1
      another table, Beta has degree 3 and cardinality 5, what will be the degree
     and cardinality of the Cartesian product of Alpha and Beta?
      a. 5.3
                                 b. 8,15
      c. 3,5
                                 d. 15.8
     Riya wants to transfer pictures from her mobile phone to her laptop. She
                                                                               1
6
      uses Bluetooth Technology to connect two devices. Which type of network
      will be formed in this case?
      a. PAN
                                          b. LAN
      c. MAN
                                          d. WAN
     Which of the following will delete key-value pair for key = "Red" from a
7
                                                                               1
     dictionary D1?
      a. delete D1("Red")
     b. del D1["Red"]
      c. del.D1["Red"]
      d. D1.del["Red"]
8
     Consider the statements given below and then choose the correct output
                                                                               1
     from the given options:
     pride="#G20 Presidency"
     print(pride[-2:2:-2])
```

	Options: a. ndsr b. ceieP0 c. ceieP d. yndsr		
9	Which of the following statement(s) would give an error	during execution of	1
	the following code?		
	tup = (20, 30, 40, 50, 80, 79)		
	print(tup) #Statement 1		
	<pre>print(tup[3]+50) #Statement 2</pre>		
	<pre>print(max(tup)) #Statement 3</pre>		
	tup[4]=80 #Statement 4		
	a. Statement 1b. Statement 2c. Statement 3d. Statement 4		
10	What possible outputs(s) will be obtained when the follow executed? import random myNumber=random.randint(0,3)		1
	<pre>COLOR=["YELLOW", "WHITE", "BLACK for I in range(1, myNumber): print(COLOR[I], end="*") print()</pre>	K" , "RED"]	
	Options:		
	a.		

	RED*	
	WHITE*	
	BLACK*	
	b.	
	WHITE*	
	BLACK*	
	c.	
	WHITE* WHITE*	
	BLACK* BLACK*	
	d.	
	YELLOW*	
	WHITE*WHITE*	
	BLACK* BLACK*	
11	Fill in the blank:	1
	The modem at the sender's computer end acts as a	
	a. Model	
	b. Modulator	
	c. Demodulator	
	d. Convertor	
12	Consider the code given below:	1
	b=100	
	<pre>def test(a):</pre>	
	b=b+a	
	print(a,b)	
	test(10) print(b)	

	Which of the following statements should be given in the blank for	
	#Missing Statement, if the output produced is 110?	
	Options:	
	a. global a	
	b. global b=100	
	c. global b	
	d. global a=100	
13	State whether the following statement is True or False:	1
	An exception may be raised even if the program is syntactically correct.	
14	Which of the following statements is FALSE about keys in a relational	1
	database?	
	a. Any candidate key is eligible to become a primary key.	
	b. A primary key uniquely identifies the tuples in a relation.	
	c. A candidate key that is not a primary key is a foreign key.	
	d. A foreign key is an attribute whose value is derived from the primary	
	key of another relation.	
15	Fill in the blank:	1
	In case of switching, before a communication starts, a	
	dedicated path is identified between the sender and the receiver.	
16	Which of the following functions changes the position of file pointer and	1
	returns its new position?	
	a.flush()	
	b.tell()	
	c.seek()	
	d.offset()	
	Q17 and 18 are ASSERTION AND REASONING based questions. Mark	
	the correct choice as (a) Both A and R are true and R is the correct explanation for A	
	(b) Both A and R are true and R is not the correct explanation for A	

	(c) A is True but R is False		
17	(d) A is false but R is True Assertion(A): List is an immutable data type	1	
-,	Reasoning(R): When an attempt is made to update the value of an		
	immutable variable, the old variable is destroyed and a new variable is		
	created by the same name in memory.		
18	Assertion(A): Python Standard Library consists of various modules.		
10	Reasoning(R): A function in a module is used to simplify the code and	1	
	avoids repetition.		
19	(i) Expand the following terms:	1+1=	
1)	POP3, URL	2	
	(ii) Give one difference between XML and HTML.		
	OR		
	(i) Define the term bandwidth with respect to networks.		
	(ii) How is http different from https?		
20	The code given below accepts a number as an argument and returns the	2	
	reverse number. Observe the following code carefully and rewrite it after		
	removing all syntax and logical errors. Underline all the corrections made.		
	define revNumber(num):		
	rev = 0		
	rem = 0		
	While num > 0:		
	rem ==num %10		
	rev = rev*10 + rem		
	num = num//10 return rev		
	print (revNumber (1234))		

21	Write a function countNow (PLACES) in Python, that takes the	2
	dictionary, PLACES as an argument and displays the names (in	
	uppercase)of the places whose names are longer than 5 characters.	
	For example, Consider the following dictionary	
	PLACES={1:"Delhi",2:"London",3:"Paris",4:"New	
	York",5:"Doha"}	
	The output should be:	
	LONDON	
	NEW YORK	
	OR	
	Write a function, lenWords (STRING), that takes a string as an argument	
	and returns a tuple containing length of each word of a string.	
	For example, if the string is "Come let us have some fun", the	
	tuple will have (4, 3, 2, 4, 4, 3)	
22	Predict the output of the following code:	2
	<pre>S = "LOST" L = [10,21,33,4] D={} for I in range(len(S)): if I%2==0: D[L.pop()] = S[I] else: D[L.pop()] = I+3 for K,V in D.items(): print(K,V,sep="*")</pre>	
23	Write the Python statement for each of the following tasks using BUILT-IN functions/methods only: (i) To insert an element 200 at the third position, in the list L1.	1+1= 2
	(ii) To check whether a string named, message ends with a full stop / period or not.	

	OR	
	A list named studentAge stores age of students of a class. Write the Python command to import the required module and (using built-in function) to display the most common age value from the given list.	
24	Ms. Shalini has just created a table named "Employee" containing	2
	columns Ename, Department and Salary.	
	After creating the table, she realized that she has forgotten to add a primary	
	key column in the table. Help her in writing an SQL command to add a	
	primary key column EmpId of integer type to the table Employee.	
	Thereafter, write the command to insert the following record in the table:	
	EmpId- 999	
	Ename-Shweta	
	Department: Production	
	Salary: 26900	
	OR	
	Zack is working in a database named SPORT, in which he has created a	
	table named "Sports" containing columns SportId, SportName,	
	no_of_players, and category.	
	After creating the table, he realized that the attribute, category has to be	
	deleted from the table and a new attribute TypeSport of data type string	
	has to be added. This attribute TypeSport cannot be left blank. Help Zack	
	write the commands to complete both the tasks.	
25	Predict the output of the following code:	2

```
def Changer(P,Q=10):
          P=P/Q
          Q=P%Q
          return P
    A = 200
    B = 20
    A=Changer (A, B)
    print(A,B, sep='$')
    B=Changer (B)
    print(A,B, sep='$', end='###')
                          SECTION C
    Predict the output of the Python code given below:
26
                                                               3
     Text1="IND-23"
     Text2=""
     T=0
    while I<len(Text1):</pre>
         if Text1[I]>="0" and Text1[I]<="9":</pre>
             Val = int(Text1[I])
             Val = Val + 1
             Text2=Text2 + str(Val)
         elif Text1[I]>="A" and Text1[I]<="Z":</pre>
             Text2=Text2 + (Text1[I+1])
         else:
             Text2=Text2 + "*"
         I+=1
    print(Text2)
27
    Consider the table CLUB given below and write the output of the SQL
                                                             1*3=
                                                               3
    queries that follow.
          CNAME | AGE | GENDER
                                   SPORTS
                                               PAY
                                                    DOAPP
     CID
     5246 AMRITA
                    35
                        FEMALE
                                    CHESS
                                               900
                                                      2006-
```

03-27

	4687	SHYAM	37	MALE	CRICKET	1300	2004-	
							04-15	
	1245	MEENA	23	FEMALE	VOLLEYBAL	L 1000	2007-	
							06-18	
	1622	AMRIT	28	MALE	KARATE	1000	2007-	
							09-05	
	1256	AMINA	36	FEMALE	CHESS	1100	2003-	
							08-15	
	1720	MANJU	33	FEMALE	KARATE	1250	2004-	
							04-10	
	2321	VIRAT	35	MALE	CRICKET	1050	2005-	
							04-30	
	(i) SELECT COUNT(DISTINCT SPORTS) FROM CLUB;							
	(ii) SELECT CNAME, SPORTS FROM CLUB WHERE							
	DOAPP<"2006-04-30" AND CNAME LIKE "%NA";							
	(iii) SELECT CNAME, AGE, PAY FROM CLUB WHERE							
	GENDER = "MALE" AND PAY BETWEEN 1000 AND							
	1200;							
28	Write a function in Python to read a text file, Alpha.txt and displays						3	
	those li	ines which b	egin w	ith the word	'You'.			
				Ol	R			
	Write a	function, v	rowelC	Count() in	Python that cou	nts and disp	olays the	
	number of vowels in the text file named Poem.txt.							
29	Consider the table Personal given below:						1*3=	
	Table: Personal					3		
	P_ID	Nan	1e	Desig	Salary	Allowance		
	P01	Roh	it	Manager	89000	4800		

P02	Kashish	Clerk	NULL	1600
P03	Mahesh	Superviser	48000	NULL
P04	Salil	Clerk	31000	1900
P05	Ravina	Superviser	NULL	2100

Based on the given table, write SQL queries for the following:

- (i) Increase the salary by 5% of personals whose allowance is known.
- (ii) Display Name and Total Salary (sum of Salary and Allowance) of all personals. The column heading 'Total Salary' should also be displayed.
- (iii) Delete the record of personals who have salary greater than 25000

A list, NList contains following record as list elements:

[City, Country, distance from Delhi]

Each of these records are nested together to form a nested list. Write the following user defined functions in Python to perform the specified operations on the stack named travel.

- (i) Push_element (NList): It takes the nested list as an argument and pushes a list object containing name of the city and country, which are not in India and distance is less than 3500 km from Delhi.
- (ii) **Pop_element():** It pops the objects from the stack and displays them. Also, the function should display "Stack Empty" when there are no elements in the stack.

For example: If the nested list contains the following data:

```
NList=[["New York", "U.S.A.", 11734],
["Naypyidaw", "Myanmar", 3219],
["Dubai", "UAE", 2194],
["London", "England", 6693],
```

3

```
["Gangtok", "India", 1580],
["Columbo", "Sri Lanka", 3405]]

The stack should contain:
['Naypyidaw', 'Myanmar'],
['Dubai', 'UAE'],
['Columbo', 'Sri Lanka']

The output should be:
['Columbo', 'Sri Lanka']
['Dubai', 'UAE']
['Dubai', 'UAE']
['Naypyidaw', 'Myanmar']

Stack Empty
```

SECTION D

31 Consider the tables PRODUCT and BRAND given below:

1*4= 4

Table: PRODUCT

PCode	PName	UPrice	Rating	BID
P01	Shampoo	120	6	M03
P02	Toothpaste	54	8	M02
P03	Soap	25	7	M03
P04	Toothpaste	65	4	M04
P05	Soap	38	5	M05
P06	Shampoo	245	6	M05


Table: BRAND

BID	BName
M02	Dant Kanti
M03	Medimix
M04	Pepsodent
M05	Dove

	Write SQL queries for the following:				
	(i) Display product name and brand name from the tables PRODUCT				
	and BRAND.				
	(ii) Display the structure of the table PRODUCT.				
	(iii) Display the average rating of Medimix and Dove brands				
	(iv) Display the name, price, and rating of products in descending order				
	of rating.				
32	Vedansh is a Python programmer working in a school. For the Annual	4			
	Sports Event, he has created a csv file named Result.csv, to store the				
	results of students in different sports events. The structure of Result.csv				
	is:				
	[St_Id, St_Name, Game_Name, Result]				
	Where				
	St_Id is Student ID (integer)				
	ST_name is Student Name (string)				
	Game_Name is name of game in which student is participating(string)				
	Result is result of the game whose value can be either 'Won', 'Lost'				
	or 'Tie'				
	For efficiently maintaining data of the event, Vedansh wants to write the				
	following user defined functions:				
	Accept () – to accept a record from the user and add it to the file				
	Result.csv. The column headings should also be added on top of the csv				
	file.				
	wonCount () — to count the number of students who have won any event.				
	As a Python expert, help him complete the task.				
	SECTION E				

Meticulous EduServe is an educational organization. It is planning to setup its India campus at Chennai with its head office at Delhi. The Chennai campus has 4 main buildings – ADMIN, ENGINEERING, BUSINESS and MEDIA

1*5= 5



Block to Block distances (in Mtrs.)

From	То	Distance
ADMIN	ENGINEERING	55 m
ADMIN	BUSINESS	90 m
ADMIN	MEDIA	50 m
ENGINEERING	BUSINESS	55 m
ENGINEERING	MEDIA	50 m
BUSINESS	MEDIA	45 m
DELHI HEAD	CHENNAI	2175 km
OFFICE	CAMPUS	

Number of computers in each of the blocks/Center is as follows:

ADMIN	110
ENGINEERING	75
BUSINESS	40
MEDIA	12
DELHI HEAD	20

a) Suggest and draw the cable layout to efficiently connect various blocks of buildings within the CHENNAI campus for connecting the digital devices.

	b) Which network device will be used to connect computers in each block to	
	form a local area network?	
	c) Which block, in Chennai Campus should be made the server? Justify your	
	answer.	
	d) Which fast and very effective wireless transmission medium	
	should preferably be used to connect the head office at DELHI with the	
	campus in CHENNAI?	
	e) Is there a requirement of a repeater in the given cable layout? Why/	
	Why not?	
34	(i) Differentiate between r+ and w+ file modes in Python.	2+3=
	(ii) Consider a file, SPORT. DAT, containing records of the following	5
	structure:	
	[SportName, TeamName, No_Players]	
	Write a function, copyData(), that reads contents from the file	
	SPORT. DAT and copies the records with Sport name as "Basket Ball"	
	to the file named BASKET. DAT. The function should return the total	
	number of records copied to the file BASKET.DAT.	
	OR	
	(i) How are text files different from binary files?	
	(ii) A Binary file, CINEMA. DAT has the following structure:	
	{MNO:[MNAME, MTYPE]}	
	Where	
	MNO - Movie Number	
	MNAME – Movie Name	
	MTYPE is Movie Type	
	Write a user defined function, findType (mtype), that accepts mtype	
	as parameter and displays all the records from the binary file	
	CINEMA. DAT, that have the value of Movie Type as mtype.	
35	(i) Define the term Domain with respect to RDBMS. Give one example	1+4=
	to support your answer.	5

- (ii) Kabir wants to write a program in Python to insert the following record in the table named Student in MYSQL database, SCHOOL:
 - rno(Roll number)-integer
 - name(Name) string
 - DOB (Date of birth) Date
 - Fee -float

Note the following to establish connectivity between Python and MySQL:

- Username root
- Password tiger
- Host localhost

The values of fields rno, name, DOB and fee has to be accepted from the user. Help Kabir to write the program in Python.

OR

- (i) Give one difference between alternate key and candidate key.
- (ii) Sartaj has created a table named Student in MYSQL database, SCHOOL:
 - rno(Roll number)-integer
 - name(Name) string
 - DOB (Date of birth) Date
 - Fee − float

Note the following to establish connectivity between Python and MySQL:

- Username root
- Password tiger
- Host localhost

Sartaj, now wants to display the records of students whose fee is more than	
5000. Help Sartaj to write the program in Python.	

Class XII

Computer Science (083)

Marking Scheme

Time Allowed: 3 hours MM: 70

Question and Answers	Distribution of Marks	Total Marks
SECTION A	,	
False	1 mark for	1
	correct	
	answer	
Option b	1 mark for	1
6.20	correct	
0,20	answer	
Option c	1 mark for	1
	correct	
-244.0	answer	
PYTHON-is-Fun	1 mark for	1
	correct	
	answer	
Option b	1 mark for	1
Q 15	correct	
8,13	answer	
Option a	1 mark for	1
DAN	correct	
TAIN	answer	
Option b	1 mark for	1
	correct	
del D1["Red"]	answer	
Ontion b	1 mark for	1
	answer	
	False Option b 6,20 Option c -244.0 PYTHON-is-Fun Option b 8,15 Option a PAN Option b	False SECTION A False 1 mark for correct answer Option b 6,20 Option c -244.0 PYTHON-is-Fun 1 mark for correct answer Option b 8,15 Option a PAN Option a PAN Option b del D1 ["Red"] Option b 1 mark for correct answer I mark for correct answer

	ceieP0		
9	Option d	1 mark for	1
	Statement 4	correct	
10	Option b	1 mark for	1
	WHITE*	correct answer	
	BLACK*		
11	Option b	1 mark for	1
	Modulator	correct	
12	Option c	1 mark for	1
	global b	correct	
13	True	1 mark for correct answer	1
14	Option c	1 mark for correct	1
	A candidate key that is not a primary key is a foreign key.	answer	
15	Circuit	1 mark for correct answer	1
16	Option c	1 mark for correct	1
	seek()	answer	
17	Option d A is false but R is True	1 mark for correct answer	1

18	Option b	1 mark for	1
	Both A and R are true but R is not the correct explanation for A	correct	
	SECTION B		
19	(i) POP3 – Post Office Protocol 3 URL – Uniform Resource Locator (ii) HTML(Hyper text mark Up language) • We use pre-defined tags • Static web development language – only focuses on how data looks • It use for only displaying data, cannot transport data • Not case sensistive XML (Extensible Markup Language) • we can define our own tags and use them • Dynamic web development language – as it is used for transporting and storing data • Case sensitive OR	½ mark for each correct expansion 1 mark for any one correct difference No mark to be awarded if only full form is given	1+1=2
	(i) Bandwidth is the maximum rate of data transfer over a given transmission medium. / The amount of information that can be transmitted over a network.	1 mark for correct definition	

(ii)	https (Hyper Text Transfer Protocol Secure) is the protocol that uses SSL (Secure Socket Layer) to encrypt data being transmitted over the Internet. Therefore, https helps in secure browsing while http does not.	1 mark for correct difference.	
rev rem whi	<pre>Number(num): = 0 = 0 le num > 0: rem =num %10 rev = rev*10 + rem num = num//10 urn rev evNumber(1234))</pre>	½ mark for each correction made	2
def countN for pl	"Delhi",2:"London",3:"Paris",4:"New York",5:"Dubai"} low(PLACES): ace in PLACES.values(): len(place)>5: print(place.upper()) PLACES) OR	½ mark for correct function header ½ mark for correct loop ½ mark for correct if statement ½ mark for displaying the output ½ mark for correct function header ½ mark for using split()	2


	<pre>def lenWords(STRING): T=() L=STRING.split() for word in L: length=len(word) T=T+(length,) return T</pre>	½ mark for adding to tuple ½ mark for return statement	
	Note: Any other correct logic may be marked		
22	4*L 33*4 21*S 10*6	½ mark for each correct line of output	2
23	(i) L1.insert(2,200) (ii) message.endswith('.')	1 mark for each correct statement	1+1=2
	OR		
	<pre>import statistics print(statistics.mode(studentAge))</pre>	1 mark for correct import statement 1 mark for correct command with mode() and print()	
24	SQL Command to add primary key: ALTER TABLE Employee ADD Empld INTEGER PRIMARY KEY;	1 mark for correct ALTER TABLE command	2

	As the primary key is added as the last field, the command for		
	inserting data will be:	1 mark for	
	INSERT INTO Employee	correct INSERT	
	VALUES ("Shweta", "Production", 26900, 999);	command	
	Alternative answer:		
	INSERT INTO		
	Employee (EmpId, Ename, Department, Salary)		
	VALUES (999, "Shweta", "Production", 26900);		
	OR		
	To delete the attribute, category:		
	ALTER TABLE Sports	1 mark for	
	DROP category;	correct ALTER TABLE	
	Brot caeegory,	command	
	To add the attribute, TypeSport	with DROP	
	To add the attribute, Typesport	1 mark for	
	AIMED MADIE Coorts	correct ALTER TABLE	
	ALTER TABLE Sports	command	
	ADD TypeSport char(10) NOT NULL;	with ADD	
25	10.0\$20	1 mark for	2
	10.0\$2.0###	each correct line of output	
		inic or output	
	SECTION C		
26	ND-*34	½ mark for	3
		each correct character	
27		Character	
27		ı	
		1 mark for each correct	1*3=3
	(i)	output	
	COUNT (DISTINCT SPORTS)		

4 (ii) **CNAME** SPORTS AMINA CHESS (iii) **CNAME** AGE PAY 28 1000 AMRIT 35 1050 VIRAT 1 mark for 28 def test(): correctly fObj1 = open("Alpha.txt","r") opening and data = f0bj1.readlines() closing files for line in data: L=line.split() ½ mark for if L[0] == "You": correctly reading data print(line) fObj1.close() 1 mark for correct loop and if statement OR ½ mark for displaying data 1 mark for correctly opening and closing the files

```
½ mark for
     def vowelCount():
                                                       correctly
           fObj = open("Alpha.txt", "r")
                                                       reading data
           data = str(fObj.read())
                                                       1 mark for
           cnt=0
                                                       correct loop
           for ch in data:
                                                       and if
                 if ch in "aeiouAEIOU":
                                                       statement
                      cnt=cnt+1
                                                       ½ mark for
           print(cnt)
                                                       displaying
           fObj.close()
                                                       the output.
     Note: Any other correct logic may be marked
29
       (i)
                                                       1 mark for
                                                                  1*3=3
                                                       each correct
            UPDATE Personal
                                                       query
            SET Salary=Salary + Salary*0.5
            WHERE Allowance IS NOT NULL;
       (ii)
            SELECT Name, Salary + Allowance AS
            "Total Salary" FROM Personal;
       (iii)
            DELETE FROM Personal
            WHERE Salary>25000
```

```
30
                                                      1 ½ marks for
                                                                   3
     travel = []
                                                      each function
     def Push element(NList):
          for L in NList:
              if L[1] != "India" and L[2]<3500:</pre>
                   travel.append([L[0],L[1]])
     def Pop element():
         while len(travel):
              print(travel.pop())
          else:
              print("Stack Empty")
                            SECTION D
       (i)
31
                                                       1 mark for
                                                                 1*4=4
                                                      each correct
            SELECT PName, BName FROM PRODUCT P,
                                                      query
            BRAND B WHERE P.BID=B.BID;
       (ii)
            DESC PRODUCT;
       (iii)
            SELECT BName, AVG(Rating) FROM PRODUCT
            P, BRAND B
            WHERE P.BID=B.BID
            GROUP BY BName
            HAVING BName='Medimix' OR
            BName='Dove';
       (iv)
            SELECT PName, UPrice, Rating
            FROM PRODUCT
           ORDER BY Rating DESC;
```



	b) Switch		
	c) Admin block, as it has maximum number of computers.		
	d) Microwave		
	e) No, a repeater is not required in the given cable layout as the		
	length of transmission medium between any two blocks does not		
	exceed 70 m.		
34	r+ mode:	1 mark for each correct difference	2+3=5
	Primary function is reading File and the state of t	(minimum	
	File pointer is at beginning of file	two differences	
	• if the file does not exist, it results in an error	should be	
	w+ mode:	given)	
	 primary function is writing 		
	• if the file does not exist, it creates a new file.		
	• If the file exists, previous data is overwritten		
	• File pointer is at the beginning of file		
	(ii)	½ mark for correctly opening and closing files ½ mark for correct try	
		and except block 1/2 mark for correct loop 1 mark for correctly copying data	

```
½ mark for
def copyData():
     fObj = open("SPORT.DAT", "rb")
                                                             correct
     fObj1 = open("BASKET.DAT", "wb")
                                                            return
     cnt=0
                                                            statement
     try:
           while True:
                data = pickle.load(f0bj)
                                                            ½ mark for
                print(data)
                                                            correctly
                if data[0] == "Basket Ball":
                                                             opening and
                      pickle.dump(data,f0bj1)
                                                             closing files
                      cnt+=1
     except:
                                                            ½ mark for
           fObj.close()
                                                            correct try
           fObj1.close()
                                                             and except
     return cnt
                                                            block
                                                            ½ mark for
                                                            correct loop
                                                            ½ mark for
                           OR
                                                            correct if
  (i)
        Text files:
                                                            statement
        • Extension is .txt
                                                             1 mark for
                                                            correctly
        • Data is stored in ASCII format that is human readable
                                                            displaying
        • Has EOL character that terminates each line of data
                                                             data
           stored in the text files
        Binary Files
        • Extension is .dat
        • Data is stored in binary form (0s and 1s), that is not
          human readable.
  (ii)
```

```
def Searchtype (mtype):
             fObj = open("CINEMA.DAT", "rb")
             try:
                   while True:
                         data = pickle.load(f0bj)
                         if data[2] == mtype:
                               print("Movie number:",data[0])
                               print("Movie Name:", data[1])
                               print("Movie Type:",data[2])
             except EOFError:
                   fObj.close()
       Note: Any other correct logic may be marked
35
                 Domain is a set of values from which an attribute can
                                                                               ½ mark for
                                                                                               1+4=5
          (i)
                                                                               correct
                 take value in each row. For example, roll no field can
                                                                               definition
                 have only integer values and so its domain is a set of
                                                                               ½ mark for
                 integer values
                                                                               correct
                                                                                example
          (ii)
       import mysql.connector as mysql
                                                                               ½ mark for
       con1 = mysql.connect(host="localhost", user="root", password="tiger", database="sample2023")
                                                                               importing
       mycursor=con1.cursor()
                                                                                correct
       rno = int(input("Enter Roll Number:: "))
                                                                                module
       name = input("Enter the name:: ")
       DOB = input("Enter date of birth:: ")
                                                                                1 mark for
       fee= float(input("Enter Fee:: "))
                                                                                correct
       query = "INSERT into student values({},'{}','{}','{}}".format(rno,name,DOB,fee)
                                                                               connect()
       mycursor.execute(query)
       con1.commit()
                                                                               ½ mark for
       print("Data added successfully")
                                                                                correctly
       con1.close()
                                                                                accepting the
                                                                               input
       Note: Any other correct logic may be marked
                                                                               1 ½ mark for
                                                                               correctly
```

		executing the query
	<u>OR</u>	½ mark for correctly using commit()
(i)	All keys that have the properties to become a primary key are candidate keys. The candidate keys that do not	
(ii)	become primary keys are alternate keys.	1 mark for correct difference
mycursor=co query = "SE mycursor.ex	LECT * FROM student where fee>{}".format(5000) ecute(query) or.fetchall() data: ec)	½ mark for importing correct module 1 mark for correct connect()
		1 mark for correctly executing the query
		½ mark for correctly using fetchall()
		1 mark for correctly

	displaying	
	data	

KENDRIYA VIDYALAYA SANGATHAN AGRA REGION FIRST PRE BOARD EXAMINATION (2023-24)

CLASS: XII SUBJECT: COMPUTER SCIENCE (083) TIME: 03 HOURS

MAXIMUM MARKS: 70

General instructions:

- 1. Please check this question paper contains 35 questions.
- 2. The paper is divided into 4 Sections- A, B, C, D and E.
- 3. Section A, consists of 18 questions (1 to 18). Each question carries 1 Mark.
- 4. Section B, consists of 7 questions (19 to 25). Each question carries 2 Marks.
- 5. Section C, consists of 5 questions (26 to 30). Each question carries 3 Marks.
- 6. Section D, consists of 2 questions (31 to 32). Each question carries 4 Marks.
- 7. Section E, consists of 3 questions (33 to 35). Each question carries 5 Marks.
- 8. All programming questions are to be answered using Python Language only.

	SECTION A	
Q1	What will be the evaluation of python expression – 2*2**3**2+2	1
	a) 130 b) 1026 c) 258 d) 68	
Q2	Which of the following is not a valid identifier in python?	1
	a) Def b) false c) True d) print	
Q3	Given a string s = 'Happy Diwali', what will be the value of string slice s[::-2]?	1
	a) iai pa b) HpyDwl c) lwDypH d) iaiypH	description of
Q4	Which among the following is/are mutable data types in python?	1
	a) list b) tuple c) string d) boolean	3.
Q5	Which python statement will delete all elements of a dictionary named d?	1
	a) d.delete(all) b) d.delete() c) d.clear() d) d.empty()	
Q6	The return type of the print() function is:	1
	a) string b) integer c) list d) None	
Q7	Consider a tuple $t = (10, 15, [20, 25], 30, 35)$. Identify the statement that will result in an error.	1
	a) print(t[2]) b) t[2][0] = 200 c) t[3] = 300 d) print(len(t))	•
Q8	Which of the following symbols is not an operator in python?	1
	a) // b) * c) ~ d) \$	
Q9	Which of the following transmission media does not use electric signals to carry data?	
	a) Twisted Pair Cable b) Optical Fiber c) Co-axial cable d) None of the above	1

1	2	3	4	5 6	7 8	Page 1 of 10	11	12	13	14	15	16 17
b	C	α	a	c d	c d	b 5		6	C			

all a fe	Which of the following connector is used for Ethernet cables in a LAN?	11
Q10	a) RIII b) RI45 c) ETHO d) F Connector	
Q11	Which two of the following queries are not valid in MySQL?	1
	a) select gender, count(*) form students having age >15;	A CONTRACTOR OF THE CONTRACTOR
	b) select gender, count(*) from students where age>15 group by gender;	
	c) select gender, sum(age) from students group by gender having sum(age)>25;	50
	d) select gender, max(age) from students group by gender order by max(age);	
Q12	Which of the following is not a DDL command in SQL?	1
	a) ALTER b) UPDATE c) DROP d) CREATE	
Q13	If a MySQL table named A has 5 columns and 6 rows and another table B has 3 columns and 4	1
Topic Control	rows, then what will be the degree and cardinality of the cartesian product of A and B?	*
	a) 15, 24 b) 8, 10 c) 8, 24 d) 5,24	
Q14	Which of the following is the unit used to measure data transfer rate of a computer network?	1
	a) mps b) bps c) Hertz (Hz) d) None of these	
Q15	Which of the following keyword is used along with try block to handle exceptions.	1
	a) catch b) handle c) follow d) except	
Q16	Which of the following are not correct ways of opening a text file in python?	1
	a) F = open('story.txt', 'read')	
Allege	b) with open('story.txt') as F:	
	c) F = open('story.txt', 'a+')	
	d) Open(F) = 'story.txt'	
	Q17 and 18 are ASSERTION AND REASONING based questions. Mark the correct choice as	***************************************
The second	a) Both A and R are true and R is the correct explanation for A	
	b) Both A and R are true and R is not the correct explanation for A	
	c) A is True but R is False	
	d) A is false but R is True	
Q17	Answer with (a) to (d) given above.	1
	Assertion (A): A function definition can have zero parameters/formal arguments.	1
	Reasoning (R): Parenthesis are not mandatory to call a function with zero arguments.	
	C-nicins.	
		1

Q18	Answer with (a) to (d) given above.	1
	Assertion (A): Number of arguments passed to a function may not match the number of	
	parameters in the function definition.	
	Reasoning (R): Function parameters can have default values.	
	SECTION B	1
Q19	a) Expand the following abbreviations:	2
	i) VoIP ii) XML	
	b) Name one protocol that can be used to access a computer remotely.	
	OR	
	Compare twisted pair cable and fiber optic cable based on - speed, cost, electromagnetic	
	interference and distance.	
Q20	Sameer has written a python program to count the occurrences of elements of a list using a dictionary. But the code has some syntax and logical errors. Re-write the code after removing all such errors and underline your corrections.	2
	$L = [1,2,1,1,2,1,2,3,5,4,1,2,5,4,4,5]$ $D = \{\}$	
	foreach x in L: if x in D:	
	D[x]=+1	
	Else: $D(x)=1$	
Q21	Write a function modifyList(L,n) in Python, which accepts a list L of numbers and n is a numeric	
	value. Function should:	
	Add 5 to all the values divisible by n	
	Subtract 5 from all values not divisible by n	
	Display the modified list	
		Section / herry
	Example:	
	Example: If L= [10,11,13,15,20,2] and n=5 then the function should print [15,6,8,20,25,-3]	
	If L= [10,11,13,15,20,2] and n=5 then the function should print [15,6,8,20,25,-3]	
	If L= [10,11,13,15,20,2] and n=5 then the function should print [15,6,8,20,25,-3] OR	

```
Predict the output of following python code:
Q22
      S = "BHARAT"
      D = \{\}
      for i in range(len(S)):
            if i%2==0:
                   D[S[i]] = i+1
            else:
                    D[S[i]] = i-1
       for k, v in D. items():
            print(k, v, sep="#")
Q23
       Consider a List L = [10,20,30,[40,50,60],70,80]
                                                                                                  2
       Write a single line python statement (using List methods only) to:
            i. Insert an element 55 as the second last element of the inner list, so that L becomes
              [10,20,30,[40,50,55,60],70,80]
            ii. Delete the inner list so the L becomes [10,20,30,70,80]
 Q24
       Consider a MySQL table named "Students" with columns - RollNo, Name, Marks.
                                                                                                1 x 2
       Write SQL commands to:
                                                                                                = 2
            (i) Add a new column named 'Phone' to store the phone number of the students.
             (ii) Set RollNo as the primary key of the table.
        Consider a MySQL table named "Books" with columns - BookID, BookName, Pages, Price,
        Rating. The rating column has data type INT.
        Write SQL commands to:
              (i) Change the data type of rating column to allow for floating point values (1.0 to 5.0)
             (ii) Delete the pages column from the database.
  Q25
        Write the output of the following python code.
                                                                                                  2
        def runme(x=1, y=2):
            x = x + y
            y+=1
            print(x, '$', y)
            return x, y
        a,b = runme()
        print(a, '#', b)
         runme (a, b)
                                              SECTION C
```

```
Q26
      Write the output of the following python code.
                                                                                              3
      def change (msg):
          n = len(msg)
          new msg = ''
          for i in range (0,n):
              if not msg[i].isalpha():
                  new msg = new msg + '@'
              else:
                  if msg[i].isupper():
                      new msg = new msg + msg[i]*2
                   else:
                       new msg = new msg + msg[i]
           return new msg
       new msg = change("15 New Men")
       print (new msg)
       Consider the table given below and write the output of SQL queries (i) to (iii).
                                                                                              1 \times 3
 O27
                                                                                              =3
                                        TABLE: PLAYERS
                                                            DoB
                                                                            Salary
                                        Game
                                                   Gender
                P ID
                        Name
                                                             1990-12-08
                                                                             12500
                        Virat Kohli
                                        Cricket
                                                      M
                 101
                                                             1993-01-12
                                                                             9000
                 102
                        PV Sindhu
                                        Badminton
                                                      F
                                                             1988-01-05
                                                                             10000
                                        Cricket
                                                      M
                        Rahul Sharma
                 103
                                                             1990-12-25
                                                                             8500
                                        Badminton
                                                      F
                 104
                        Saina Nehwal
                                                             1985-06-16
                                                                             10000
                                                      M
                                        Snooker
                        Pankaj Advani
                 105
                                                             1994-10-10
                                                                             12500
                                                       F
                                        Cricket
                 106
                        Harmanpreet
                                                             1982-11-09
                                                                              9000
                                                      M
                                        Hockey
                 107
                        Sardar Singh
                                                             1982-11-01
                                                                             12000
                                        Chess
                        V Anand
                  108
               i. Select Name, Salary from players where Game not in ('cricket', 'chess');
              ii. Select sum(Salary) from players where Name like '%i';
              iii. Select count(distinct Game) from players;
        Neha has a very large text file named 'log_report.txt' which contains more than 50,000 log
  Q28
        entries for logins on a local ssh server. Following is a truncated view of the file log_report.txt.
        2022-10-14:22:40:39 Login failed > from 192.168.11.16
        2022-10-14:22:20:19 Login success > from 192.168.11.220
        2022-10-14:10:14:40 Login success > from 192.168.0.66
        2022-10-13:11:19:17 Login failed > from 192.168.0.45
        2022-10-14:22:40:39 Login success > from 192.168.11.156
```

British Proposition of the Personal	Neha has asked you to help her count the number of failed login attempts. Write a function
Continue or other Designation of the last	countFailedAttempts() in python to count the number of lines containing the word 'failed' in
	the text file 'log_report.txt'.

OR

Rajat is working on a language statistics project. He has to analyze the writings of a famous English novelist. He has downloaded a text file named 'russel.txt' containing major writings of the author. He is stuck at the problem of counting the number of words starting with 'th' or 'Th'. Being a computer science student, help Rajat by writing a function **countWords()** in python to count the number of words starting with 'Th' or 'th' in the text file 'russel.txt'.

3

3

Q29 Consider the table Employees Given below and write SQL queries (i) to (iii) based on it.

Table: Employees

emp_id	name	dob	gender	salary
101	Simar	1994-01-15	F	26000
102	Alok	1995-10-18	M	17000
103	Hasan	1996-08-21	М	25000
104	Kriti	1993-01-12	F	35000
105	Gulab	1994-02-20	M	NULL
106	Jaya	1993-12-01	F	16500

- To increase the salary of all Female employees by 10%.
- ii. To display the name and gender of employees for whom salary is NULL.
- iii. To delete the records of all employees born before 01 January 1995.
- Q30 Consider a Nested List 'Inventory' in which all the elements are lists of the format [ItemID, ItemName, Price, Quantity]. Write the following user defined functions in python to perform the task specified on the stack named 'items' which is initially an empty list.
 - Push_item(Inventory) It takes nested list Inventory as argument and pushes records of those items onto stack which have quantity > 100.
 - Pop_items() -It repeatedly pops the top element of stack and displays it. Appropriate
 message should be displayed when there are no more elements left in the stack.

For example, if

Inventory = [[101, 'Pen', 10, 120],

[102, 'Pencil', 10, 100],

[103, 'Eraser', 5, 90],

[104, 'Notebook', 20, 52],

[105, 'Marker', 30, 130],

[106, 'Sharpener', 5, 110],]

After execution of Push_Items(Inventory), Stack should contain:

[[101, 'Pen', 10, 120], [105, 'Marker', 30, 130], [106, 'Sharpener', 5, 110]] \leftarrow Top

The output after Pop Items() should be:

[106, 'Sharpener', 5, 110]

[105, 'Marker', 30, 130]

[101, 'Pen', 10, 120]

Stack Empty

SECTION D

Q31 Write the output of SQL queries (i) to (iv) based on the relations Employees and Departments given below:

Table: Employees

10	emp_id	name	dob	gender	salary	dept_id
STATE OF THE PARTY	101	Simar	1994-01-15	F	26000	1
	102	Alok	1995-10-18	M	17000	2
	103	Hasan	1996-08-21	M	25000	1
Service of	104	Kriti	1993-01-12	F	35000	1
	105	Gulab	1994-02-20	M	15000	3
	106	Jaya	1993-12-01	F	16500	4

Table: Departments

dept_id	dept_name	dept_location
1	HR	GF-005
2	Sales	GF-006
3	Analysis	SF-204
4	Training	FF-102

4

- Display the Average Salary for Male and Female Employees. i. Display the Employee Name and Department Name for all employees in descending ii. order of their salary. Display the maximum salary of employees born after 31 December 1995. iii. Display the department id and number of employees for all departments having more iv. than 1 employee. Vijay has created a csv file 'FOOTBALL.CSV' to store player name, matches and goals scored. Q32 Write a program in python that defines and calls following user defined functions. i. addPlayer(name, matches, goals): Three parameters - name of the player, matches played and goals scored are passed to the function. The function should create a list object and append it to the csv file. ii. highestAverage(): The function should read the csv file and display the name of the player with the highest average goals (goals/matches). SECTION E Stalwart Solutions Pvt Ltd. is setting up its campus in Noida. The company campus will have 1 x 5 Q33 four blocks - Shivaji (S), Tagore (T), Ashoka (A) and Raman (R). The company has consulted =5you for networking at the campus. Suggest the best possible solutions for their questions (a) to (e) based on the information given below. Distance No. of Blocks Block (m) Computers Shivaji (S) 75 25 Shivaji to Tagore 125 Tagore (T) Shivaji to Ashoka 150 25 Ashoka(A) 125 Shivaji to Raman Raman (R) 20 75 Tagore to Ashoka 90 Tagore to Raman a) Suggest the most appropriate block to house the FTP server. Justify your answer. b) Which Hardware/Software can be installed prevent unauthorized access to FTP server? c) Suggest the best economical wired transmission medium and draw the cable layout
 - c) Suggest the best economical wired transmission medium and draw the cable layout diagram to connect the four blocks.
 - d) The company doesn't want to use any wired media for connecting the computers within the Raman block. Which device can be used to provide wireless access, given that all the machines in this block are wi-fi enabled.

	e) The company wishes to minimize the broadcast traffic in the LAN established. Keeping	
	this in mind, which device will you suggest to connect the computers inside every block	
	- hub or switch? Why?	
Q34	(i) What is the difference between text files and binary files?	2+:
ζ3 .	(ii) Shweta had stored all her passwords in one binary file named 'PASSWORDS.DAT'. The	= 5
	passwords were stored in following format:	
	[app_name, username, password] Write a function search(app) that accepts title as a parameter and displays the username and	
	그 그 그 그 그 그 그를 그렇게 하면 나를 다른 하는 것 같아. 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그	
	password for that particular app.	
	O.D.	
	OR	
	(i) What happens when we try to open a file that does not exist in rb, ab, rb+ and wb+ modes?	
	(ii) Consider a file named 'STUDENTS.DAT', containing records in following format:	
	[ADM_NO, NAME, CLASS, SECTION]	
	Write a function, filterStudents(clas, sec), which takes class and section as parameters and	
	copies the records matching with that class and section to a new file named 'FILTERED.DAT'.	
	copies the records matching with that class and section to a new the named Thereice.	
Q35	(i) What are the characteristics of a Primary key in RDBMS. Which attribute can act as a primary	1+
	key for a table storing details of all students of a school?	
	Civil I and the second sists the CDICKET Toble	
	(ii) Heerakh wants to write a program in python to add some records into the CRICKET Table	
	of SPORTS Database. The MySQL server is running on LOCALHOST and the login	
	credentials are as following:	
	Username – heerakh	
	Password – happy	
	The columns of the CRICKET table are described below:	
	pid (Player ID) – integer	
	pid (Player ID) – integer pname (Player Name) – string	
	pname (Player Name) – string	

Help her write a program, which will accept the player details from user and insert a new row into the table.

OR

- (i) What do you mean by term domain in context of RDBMS? What will be the domain for an attribute called 'age' of voters of a village?
- (ii) Keshav wants to write a program in python to display some records from the CRICKET Table of SPORTS Database. The MySQL server is running on LOCALHOST and the login credentials are as following:

Username - keshav

Password - karma

The columns of the CRICKET table are described below:

pid (Player ID) – integer

pname (Player Name) - string

innings (Innings Played) - integer

runs (Runs Scored) - integer

wickets (Wickets taken) - integer

Help him write a program, which will display the name (only name) of all players who have player 100 or more innings.

o End of Paper | o

KENDRIYA VIDYALAYA SANGATHAN AGRA REGION FIRST PRE BOARD EXAMINATION (2023-24)

CLASS: XII

SUBJECT: COMPUTER SCIENCE (083)

TIME: 03 HOURS
MAXIMUM MARKS: 70

[ANSWER KEY / MARKING SCHEME]

	SECTION A	
	(No marks for partially correct answers)	
Q1	b) 1026	1
Q2	c) True	1
Q3	a) iai pa	1
Q4	a) list	1
Q5	c) d.clear()	1
Q6	d) None	1
Q7	c) t[3] = 300	1
Q8	d) \$	1
Q9	b) Optic Fiber	1
Q10	b) RJ45	1
Q11	a) select gender, count(*) form students having age >15;	1
Q12	b) UPDATE	1
Q13	c) 8, 24	1
Q14	b) bps	1
Q15	d) except	1
Q16	a) F = open('story.txt', 'read')	1
	d) Open(F) = 'story.txt'	
	Q17 and 18 are ASSERTION AND REASONING based questions. Mark the correct choice as	
	a) Both A and R are true and R is the correct explanation for A	
	b) Both A and R are true and R is not the correct explanation for A	
	c) A is True but R is False	
	d) A is false but R is True	
Q17	c) A is True but R is False	1

Q18	a) Both A and R are true and R is the correct explanation for A	1		
	SECTION B			
Q19	a)	2		
	i) Voice over Internet Protocol ii) eXtensible Markup Language (½ + ½)			
	b) Telnet / SSH (1)			
	OR			
	½ Mark for each factor of comparison			
Q20	L = [1,2,1,1,2,1,2,3,5,4,1,2,5,4,4,5]	2		
	<pre>D = {} for x in L:</pre>			
	if x in D:			
	D[x] <u>+=</u> 1 <u>else:</u>			
	D[x]=1 (½ Mark for each correction)			
Q21	1 Mark for correct iterations	2		
Q21	1 Mark for correct modifications	2		
	OR			
	1 Mark for taking input and returning True or False			
	1 Mark for comparing the string with its reverse			
Q22	B#1	2		
	H#0			
	A#5			
	R#2			
	T#4			
Q23	i. L[3].insert(2, 55) (1 mark)	2		
	ii. L.pop(3) or L.pop(-3) or L.remove([40,50,55,60]) (1 mark)			
Q24	(i) ALTER TABLE Students ADD Phone INT; (1 mark)	1 x 2		
	(ii) ALTER TABLE Students ADD PRIMARY KEY (RollNo); (1 mark)	= 2		
	OR			
	(i) ALTER TABLE Books MODIFY rating DECIMAL(2,1); (1 mark)			
	(ii) ALTER TABLE Books DROP [COLUMN] pages; (1 mark)			
Q25	3 \$ 3	2		
	3 # 3			
	6 \$ 4			

	SECTION C	
Q26	@@@NNew@MMen	3
Q27	i.	1 x 3
	NameSalaryPV SindhuBadmintonSaina NehwalBadmintonPankaj AdvaniSnookerV AnandHockey	= 3
	ii. sum(Salary) 22500 iii. count(distinct Game) 5	
Q28	<pre>def countFailedAttempts(): f = open('log_report.txt') lines = f.readlines()</pre>	3
	c = 0 for line in lines: if 'failed' in line: #if line.split()[2] == 'failed' c+=1	
	f.close() return c #print(c) OR	
	def countWords():	
	f = open('russel.txt') words = f.read().split() c=0 for word in words: if word.startswith('th') or word.startswith('Th'): #if word[0:2] == 'th' or word[0:2] - 'Th'	
	c+=1	


	f.close()	
	return c #print(c)	
Q29	i. UPDATE Employees SET salary = salary + salry*0.1 WHERE gender = 'F';	3
	ii. SELECT name, gender from Employees WHERE salary is NULL;	
	iii. DELETE from Employees WHERE dob<'1995-01-01';	
Q30	def Push_item(Inventory):	3
	for item in Inventory:	
	if item[3]>100:	
	items.append(item)	
	def Pop_items():	
	try:	
	item = items.pop()	
	print(item)	
	except:	
	print("Stack Empty")	
	(or any other valid implementation)	
	SECTION D	
Q31	i. SELECT gender, avg(Salary) from Employees group by gender;	4
	ii. SELECT name, dept_name from Employees E and Departments D WHERE E.dept_id	
	= D.dept_id ORDER BY Salary DESC;	
	iii. SELECT max(Salary) FROM Employees WHERE dob>'1995-12-31';	
	iv. SELECT dept_id, count(*) from Employees GROUP BY dept_id HAVING	
	count(*)>1;	
Q32	def addPlayer(name, matches, goals):	4
	player_data = [name, matches, goals]	
	with open('FOOTBALL.CSV', 'a', newline=") as csvfile:	
	writer = csv.writer(csvfile)	
	writer.writerow(player_data)	
	def highestAverage():	

```
max\_average = 0
         best_player = "
         with open('FOOTBALL.CSV', 'r') as csvfile:
           reader = csv.reader(csvfile)
           next(reader) # Skip the header row if it exists
           for row in reader:
              name, matches, goals = row[0], int(row[1]), int(row[2])
              if matches > 0:
                average = goals / matches
                if average > max_average:
                  max_average = average
                  best_player = name
        if best_player:
           print(best_player)
         else:
           print("No player data found in the CSV file.")
                                              SECTION E
          a) Tagore, as it has maximum number of computers. Housing the server here will reduce
Q33
                                                                                                      1 x 5
```

Q33 a) Tagore, as it has maximum number of computers. Housing the server here will reduce 1 the external traffic.

= 5

- b) Firewall
- c) Ethernet Cable



- d) Wi-Fi Router / Access Points
- e) Switch, as hub will create the broadcast traffic.

```
(i) 1 Mark for 1 difference point
Q34
                                                                                                        2 + 3
                                                                                                        = 5
      (ii)
      import pickle
      def search(app):
           f = open('PASSWORDS.DAT', 'rb')
           while True:
                  try:
                      obj = pickle.load(f)
                      if obj[0] == app:
                              print(obj)
                              break
                   except:
                      break
            f.close()
                                                    OR
      (i) rb, rb+ will give error, while ab and wb+ modes will create the file (1/2 mark each)
      (ii)
      import pickle
      def filterStudents(clas, sec):
         fin = open('STUDENTS.DAT', 'rb')
         fout = open('FILTERED.DAT', 'wb')
         while True:
           try:
              stu = pickle.load(fin)
              if stu[2] == clas and stu[3] == sec:
                pickle.dump(stu, fout)
           except:
              break
```

```
Q35
      (i) \frac{1}{2} + \frac{1}{2}
                                                                                                             1 + 4
                                                                                                             =5
      import mysql.connector as ms
      conn = ms.connect(host="localhost",
                  user="heerakh",
                  passwd='happy',
                  db='sports')
      cur = conn.cursor()
      pid = int(input("Enter player ID : "))
      pname = input("Enter name : ")
      inn = int(input("Enter innings : "))
      runs = int(input("Runs Scored : "))
       wickets = int(input("Wickets : "))
      query = f"insert into cricket values({pid}, '{pname}', {innings}, {runs}, {wickets})"
      try:
         cur.execute(query)
         print("Row inserted")
      except:
         print("SQL Error")
      conn.close()
                                                      OR
      (i) \frac{1}{2} + \frac{1}{2}
      (ii)
      import mysql.connector as ms
      conn = ms.connect(host="localhost",
                  user="keshav",
                  passwd='karma',
                  db='sports')
      cur = conn.cursor()
      query = "select pname from cricket where innings>100"
      cur.execute(query)
      for row in cur.fetchall():
         print(row[0])
       conn.close()
```

o----| End of Paper |-----o

KENDRIYA VIDYALAYA SANGATHAN ERNAKULAM REGION PRE-BOARD EXAMINATION 2023-24 COMPUTER SCIENCE (083)

Time allowed: 3 Hours Maximum Marks: 70

General Instructions:

- Please check this question paper contains 35 questions.
- The paper is divided into 5 Sections- A, B, C, D and E.
- Section A, consists of 18 questions (1 to 18). Each question carries 1 Mark.
- Section B, consists of 7 questions (19 to 25). Each question carries 2 Marks.
- Section C, consists of 5 questions (26 to 30). Each question carries 3 Marks.
- Section D, consists of 2 questions (31 to 32). Each question carries 4 Marks.
- Section E, consists of 3 questions (33 to 35). Each question carries 5 Marks.
- All programming questions are to be answered using Python Language only.

Q.NO	QUESTION	MARKS
SECTION - A		
1	Which of the following is a keyword in Python?	
	a) true b) For c) pre-board d) False	1
2	What will be the output for the following Python statement? print(20//3*2+(35//7.0))	1
	a) 17.0 b) 17 c) 8.5 d) 8	
3	In MYSQL database, if a table, BOOK has degree 8 and cardinality 7, and another table, SALE has degree 4 and cardinality 7, what will be the degree and cardinality of the Cartesian product of BOOK and SALE? a) 32,49 b) 12,49 c) 12,14 d) 32,14	1
4	a) 32,49 b) 12,49 c) 12,14 d) 32,14 What is "C" stands in TCP/IP? a) Common b) Centre c)Control d) Coordinate	1
5	What is printed by the following statements? ANIMAL={"dog":10,"tiger":5,"elephant":15,"Cow":3} print("Tiger" not in ANIMAL) a) True b)False c)Error d) None	1
6	Consider the following statements and choose the correct output from the given options: EXAM="COMPUTER SCIENCE" print(EXAM[:12:-2]) a) EN b) CI c)SCIENCE d) ENCE	1
7	What will be the output of the following code? Tuple1=(10,)	1

	Tuple2=Tuple1*2	
	print(Tuple2)	
	a) 20 b) (20,) c) (10,10) d) Error	
8	Fill in the blanks:	
	The SQL keyword is used in SQL expression to select records	1
	based on patterns	
9	What possible outcome will be produced when the following code is executed?	
	import random	
	value=random.randint(0,3)	
	fruit=["APPLE","ORANGE","MANGO","GRAPE"]	
	for i in range(value):	
	print(fruit[i],end='##')	
	print()	
	a) APPLE##	1
	1.) ADDIE#	
	b) APPLE# ORANGE##	
	ORANGE##	
	c) APPLE## ORANGE##	
	, , , , , , , , , , , , , , , , , , , ,	
	d) ORANGE##	
	MANGO##	
	APPLE##	
10	Select the network device from the following, which connects, networks with	
	different protocols	1
	a) Bridge b)Gateway c)Hub d) Router	
11	State whether the following statement is TRUE or FALSE:	1
10	The value of the expression $4/3*(2-1)$ and $4/(3*(2-1))$ is the same	
12	In the relational models, cardinality actually refers to	1
	a) Number of tuples b) Number of attributes c) Number of tuples d) Number of autorium	1
13	c) Number of tables d) Number of constraints Data structure STACK is also known as list	
13	a)First In First Out b) First In Last Out	1
	c)Last In First Out d) Last In Last Out	1
14	Which function is used to write a list of strings in a file?	
17	a) writeline() b) writelines() c) write() d) writeall()	1
15	Which of the following is NOT a guided communication medium?	
	a) Twisted pair cable b) Microwave	1
	c) Coaxial cable d) Optical fibre	-
16	Which of the following function header is correct?	
	a) def fun(a=1,b):	
	b) def fun(a=1,b,c=2):	1
	c) def fun(a=1,b=1,c=2):	
	d) def fun(a=1,b=1,c=2,d):	
	Q17 and 18 are ASSERTION AND REASONING based questions. Mark the	
	correct choice as	
	(a) Both A and R are true and R is the correct explanation for A	
	(b) Both A and R are true and R is not the correct explanation for A.	
	(c) A is True but R is False	

	(d) A is false but R is True	
17	Assertion (A): In SQL, the aggregate function avg() calculates the average value on a set of values and produces a single result. Reason (R): The aggregate functions are used to perform some fundamental arithmetic tasks such as min(), max(), sum() etc	1
18	Assertion(A): Python overwrites an existing file or creates a non-existing file when we open a file with 'w' mode. Reason(R): a+ mode is used only for writing operations	1
	SECTION - B	
19	 i) Expand the following: a) SMTP b) VoIP ii) Give one disadvantage of Star topology OR i) What is a web browser ? ii) Define the term MAC Address 	1+1=2
20	Rewrite the following code in Python after removing all syntax error(s) and underline each correction done in the code . 30 = num for k in range(0,num) IF k%4==0: print(k*4) Else: print(k+3)	2
21	Write a function letter_count(lst) that takes a list of string and returns a dictionary where the keys are the letters from lst and the values are the number of times that letter appears in the lst. For example: if the passed list, lst is: lst=list("apple") Then it should return a dictionary as {'a':1,'p':2,'l':1,'e':1} OR Write a function max_length(), that takes a list of string as argument and display the longest string from the list.	2
22	Predict the output of the following code: lst=[2,4,6,8,10] for i in range(1,5): lst[i-1]=lst[i] for i in range(0,5): print(lst[i],end=' ')	2
23	Consider the following list of elements and write Python statement to print the output of each question. elements=['apple',200,300,'red','blue','grapes'] i) print(elements[3:5]) ii) print(elements[::-1])	2

	OR	
	Consider the following list exam and write Python statement for the following	
	questions:	
	exam=['english','physics','chemistry','cs','biology']	
	i) To insert subject "maths" as last element	
	ii) To display the list in reverse alphabetical order	
24	Satheesh has created a database "school" and table "student". Now he wants to	
	view all the databases present in his laptop. Help him to write SQL command	
	for that, also to view the structure of the table he created.	
	OR	2
	Magazi got confused with DDL and DML commands. Halp hou to calcut only	_
	Meera got confused with DDL and DML commands. Help her to select only DML command from the given list of command.	
	UPDATE, DROP TABLE, SELECT, CREATE TABLE, INSERT INTO,	
	DELETE, USE	
25	Predict the output for the following Python snippet	
	Troubt the output for the following Tython shipped	
	def calc(p,q=3):	
	ans=1	
	for x in range(q):	
	ans=ans*p	2
	return ans	
	power=calc(3)	
	print(power,'9')	
	power=calc(3,2)	
	print(power,'27')	
	SECTION C	
26	Predict the output of the Python code given below:	
	def calculate(str):	
	text="	
	x=range(len(str)-1)	
	for i in x:	
	if str[i].isupper():	
	text+=str[i]	
	elif str[i].islower():	3
	text+=str[i+1]	
	else:	
	text+='@'	
	return text	
	start='Pre-board Exam'	
	final=calculate(start)	
	print(final)	
	Print(iniai)	

	D_I			D_DEP		GENDER		ERIENCE	
	101	JOSEP:	H	ENT	1	MALE	10		
	104	GUPTA	A :	MEDIC	CINE I	MALE	12		
	106	SUMA	N	ORTHO) I	FEMALE	7		
	111	HANE	EF :	ENT	ı	MALE	12		
	123	DEEPT	TI .	CARDI	OLOGY I	FEMALE	6		
	132	VEENA SELECT D		SKIN		FEMALE	12		
	ii) iii)	AND EXPE SELECT DI SELECT D EXPERIEN	ISTINC _NAMI	CT(D_D	EPT) FROM			ORDER BY	
W O W	hich st R	function in Pyth tart with an alph function in Pyth	habet 'T	Γ'.					
	ext file	"DETAILS.tx: er the following	t".			or can w	ords pro	esent in a	
) C	ext file conside	"DETAILS.tx: er the following	t". Table '	"TEAC	CHER"		•	SALARY	
C	ext file	"DETAILS.tx	t".			D_O	JOIN /2002		
C	ext file conside	"DETAILS.tx: er the following NAME	t". Table '	"TEAC	CHER"	D_O ER 10/10	_ JOIN /2002	SALARY	
C	ext file conside T_ID 902	"DETAILS.tx: er the following NAME SANDEEP	Table GAGE	"TEAC	CHER" DEPT COMPUT	D_O_ ER 10/10	_ JOIN /2002	SALARY 56000	
	ext file consider T_ID 902 813	"DETAILS.tx: er the following NAME SANDEEP SANGEETA	Table 45 34	SEX M F	DEPT COMPUT HISTORY	D_O ER 10/10 24/9/2 4/5/20	_ JOIN /2002	SALARY 56000 50000	
	ext file consider to the consideration	"DETAILS.tx: er the following NAME SANDEEP SANGEETA JOEL	Table 45 45 48	SEX M F	DEPT COMPUT HISTORY ENGLISH	D_O_ER 10/10 24/9/2 4/5/20 27/09	_ JOIN /2002 2010 001 /2012	SALARY 56000 50000 67900	
	ext file donside T_ID 902 813 771 703	"DETAILS.tx: er the following NAME SANDEEP SANGEETA JOEL MANVITH	Table 'AGE 45 34 48 36	SEX M F M	DEPT COMPUT HISTORY ENGLISH MATHS	D_O_ER 10/10 24/9/2 4/5/20 27/09	JOIN /2002 2010 001 /2012 2013	SALARY 56000 50000 67900 48000	
	ext file fonside fonsi	"DETAILS.tx: or the following NAME SANDEEP SANGEETA JOEL MANVITH NEENA	Table 45 45 48 36 32	SEX M F M M F	DEPT COMPUT HISTORY ENGLISH MATHS ENGLISH	D_O_ER 10/10 24/9/2 4/5/20 27/09 23/5/2	JOIN /2002 2010 001 /2012 2013	SALARY 56000 50000 67900 48000 40000	
	ext file fonside fonsi	"DETAILS.tx: or the following NAME SANDEEP SANGEETA JOEL MANVITH NEENA ABHILASH	Table 45 45 48 36 32 42	SEX M F M M F	DEPT COMPUT HISTORY ENGLISH MATHS ENGLISH MATHS	D_O_ER 10/10 24/9/2 27/09 23/5/2 6/2/20 8/3/20	JOIN /2002 2010 001 /2012 2013	SALARY 56000 50000 67900 48000 40000 47000	
	ext file fonside fonsi	"DETAILS.tx: or the following NAME SANDEEP SANGEETA JOEL MANVITH NEENA ABHILASH MUHSIN	Table 4 AGE 45 34 48 36 32 42	SEX M F M M F M M H M	DEPT COMPUT HISTORY ENGLISH MATHS ENGLISH MATHS ENGLISH	D_O_ER 10/10 24/9/2 27/09 23/5/2 6/2/20 10/11	JOIN /2002 2010 001 /2012 2013 006 003 /1999	\$ALARY 56000 50000 67900 48000 40000 47000 70450	
	ext file donside T_ID 902 813 771 703 606 537 420 412	"DETAILS.tx: er the following NAME SANDEEP SANGEETA JOEL MANVITH NEENA ABHILASH MUHSIN SUBESH	Table 45 45 48 36 32 42 49 52	SEX M F M M F M M M M M	DEPT COMPUT HISTORY ENGLISH MATHS ENGLISH MATHS ENGLISH HINDI	D_O_ER 10/10 24/9/2 27/09 23/5/2 6/2/20 10/11	JOIN /2002 2010 001 /2012 2013 006 003 /1999 2010	\$ALARY 56000 50000 67900 48000 40000 47000 70450 60500	
	ext file fonside fonsi	"DETAILS.tx: or the following NAME SANDEEP SANGEETA JOEL MANVITH NEENA ABHILASH MUHSIN SUBESH RENJINI	Table 45 45 34 48 36 32 42 49 52 36	SEX M F M M F M M F M F F F F F M F F M F M F M F M M F M M F M M F M M F M M F M M F M M M F M M F M M M F M M M F M M M F M M M M F M M M M F M M M M F M M M M M F M M M M M M F M	DEPT COMPUT HISTORY ENGLISH MATHS ENGLISH MATHS ENGLISH HINDI COMPUT	ER 10/10 24/9// 27/09 23/5// 6/2/20 10/11 ER 27/4//	JOIN /2002 2010 001 /2012 2013 006 003 /1999 2010 016	\$ALARY 56000 50000 67900 48000 40000 47000 70450 60500 45000	

30	He want to by perform a) Pus b) Pop For If t	extract a ning the f sh the up and disp example he messa	all the upper collowing upper case alp play the co	er case I ser define the Best E P B A	etters separately ned function in I in the string into the stack. for your Pre-box	.Help h Python: a STA		3
31	Consider the	he table I	PRODUCT		LIENT given bel	ow:		
	PR_ID	PR_N	AME	1	UFACTURER	PRIC	E QTY	
	BS101	BATH	SOAP	PEAR	SE	45.00	25	
	SP210	SHAM	IPOO	SUN S	SILK	320.00) 10	
	SP235	SHAM	IPOO	DOVE	3	455.00) 15	
	BS120	BATH	SOAP	SANT	OOR	36.00	10	
	TB310	TOOT BRUS		COLC	SATE	48.00	15	
	FW422	FACE	WASH	DETC	D L	66.00	10	
	BS145	BATH	SOAP	DOVE	Ξ	38.00	20	4
					CLIENT			
	C ID		C NAMI	 E	CITY	PR	ID	
	01		DREAM :	MART	COCHIN	BS	_	
	02		SHOPRIX	ζ	DELHI	TB3	310	
	03		BIG BAZ		DELHI	SP2		
	04		LIVE LIF		CHENNAI	FW	422	
	Write SQL i)	-		_	e clients whose c	ity is Di	ELHI	
	ii)				th soap by 10	10, 10 2	ELIII	
	iii)				ucts having the l			
	iv)		the produce onding mate		price, client nan	ne and c	ity with their	
32	Gupta is w				csv file "emplo	vee.csv"	which will	
	contain use	er name a	ınd passwo	ord for d	epartment entrie	s. He ha	s written the	
	_	code . As	a program	imer, he	lp him to succes	sfully ex	xecute the given	
	task. import					#9	statement 1	
	def add en			ord):		113	ratement 1	4
	•		ee.csv', '	°])	# \$	statement 2	4
		=csv.writ			47)			
	f.close()		([username	z,passwo	oraj)			
	def read_e							
	with op	en ('emp	loyee.csv',	,'r') as f	île:			

content reader=csv.----(file) # statement 3 for row in content reader: print(row[0], row[1])file.close() add emp('mohan','emp123#') add emp('ravi','emp456#') read emp() #statement 4 i) Name the module he should import in statement 1 ii) In which mode, Gupta should open the file to add record in to the file ? (statement 2) Fill in the blank in statement 3 to read the record from a csv file iii) iv) What output will he obtain while executing statement 4? **SECTION E** 33 Oxford college, in Delhi is starting up the network between its different wings. There are four Buildings named as SENIOR, JUNIOR, ADMIN and HOSTEL as shown below: **ADMIN** HOSTEL **JUNIOR** SENIOR The distance between various building is as follows: ADMIN TO SENIOR 200 m ADMIN TO JUNIOR 150 m ADMIN TO HOSTEL 50 m SENIOR TO JUNIOR 250 m SENIOR TO HOSTEL 350 m JUNIOR TO HOSTEL 350 m Number of computer in each building is: 5 **SENIOR** 130 JUNIOR 80 ADMIN 160 HOSTEL 50 i) Suggest the cable layout of connections between the buildings. ii) Suggest the most suitable place (i.e., building) to house the server of this college, provide a suitable reason. iii) Is there a requirement of a repeater in the given cable layout? Why/ Why not? Suggest the placement of hub/switch with justification. iv) The organisation also has inquiry office in another city about 50-60 v) km away in hilly region. Suggest the suitable transmission media to interconnect to college and inquiry office out of the following: a. Fiber optic cable b. Microwave c. Radiowave

34 i) ii) ii) ii)	What is Pickling or Serialization? A binary file "salary.DAT" has structure [employee id, employee name, salary]. Write a function countrec() in Python that would read contents of the file "salary.DAT" and display the details of those employee whose salary is above 20000. OR What is the difference between 'r' and 'rb' mode in Python file? A binary file "STUDENT.DAT" has structure [admission_number, Name, Percentage]. Write a function countrec() in Python that would read contents of the file "STUDENT.DAT" and display the details of those students whose percentage is above 90. Also display number	2+3=5
	of students scoring above 90%	
con cur- cur- data for	What do you mean by a Primary key in RDBMS? Complete the following database connectivity program by writing the missing statements and performing the given query port ————————————————————————————————————	1+4=5

KENDRIYA VIDYALAYA SANGATHAN ERNAKULAM REGION

1st PRE BOARD EXAMINATION 2023 – 24

COMPUTER SCIENCE (083)

Class: XII

Time allowed: 3 Hours Maximum Marks: 70

MARKING SCHEME

Q.NO	QUESTION						
	SECTION - A						
1	Which of the following is a keyword in Python? a) true b) For c) pre-board d) False	1					
2	What will be the output for the following Python statement?						
	print(20//3*2+(35//7.0))	1					
	a) 17.0 b) 17 c) 8.5 d) 8						
3	In MYSQL database, if a table, BOOK has degree 8 and cardinality 7, and another table, SALE has degree 4 and cardinality 7, what will be the degree and cardinality of the Cartesian product of BOOK and SALE?	1					
4	b) 32, 49 b) 12, 49 c) 12,14 d) 32,14 What is "C" stands in TCP/IP? a) Common b) Centre c)Control d) Coordinate	1					
5	What is printed by the following statements? ANIMAL={"dog":10,"tiger":5,"elephant":15,"Cow":3} print("Tiger" not in ANIMAL)	1					
6	a) True b)False c)Error d) None Consider the following statements and choose the correct output from the given options: EXAM="COMPUTER SCIENCE" print(EXAM[:12:-2])	1					
7	a) EN b) CI c)SCIENCE d) ENCE						
7	What will be the output of the following code? Tuple1=(10,) Tuple2=Tuple1*2 print(Tuple2)	1					

	a) 20 b)	(20,)	c) (10,10)	d) Error	
8	Fill in the blanks: The SQL keywordbased on patterns LIKE	is used in	n SQL expression	to select records	1
9	What possible outcome wind import random value=random.rand fruit=["APPLE","C for i in range(value print(fruit[i],end print()	lint(0,3) DRANGE","MA			
	a) APPLE##				1
	b) APPLE# ORANGE##				
	c) APPLE## ORANG	GE##			
	d) ORANGE## MANGO## APPLE##				
10	Select the network device different protocols a) Bridge b)Gateway	c)Hub	d) Router	1
11	State whether the following The value of the expression TRUE				1
12	In the relational models, c a) Number of tuples c) Number of tables	b) 1	ally refers to Number of attribut lber of constraints	tes	1
13	Data structure STACK is a a)First In First Out c)Last In First O		b) First In Las	st Out n Last Out	1
14	Which function is used to a) Writeline() b)	write a list of st writelines()	•	d) writeall()	1
15	Which of the following is a) Twisted pair cable c)Coaxial cable	NOT a guided of b) N	/ /		1
16	Which of the following fun a) def fun(a=1,b): b) def fun(a=1,b,c=2) c) def fun(a=1,b=1, d) def fun(a=1,b=1,c=	: c=2):	s correct ?		1
	Q17 and 18 are ASSERTIC correct choice as (a) Both A and R are	ON AND REAS	-		

	(b) Both A and R are true and R is not the correct explanation for A.	
	(c) A is True but R is False	
	(d) A is false but R is True	
17	Assertion (A): In SQL, the aggregate function avg() calculates the average	
-,	value on a set of values and produces a single result.	
	Reason (R): The aggregate functions are used to perform some fundamental	
	arithmetic tasks such as min(), max(), sum() etc	1
	distinition tasks such as min(), max(), suni() etc	
	(b) Both A and R are true and R is not the correct explanation for A.	
18	Assertion(A): Python overwrites an existing file or creates a non-	
10	existing file when we open a file with 'w' mode.	
	Reason(R): a+ mode is used only for writing operations	
	Reason(R). at mode is used only for writing operations	1
	(a) A is True but D is False	
	(c) A is True but R is False	
	SECTION - B	
10		
19	i) Expand the following:	
	a) SMTP: Simple Mail Transfer Protocol	
	b) VoIP: Voice Over Internet Protocol	
	ii) Give one disadvantage of Star topology	
	Star topology has a single point of failure. If the central hub or switch fails,	
	the entire network will be down. This can be a major problem for networks	
	that require high availability. Or any other dis advantage.	
	OR	
	i) What is a web browser?	
	A software application used to access information on the World Wide Web is	1+1=2
	A software application used to access information on the World Wide Web is	1+1-2
	called a Web Browser. When a user requests some information, the web browser	
	fetches the data from a web server and then displays the webpage on the user's	
	screen.	
	ii) Define the term MAC Address	
	A MAC - 11 (11	
	A MAC address (media access control address) is a 12-digit hexadecimal	
	number assigned to each device connected to the network. Primarily specified as	
	a unique identifier during device manufacturing, the MAC address is often	
	found on a device's network interface card (NIC).	
20	Rewrite the following code in Python after removing all syntax error(s) and	
20	underline each correction done in the code.	
	$\frac{\text{num}=30}{6\pi n^{1/2}}$	1/1-
	for k in range(0,num):	½ mark
	$\underline{\text{if }} k\% 4 == 0 :$	each
	print(k*4)	
	else:	
21	print(k+3)	
21	Write a function letter_count(lst) that takes a list of string and returns a	
	dictionary where the keys are the letters from lst and the values are the number	2
	of times that letter appears in the lst.	_
	For example: if the passed list is:	

	T . 1' ./(1 22)	
	Lst=list("apple") Then it should return a dictionary as {'a':1,'p':2,'l':1,'e':1} OR	
	Write a function max_length(), that takes a list of string as argument and display the longest string from the list. Correct Program: 2 Marks	
22	Predict the output of the following code:	
	lst=[2,4,6,8,10]	
	for i in range(1,5):	
	lst[i-1]=lst[i]	2
	for i in range(0,5):	
	print(lst[i],end=' ')	
	output: 4 6 8 10 10	
23	Consider the following list of elements and write Python statement to print the output of each questions. elements=['apple',200,300,'red','blue','grapes'] i) print(elements[3:5]) ['red', 'blue'] ii) print(elements[::-1]) ['grapes', 'blue', 'red', 300, 200, 'apple'] OR Consider the following list exam and write Python statement for the following questions: i) To insert subject "maths" as last element exam.append('maths')	2
	ii) To display the list in reverse alphabetical order exam.sort(reverse=True)	
24	Satheesh has created a database "school" and table "student". Now he wants to view all the databases present in his laptop. Help him to write SQL command for that, also to view the structure of the table he created.	
	SHOW DATABASES DESCRIBE/DESC student OR	2
	Meera got confused with DDL and DML commands. Help her to select only DML command from the given list of command.	

	UPDATE, DROP TABLE, SELECT, CREATE TABLE, INSERT INTO, DELETE, USE	
	DELETE, OSE	
	DML: UPDATE,SELECT,INSERT INTO,DELETE	
25	Predict the out put for the following Python snippet	
	def calc(p,q=3):	
	ans=1	
	for x in range(q):	
	ans=ans*p	
	return ans	
	power=calc(3)	2
	print(power,'9')	
	power=calc(3,2)	
	print(power,'27')	
	OUTPUT:	
	27 9 9 27	
	SECTION C	
26	Predict the output of the Python code given below:	
	def calculate(str):	
	text="	
	x=range(len(str)-1)	
	for i in x:	
	if str[i].isupper():	
	text+=str[i]	
	elif str[i].islower():	
	text + = str[i+1]	3
	else:	
	text+='@'	
	return text	
	start='Pre-board Exam'	
	final=calculate(start)	
	print(final)	
	OUTPUT:	
	Pe-@oard @Eam	

D_ID	D_NAME	D_DEPT	GENDER	EXPERIENCE	
101	JOSEPH	ENT	MALE	10	
104	GUPTA	MEDICINE	MALE	12	
106	SUMAN	ORTHO	FEMALE	7	
111	HANEEF	ENT	MALE	12	
123	DEEPTI	CARDIOLOGY	FEMALE	6	
132	VEENA	SKIN	FEMALE	12	
DISTINCT (EENT MEDICINE ORTHO CARDIOLOG SKIN iii) SE EZ D_NAME DEEPTI SUMAN JOSEPH GUPTA HANEEF VEENA	O_DEPT) GY ELECT D_NAI XPERIENCE;	ME, EXPERIENCE EXPERIENCE 6 7 10 12 12 12 12 10 10 10 10 10	E FROM DOO	CTOR ORDER BY	3
which start w Correct funct Correct openi Correct logic Closing the fi	ith an alphabet ion prototype ½ ing text file stat 1 and ½ mark ile ½ mark ion in Python tl TAILS.txt".	'T'. ½ mark tement ½ mark			3

29	conte word for i i if i print(f.clos count_v Correct Correct Closing	~	ype ½ n le staten narks	nark nent ½	mark			
		T	I	1	I	D O JOIN	SALARY	
	902	NAME SANDEEP	AGE 45	SEX M	DEPT COMPUTER	10/10/2002	56000	
	813	SANGEETA	34	F	HISTORY	24/9/2010	50000	
	771	JOEL	48		ENGLISH	4/5/2001	67900	
	703	MANVITH	36	M	MATHS	27/09/2012	48000	
	606		32	F		23/5/2013	40000	
	537	NEENA ABHILASH	42	М	ENGLISH MATHS	6/2/2006	47000	
						8/3/2003	70450	
	420	MUHSIN	49	M	ENGLISH	10/11/1999	60500	
	412	SUBESH	52	M	HINDI	27/4/2010	45000	1MARK
	345	RENJINI	36	F	COMPUTER	2/2/2016	40000	EACH
	218	DEEPTI	28	F	HINDI	19/9/2011	45000	
	160	SHUBHAM	39	M	SCIENCE	19/9/2011	43000	
	i) SELEC ii) SELEC iii) SELEC	To show all T * FROM TEA To list name T NAME,DEP To display a 35000 and 5	informa ACHER e and de Γ FRON all detail	ation at WHEI partme I TEAC Is of fer	command for the teacher RE DEPT='MA nt whose name and the CHER WHERE male teacher where the control of the cont	of maths departed of maths departed in the starts with letter NAME LIKE ose salary in b	er 'M' 'M%'; etween	
30	alphabe	t.He want to ex	tract all	the upp	at has upper cas per case letters s user defined fund	eparately .Help	p him to do	1 mark for push (), 1 mark

```
a) Push the upper case alphabets in the string into a STACK
                                                                                   for pop()
                                                                                    and 1
   b) Pop and display the content of the stack.
                                                                                   mark for
       For example:
       If the message is "All the Best for your Pre-board Examination"
                                                                                   displaying
       The output should be: E P B A
Ans:
def push(s,ch):
   s.append(ch)
def pop(s):
  if s!=[]:
      return s.pop()
  else:
      return None
string="All the Best for your Pre-board Examination"
for ch in string:
  if ch.isupper():
      push(st,ch)
while True:
  item=pop(st)
  if item!=None:
      print(item,end= ' ')
  else:
      break
```

SECTION D

Consider the table PRODUCT and CLIENT given below:

PR_ID	PR_NAME	MANUFACTURER	PRICE	QTY
BS101	BATH SOAP	PEARSE	45.00	25
SP210	SHAMPOO	SUN SILK	320.00	10
SP235	SHAMPOO	DOVE	455.00	15
BS120	BATH SOAP	SANTOOR	36.00	10
TB310	TOOTH BRUSH	COLGATE	48.00	15
FW422	FACE WASH	DETOL	66.00	10
BS145	BATH SOAP	DOVE	38.00	20

1 mark each

PRODUCT

C_ID	C_NAME	CITY	PR_ID
01	DREAM MART	COCHIN	BS101
02	SHOPRIX	DELHI	TB310
03	BIG BAZAR	DELHI	SP235
04	LIVE LIFE	CHENNAI	FW422

	Write SQL Queries for the following: i) Display the details of those clients whose city is DELHI SELECT * FROM CLIENT WHERE CITY='DELHI'; ii) Increase the Price of all Bath soap by 10 UPDATE PRODUCT SET PRICE=PRICE+10 WHERE PR_NAME='BATH SOAP'; iii) Display the details of Products having the highest price SELECT * FROM PRODUCT WHERE PRICE=(SELECT MAX(PRICE) FROM PRODUCT); iv) Display the product name, price, client name and city with their corresponding matching product Id. SELECT PR_NAME, PRICE, C_ID, CITY FROM PRODUCT, CLIENT WHERE PRODUCT.PR_ID=CLIENT.PR_ID;	
32	Gupta is writing a program to create a csv file "employee.csv" which will contain user name and password for department entries. He has written the following code. As a programmer, help him to successfully execute the given task. import	4

SECTION E

Oxford college, in Delhi is starting up the network between its different wings. There are four Buildings named as SENIOR, JUNIOR, ADMIN and HOSTEL as shown below:

JUNIOR

SENIOR

ADMIN

HOSTEL

The distance between various building is as follows:


ADMIN TO SENIOR	200 m
ADMIN TO JUNIOR	150 m
ADMIN TO HOSTEL	50 m
SENIOR TO JUNIOR	250 m
SENIOR TO HOSTEL	350 m
JUNIOR TO HOSTEL	350 m

Number of computer in each building is:

SENIOR	130
JUNIOR	80
ADMIN	160
HOSTEL	50

1 mark each

i) Suggest the cable layout of connections between the buildings.



ii) Suggest the most suitable place (i.e., building) to house the server of this college, provide a suitable reason.

ADMIN, as number of computers are more in ADMIN building

iii) Is there a requirement of a repeater in the given cable layout? Why/ Why not? Yes, between ADMIN TO JUNIOR and ADMIN TO SENIOR distance is more than 100 m. iv) Suggest the placement of hub/switch with justification. In all building as it is required to connect all computers in to a network. v) The organisation also has inquiry office in another city about 50-60 km away in hilly region. Suggest the suitable transmission media to interconnect to college and inquiry office out of the following: a. Fiber optic cable b. Microwave c. Radiowave Radio wave What is Pickling or Serialization? 34 The process of converting Python object hierarchy into byte stream so that it can be written into a file. A binary file "salary.DAT" has structure [employee id, employee ii) name, salary]. Write a function countrec() in Python that would read contents of the file "salary.DAT" and display the details of those employee whose salary is above 20000. def countrec(): num=0fobj=open("salary.dat", 'rb') try: while True: rec=pickle.load(fobj) if rec[2] > 20000: print(rec[0],rec[1],rec[2]) 2+3=5except: fobj.close() OR What is the difference between 'r' and 'rb' mode in Python file? r is used to read text files and rb is used to read binary files A binary file "STUDENT.DAT" has structure [admission number, ii) Name, Percentage]. Write a function countrec() in Python that would read contents of the file "STUDENT.DAT" and display the details of those students whose percentage is above 90. Also display number of students scoring above 90% import pickle def countrec(): fobj=open('student.dat','rb') num=0 try:

exc fobj retu			
minim ii) import con=m cursor- cursor. data=c for rec con.clc mysql connec select	relational mode al set of attribe Complete the missin rysql(=con.cursor() execute(in data: print(rec) pse() i) connector ii) ct() iii)	host='localhost',user='root',passwd='123', database='student') # statement 2	1+4=5
i)	constrain The diffe	rence between a UNIQUE constraint and a Primary Key is	
	that per ta	able may only have one Primary Key but may define more UNIQUE constraints	

ii) Maya has created a table named BOOKt in MYSQL database,

LIBRARY

BNO(Book number)- integer

B_name(Name of the book) - string

Price (Price of one book) -integer

Note the following to establish connectivity between Python and

MySQL:

Username - root

Password - writer

Host - localhost

Maya, now wants to display the records of books whose price is more than 250. Help Maya to write the program in Python

1 mark each for creating connection object, Creating cursor, Writing sql command

केंद्रीय विद्यालय संगठन, जयपुर संभाग

Kendriya Vidyalaya Sangathan, Jaipur Region प्रथम प्री-बोर्ड परीक्षा 2023-24

First Pre-Board Exam 2023-24

कक्षा/Class: XII विषय/Subject : Computer Science (083)

समय : 3 घंटे पूर्णांक/Max Marks: 70

सामान्य निर्देश / General Instructions:

- 1. This question paper contains five sections, Section A to E.
- 2. All questions are compulsory.
- 3. Section A has 18 questions carrying 01 mark each.
- **4.** Section B has 07 Very Short Answer type questions carrying 02 marks each.
- **5.** Section C has 05 Short Answer type questions carrying 03 marks each.
- **6.** Section D has 03 Long Answer type questions carrying 05 marks each.
- **7.** Section E has 02 questions carrying 04 marks each. One internal choice is given in Q35 against part c only.

	खंड / SECTION-A	
प्रश्न सं Q. No.	प्रश्न / Question	अंक / Marks
1.	State True or False "break keyword skips remaining part of an iteration in a loop and comp starting of the loop and executes again"	oiler goes to
2.	Find the valid keyword from the following? a) Student-Name b) False c) 3rdName d) P_no	1
3.	What will be the output for the following Python statement? X={'Sunil':190, 'Raju':10, 'Karambir':72, 'Jeevan':115} print('Jeevan' in X, 190 in X, sep="#") (a)True#False (b) True#True (c) False#True (d) False#False	1
4.	Consider the given expression: True and False or not True Which of the following will be correct output if the given expression is e	valuated?
	(a) True (b) False (b) (c) NONE (d) NULL	
5.	Select the correct output of the code: a = "Python! is amazing!" a = a.split('!') b = a[0] + "." + a[1] + "." + a[2] print (b) (a) Python!. is amazing!. (b) Python. is amazing. (c) Python.! is amazing.! (d) will show error	1
6.	Which of the following mode in file opening statement overwrite the exicontent? (a) a+ (b) r+ (c) w+ (d) None of the above	sting 1
7.	The attribute which have properties to be as referential key is known as. (a) foreign key (b) alternate key (c) candidate key (d) Both (a) and (c)	1
8.	Which command is used to change some values in existing rows? (a) CHANGE (b) MODIFY (b) (c) ALTER (d) UPDATE	1

following code? Q="Humanity is the best quality" # Statement1 print(Q) Q="Indeed." # Statement3 Q[0]= #" # Statement4 Q=Q+"It is." # Statement5 (a) Statement3 (b) Statement4 (c)Statement5 (d)Statement 4 and 5 10. p=150 def fn(q):	9.	Which of the following statement(s) would give an error after executing the	1
print(Q) # Statement2 Q="Indeed." # Statement3 Q[0]= # # Statement4 Q=Q+"It is." # Statement5 (a) Statement3 (b) Statement5 (d)Statement4 and 5 10. p=150 def fn(q): #missing statement p=p+q fn(50) print(p) Which of the following statements should be given in the blank for #missing statement if the output produced is 200 (a) global p=150 (b) global q 11. Which function is used to split a line of string in list of words? (a) split() (c) split() (d) all of these 12. What possible output(s) will be obtained when the following code is executed import random k=random.randimt(1,3) fruits=[mango', banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (c) banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:			
Q="Indeed." # Statement3 Q[0]='#' # \$Statement4 Q=Q+'It is." # \$Statement5 (a) Statement3 (b) Statement 4 (c)Statement 5 (d)Statement 4 and 5 10. p=150 def fn(q):			
Qi(p)='#'			
Q=Q+"It is." #Statement5 (a) Statement3 (b) Statement 4 (c)Statement 5 (d)Statement 4 and 5 10. p=150 def fm(q):		· ·	
(a) Statement 3 (b) Statement 4 (c)Statement 5 (d)Statement 4 and 5 p=150			
10. p=150 def fn(q):			
def fn(q): #missing statement p=p+q fn(50) print(p) Which of the following statements should be given in the blank for #missing statement if the output produced is 200 (a) global p=150 (b) global p (c) p=150 (d) globalq 11. Which function is used to split a line of string in list of words? (a) split() (b) split() (c) split line() (d) all of these 12. What possible output(s) will be obtained when the following code is executed import random k=random.randint(1,3) fruits=[mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:	10.		1
#missing statement p=p+q fn(50) print(p) Which of the following statements should be given in the blank for #missing statement if the output produced is 200 (a) global p=150 (b) global p (c) p=150 (d) global p (c) split (b) (c) split (b) (d) all of these 12. What possible output(s) will be obtained when the following code is executed import random k=random.randint(1,3) fruits=[mango', banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank: is a communication protocol responsible for sending emails. (a) TCP (b) SMTP (c) PPP (d) HTTP 14. What will be the ouput when following expression be evaluated in Python? print(21.5 // 4 + (8 + 3.0)) (a) 16 (b) 14.0 (c) 15 (d) 15.5 15. Which of the following functions other than close() writes the buffer data to file (a) push() (b) write() (c) writeBuffer() (d) flush() 16. To get counting of the returned rows, you may use		•	
p=p+q fn(50) print(p) Which of the following statements should be given in the blank for #missing statement if the output produced is 200 (a) global p=150 (b) global p (c) p=150 (d) global p (a) split() (b) split() (c) split() (c) split() (d) all of these 12. What possible output(s) will be obtained when the following code is executed import random k=random.randint(1,3) fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="#") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:is a communication protocol responsible for sending emails. (a) TCP (b) SMTP (c) PPP (d) HTTP 14. What will be the output when following expression be evaluated in Python? print(21,5 // 4 + (8 + 3.0)) (a) 16 (b) 14.0 (c) 15 (d) 15.5 15. Which of the following functions other than close() writes the buffer data to file (a) push() (b) write() (c) writeBuffer() (d) flush() 16. To get counting of the returned rows, you may use			
print(p) Which of the following statements should be given in the blank for #missing statement if the output produced is 200 (a) global p=150 (b) global p (c) p=150 (d) global q 11. Which function is used to split a line of string in list of words? (a) split() (b) split() (c) split_line() (d) all of these 12. What possible output(s) will be obtained when the following code is executed import random k=random_randint(1,3) fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:			
Which of the following statements should be given in the blank for #missing statement if the output produced is 200 (a) global p=150 (b) global p (c) p=150 (d) globalq 11. Which function is used to split a line of string in list of words? (a) split() (b) splt() (c) split_line() (d) all of these 12. What possible output(s) will be obtained when the following code is executed import random k=random.randint(1,3) fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:		fn(50)	
statement if the output produced is 200 (a) global p=150 (b) global p (c) p=150 (d) global q 11. Which function is used to split a line of string in list of words? (a) split() (c) split_line() (d) all of these 12. What possible output(s) will be obtained when the following code is executed import random k=random.randint(1,3) fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:		print(p)	
(a) global p=150 (b) global p (c) p=150 (d) global q 11. Which function is used to split a line of string in list of words? (a) split() (b) split() (c) split_line() (d) all of these 12. What possible output(s) will be obtained when the following code is executed import random k=random.randint(1,3) fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="+") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank: is a communication protocol responsible for sending emails. (a) TCP (b) SMTP (c) PPP (d)HTTP 14. What will be the ouput when following expression be evaluated in Python? print(21.5 // 4 + (8 + 3.0)) (a) 16 (b) 14.0 (c) 15 (d) 15.5 15. Which of the following functions other than close() writes the buffer data to file (a) push() (b) write() (c) writeBuffer() (d) flush() 16. To get counting of the returned rows, you may use			
Comparison Com			
Which function is used to split a line of string in list of words? (a)split() (c) split line() (d) all of these			
(a)split() (b) split() (c) split_line() (d) all of these 12. What possible output(s) will be obtained when the following code is executed import random k=random.randint(1,3) fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:	11		1
(c) split_line() (d) all of these 12. What possible output(s) will be obtained when the following code is executed import random k=random.randint(1,3) fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k):	11.		1
12. What possible output(s) will be obtained when the following code is executed import random k=random.randint(1,3) fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank: — is a communication protocol responsible for sending emails. (a) TCP (b) SMTP (c) PPP (d)HTTP 14. What will be the ouput when following expression be evaluated in Python? print(21.5 // 4 + (8 + 3.0)) (a) 16 (b) 14.0 (c) 15 (d) 15.5 15. Which of the following functions other than close() writes the buffer data to file (a) push() (b) write() (c) writeBuffer() (d) flush() 16. To get counting of the returned rows, you may use			
import random k=random.randint(1,3) fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:	12		1
k=random.randint(1,3) fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:	12.		1
fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya'] for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:		·	
for j in range(k): print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:		k=random.randint(1,3)	
print(j, end="*") (a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:		fruits=['mango', 'banana', 'grapes', 'water melon', 'papaya']	
(a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:		for j in range(k):	
(a) mango*banana*grapes (b) banana*grapes (c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:		print(j, end="*")	
(c) banana*grapes*watermelon (d) mango*grapes*papaya 13. Fill in the blank:			
Fill in the blank:is a communication protocol responsible for sending emailsis a communication protocol general sending emailsis a communication protocol general sending emailsis a communication protocol general sending emailsis a communication general sending emails			
(a) TCP (b) SMTP (c) PPP (d)HTTP 14. What will be the ouput when following expression be evaluated in Python? print(21.5 // 4 + (8 + 3.0)) (a) 16 (b) 14.0 (c) 15 (d) 15.5 15. Which of the following functions other than close() writes the buffer data to file (a) push() (b) write() (c) writeBuffer() (d) flush() 16. To get counting of the returned rows, you may use	13.		1
14. What will be the ouput when following expression be evaluated in Python? print(21.5 // 4 + (8 + 3.0)) (a) 16 (b) 14.0 (c) 15 (d) 15.5 15. Which of the following functions other than close() writes the buffer data to file (a) push() (b) write() (c) writeBuffer() (d) flush() 16. To get counting of the returned rows, you may use		is a communication protocol responsible for sending emails.	
print(21.5 // 4 + (8 + 3.0)) (a) 16 (b) 14.0 (c) 15 (d) 15.5 15. Which of the following functions other than close() writes the buffer data to file (a) push() (b) write() (c) writeBuffer() (d) flush() 16. To get counting of the returned rows, you may use		(a) TCP (b) SMTP (c) PPP (d)HTTP	
(a) 16 (b) 14.0 (c) 15 (d) 15.5 15. Which of the following functions other than close() writes the buffer data to file (a) push() (b) write() (c) writeBuffer() (d) flush() 16. To get counting of the returned rows, you may use	14.		1
15. Which of the following functions other than close() writes the buffer data to file (a) push() (b) write() (c) writeBuffer() (d) flush() 16. To get counting of the returned rows, you may use			
(a) push() (b) write() (c) writeBuffer() (d) flush() 16. To get counting of the returned rows, you may use	4.5		
To get counting of the returned rows, you may use	15.		1
(a) cursor.rowcount (b) cursor.count (c) cursor.countrecords() Q17 and 18 are ASSERTION AND REASONING based questions. Mark the correct choice as (a) Both A and R are true and R is the correct explanation for A (b) Both A and R are true and R is not the correct explanation for A (c) A is True but R is False (d) A is false but R is True 17. Assertion (A):- If the arguments in function call statement are provided in the format parameter=argument, it is called keyword arguments. Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).	1.0		1
(c) cursor.countrecords() (d) cursor.manyrecords() Q17 and 18 are ASSERTION AND REASONING based questions. Mark the correct choice as (a) Both A and R are true and R is the correct explanation for A (b) Both A and R are true and R is not the correct explanation for A (c) A is True but R is False (d) A is false but R is True 17. Assertion (A):- If the arguments in function call statement are provided in the format parameter=argument, it is called keyword arguments. Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).	16.		1
Q17 and 18 are ASSERTION AND REASONING based questions. Mark the correct choice as (a) Both A and R are true and R is the correct explanation for A (b) Both A and R are true and R is not the correct explanation for A (c) A is True but R is False (d) A is false but R is True 17. Assertion (A):- If the arguments in function call statement are provided in the format parameter=argument, it is called keyword arguments. Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).		(a) cursor.rowcount (b) cursor.count	
(a) Both A and R are true and R is the correct explanation for A (b) Both A and R are true and R is not the correct explanation for A (c) A is True but R is False (d) A is false but R is True 17. Assertion (A):- If the arguments in function call statement are provided in the format parameter=argument, it is called keyword arguments. Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).		(c) cursor.countrecords() (d) cursor.manyrecords()	
(a) Both A and R are true and R is the correct explanation for A (b) Both A and R are true and R is not the correct explanation for A (c) A is True but R is False (d) A is false but R is True 17. Assertion (A):- If the arguments in function call statement are provided in the format parameter=argument, it is called keyword arguments. Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).			
(b) Both A and R are true and R is not the correct explanation for A (c) A is True but R is False (d) A is false but R is True 17. Assertion (A):- If the arguments in function call statement are provided in the format parameter=argument, it is called keyword arguments. Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).			
(c) A is True but R is False (d) A is false but R is True 17. Assertion (A):- If the arguments in function call statement are provided in the format parameter=argument, it is called keyword arguments. Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).			
(d) A is false but R is True 17. Assertion (A):- If the arguments in function call statement are provided in the format parameter=argument, it is called keyword arguments. Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).			
Assertion (A):- If the arguments in function call statement are provided in the format parameter=argument, it is called keyword arguments. Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).	` -		
parameter=argument, it is called keyword arguments. Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).			· 1
Reasoning (R):- During a function call, the argument list first contain keyword argument(s) followed by positional argument(s).			
argument(s) followed by positional argument(s).	1		
18. Assertion (A): CSV (Comma Separated Values) is a file format for data storage with one 1		Assertion (A): CSV (Comma Separated Values) is a file format for data storage with one	1
record on each line and each field is separated by comma.		record on each line and each field is separated by comma.	
Reason (R): The format is used to share data between cross platform as text editors are		Reason (R): The format is used to share data between cross platform as text editors are	!

	available on all platforms.	
	खंड / SECTION-B	
19.	Rewrite the following code in python after removing all syntax error(s). Underline each	2
	correction done in the code.	
	Num=int(rawinput("Number greater than 10:"))	
	sum=0	
	for i in range(10,Num,3)	
	sum+=1	
	if i%2=0:	
	print(i*2)	
	else:	
	print(i*3)	
20	print(sum)	2
20.	Write one advantage and one disadvantage of packet switching	Z
	OR	
21.	Which language is the most suitable language to create web pages?	1
41.	(a) Given is a Python string:	1
	X="Kendriya Vidyalaya sangathan"	
	Write the output of: print(X[4:9]*2)	
	(b) Write the output of the python program code given below:	1
	hello = {empname: "Ishan", address: "New Delhi", salary: 10000}	•
	hello[salary] = 15000	
	hello[address] = "Delhi"	
22.	print(hello.keys()) Explain the use of GROUP BY clause in a Relational Database Management	2
22.	System. Give example to support your answer.	2
23.	(a) Write the full forms of the following:	2
20.	(i) POP3 (ii) VoIP	_
24.	(b) Define RJ-45?	2
24.	Predict the output of the Python code given below: def Alter(P=15,Q=10):	۷
	P=P*Q	
	Q=P/Q	
	print(P,"#",Q)	
	return Q	
	A=100 B=200	
	A=Alter(A,B)	
	print(A, "\$", B)	
	B=Alter(B)	
	print(A,"\$",B)	
	A=Alter(A) print(A,"\$",B)	
	and the state of t	
	OR	
	Predict the output of the Python code given below:	
	a=tuple()	
	a=a + tuple('Python')	
	print(a)	
	print(len(a))	
	b=(10,20,30)	
	print(len(b))	
25.	Differentiate Where and Having clause in SQL with example.	2
	OR	
	Define aggregate function and give example.	

खंड / SECTION-C

26. (a) Consider the following tables – Employee and Office:

Table: Emp

	14.514. =p				
Emp_Id	Name	Salary			
E01	Lakshya	54000			
E02	Ravi	NULL			
E03	Neeraj	32000			
E04	Brijesh	42000			

Table: dept

Emp_Id	Dept	DOJ
E01	Computer	05-SEP-2007
E02	Physics	05-JAN-2008
E03	Sports	30-DEC-2000
E04	English	05-SEP-2012

What will be the output of the following statement? SELECT Name, Dept FROM Emp E, dept d WHERE E.Emp_Id=d.Emp_Id;

(b) Consider the following tables SCHOOL and ADMIN. Give the output the following SQL queries:

TABLE: SCHOOL

CODE	TEACHER	SUBJECT	DOJ	PERIODS	EXPERIENCE
1001	RAVI SHANKAR	ENGLISH	12/3/2000	24	10
1009	PRIYA RAI	PHYSICS	03/09/1998	26	12
1203	LIS ANAND	ENGLISH	09/04/2000	27	5
1045	YASHRAJ	MATHS	24/8/2000	24	15
1123	GANAN	PHYSICS	16/7/1999	28	3
1167	HARISH B	CHEMISTRY	19/10/1999	27	5
1215	UMESH	PHYSICS	11/05/1998	22	16

TABLE: ADMIN

CODE	GENDER	DESIGNATION
1001	MALE	VICE PRINCIPAL
1009	FEMALE	COORDINATOR
1203	FEMALE	COORDINATOR
1045	MALE	HOD
1123	MALE	SENIOR TEACHER
1167	MALE	SENIOR TEACHER
1215	MALE	HOD

- i. SELECT Designation, COUNT (*) FROM Admin GROUP BY Designation HAVING COUNT (*) <2;
- ii. SELECT TEACHER FROM SCHOOL WHERE EXPERIENCE >12 ORDER BY TEACHER DESC;
- Write a method **beginA()** in Python to read lines from a text file Notebook.TXT, and display those lines, which are starting with 'A'.

For example If the file content is as follows:

An apple a day keeps the doctor away.

We all pray for everyone's safety.

A marked difference will come in our country.

The beginA() function should display the output as:

An apple a day keeps the doctor away.

A marked difference will come in our country.

OR

A text file "PYTHON.TXT" contains alphanumeric text. Write a program that reads this

3

1+2

				queries (i) to	(iv) based	on the r	elations CL	UB and	3	
'	STUDENT given below: Table : CLUB									
	COACHID	CNAM	E AGE		DATEOFAPP	PAY	GENDER			
	1	KUKRE		KARATE	27/03/1996	1000	M			
	2	RAVIN	_	KARATE	20/01/1998	1200	F			
	3	KARA		SQUASH	19/02/1998	2000	M			
	4	TARUI		BASKETBALL	01/01/1998	1500	M			
	5 6	ZUBIN		SWIMMING SWIMMING	12/01/1998	750 800	M F			
	7	KATAI ANKIT		SQUASH	24/02/1998 20/02/1998	2200	F			
	8	ZAREE		KARATE	22/02/1998	1100	F			
	9	KUSH	I 41	SWIMMING	13/01/1998	900	M			
	10	SHAILY	7A 37	BASKETBALL	19/02/1998	1700	M			
				Table : STUD	ENT					
	COACHID	SNAME	STIPEND	STREAM	MARKS	GRAI	DE CLASS			
	1	KARAN	400.00	MEDICAL	78.5	В	12B			
	12	VINNET	450.00	COMMERCE	89.2	A	11C	4		
	13	VIVEK DHRUV	300.00 350.00	COMMERCE HUMANITIE	68.6 ES 73.1	C B	12C 12C	-		
	15	MOHIT	500.00	NONMEDICA		A	11A	-		
	6	ANUJ	400.00	MEDICAL	75.4	В	12B	1		
	17	ABHAY	250.00	HUMANITIE		С	11A			
	18	PAYAL	450.00	NONMEDICA	AL 88.5	A	12A			
	19	DIKSHA	500.00	MONMEDIC						
				NONMEDICA		A	12A			
-	SELECT SPO	RISHIKA DRTS, MIN(300.00 (PAY) FRO	COMMERC M Club Group	E 67.5 by SPORTS;	С	12A 12C			
	SELECT SPO i) SELECT M ii) SELECT CI C.COA iv) SELECT WHEI (b) Write SQ Write a funct should retur Example: If t then function	RISHIKA ORTS, MIN(AX(DATEC NAME, PAY ACHID =S.C SName, Cl RE Gender L comman tion shiftn(n a list afte he list initi n should re tially conta	300.00 (PAY) FRODFAPP), M (A C.COAC (OACHID A NAME FRODF AND C d to list al (L,n), where er shifting fally conta eturn [3, 1 ins [2, 15,	COMMERC M Club Group IN(DATEOFAPI CHID, SPORTS F ND PAY>=150 DM Student S, C C.COACHID=S.C databases. The L is a list of in number of ele ins [2, 15, 3, 14 4, 7, 9, 19, 6, 1, 3, 14, 7, 9, 19, 6, 1,	by SPORTS; P) FROM CLUB CO; CLUB COACHID; entegers and nements to the company of	JB; c, STUDE i is an in e left. ., 10] an	ENT S WHER		3	
	SELECT SPO i) SELECT M ii) SELECT CI C.COA iv) SELECT WHEI (b) Write SQ Write a funct should retur Example: If t then function	RISHIKA ORTS, MIN(AX(DATEC NAME, PAY ACHID =S.C SName, Cl RE Gender L comman tion shiftn(n a list afte he list initi n should re tially conta	300.00 (PAY) FRODFAPP), M (A C.COAC (OACHID A NAME FRODF AND C d to list al (L,n), where er shifting fally conta eturn [3, 1 ins [2, 15,	M Club Group IN(DATEOFAPICHID, SPORTS FOR STORY) STORY	by SPORTS; P) FROM CLUB CO; CLUB COACHID; entegers and nements to the company of	JB; c, STUDE i is an in e left. ., 10] an	ENT S WHER			
	SELECT SPO i) SELECT M ii) SELECT CI C.COA iv) SELECT WHEI (b) Write SQ Write a funct should return Example: If then function If the list inite then function A nested list the following	RISHIKA ORTS, MIN(AX(DATEC NAME, PAY ACHID =S.C SName, Cl RE Gender L comman tion shiftn(n a list afte he list initi n should re tially conta n should re contains the	300.00 (PAY) FRODFAPP), M (A. C.COAC (OACHID A) (NAME FRODFA) (A to list all (L,n), where shifting the contact of the contact	COMMERC M Club Group IN(DATEOFAPI CHID, SPORTS F ND PAY>=150 DM Student S, C C.COACHID=S.C databases. The L is a list of in number of ele ins [2, 15, 3, 14 4, 7, 9, 19, 6, 1, 3, 14, 7, 9, 19, 6, 1, 19, 6, 1, 10, 2, visitors in a mu	by SPORTS; P) FROM CLUB CO; CLUB COACHID; Integers and mements to the company of	JB; c, STUDE i is an in e left. c, 10] and n=4	teger. The f	unction		
	SELECT SPO i) SELECT M ii) SELECT CI C.COA iv) SELECT WHEI (b) Write SQ Write a funct should return Example: If then function If the list inite then function A nested list the following	RISHIKA ORTS, MIN(AX(DATEC NAME, PAY ACHID =S.C SName, Cl RE Gender L comman tion shiftn(n a list afte he list initi n should re tially conta n should re contains the	300.00 (PAY) FRODFAPP), M (A. C.COAC (OACHID A) (NAME FRODFA) (A to list all (L,n), where shifting the contact of the contact	M Club Group IN(DATEOFAP) CHID, SPORTS FOR STUDENTS FOR S	by SPORTS; P) FROM CLUB CO; CLUB COACHID; Integers and mements to the company of	JB; c, STUDE i is an in e left. c, 10] and n=4	teger. The f	unction		
	SELECT SPO i) SELECT M ii) SELECT CI C.COA iv) SELECT WHEI (b) Write SQ Write a function Example: If then function If then function A nested list then following [V_no (in) Write the following	RISHIKA ORTS, MIN(AX(DATEC NAME, PAY ACHID = S.C SName, Cl RE Gender L comman tion shiftn(n a list after he list inition n should received a should received contains the g data of a very t), Date (st llowing uses us":	300.00 (PAY) FRODFAPP), M (A. C.COAC (OACHID ANAME FRODFA), where shifting its contact and the country of the data of visitor: aring), Name of the defined of the defined its contact and the country of the data of visitor: aring), Name of defined its contact and the contact and the country of the data of visitor: aring), Name of defined its contact and the contact and the country of the contact and the country of the contact and the country of the co	M Club Group IN(DATEOFAP) CHID, SPORTS FOR Student S, COCOACHID=S.	by SPORTS; P) FROM CLUB CO; CLUB COACHID; Integers and mements to the company of	JB; c, STUDE is an in e left. , 10] and of the in M/F), Ag n operat	teger. The formula to the description on the contract of the c	unction ntains		
	SELECT SPO i) SELECT M ii) SELECT CI C.COA iv) SELECT WHEI (b) Write SQ Write a function Should return Example: If then function If the list inite then function A nested list the following [V_no (in) Write the following mamed "statu (i) Push are in	RISHIKA ORTS, MIN(AX(DATEC NAME, PAY ACHID =S.C SName, Cl RE Gender L comman- cion shiftn(n a list after he list initi n should re- cially contains the g data of a v t), Date (st llowing us us": _element(V n the age ra	300.00 (PAY) FRODFAPP), M (A. C.COAC (DACHID A NAME FRODFA (L,n), where er shifting fally contact turn [3, 1 ins [2, 15, 2 turn [7, 9 the data of visitor: cring), Name of defined Visitors) - ange of 15	M Club Group IN(DATEOFAP) CHID, SPORTS FOR STUDENTS FOR STUDENTS FOR STUDENTS FOR STUDENTS FOR LIST A 15, 15, 14, 15, 19, 19, 10, 19, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10	by SPORTS; P) FROM CLUB CO; CLUB COACHID; Integers and mements to the contents to the contents of the contents	JB; c, STUDE i is an in e left, 10] and of the in M/F), Ag n operat ng Gend	teger. The formula to the description on the description of the descri	ntains e stack r who		

[['305', "10/11/2022", "Geeta", "F", 35], ['306', "10/11/2022", "Arham", "M", 15], ['307', "11/11/2022", "David", "M", 18], ['308', "11/11/2022", "Madhuri", "F", 17], ['309', "11/11/2022", "Sikandar", "M", 13]] The stack should contain M M The output should be: Female: 1 Male: 2 Done OR Write a function in Python, Push(EventDetails) where, EventDetails is a dictionary containing the number of persons attending the events- {EventName : Number Of Persons \}. The function should push the names of those events in the stack named 'BigEvents' which have number of persons greater than 200. Also display the count of elements pushed on to the stack. For example: If the dictionary contains the following data: EventDetails = {"Marriage": 300, "Graduation Party": 1500, "Birthday Party": 80, "Get together":150} The stack should contain: Marriage **Graduation Party** The output should be: The count of elements in the stack is 2 खंड / SECTION-D 5*1 31. Ripunjay is planning to connect its Delhi Campus with its head office at Goregaon. Its Delhi Campus is spread across an area of approx. 1 square kilometers consisting of 3 blocks. HR, Acad and Adm. You as a network expert have to suggest answers to the five queries (i) to (v) raised by them. Delhi Campus Goregaon Office HR Finance Acad Adm Shortest distances between various blocks HR to Adm 120m HR to Acad 75m Acad to Adm 130m HR to Finance 70m Finance to Adm 90m Goregaon to Delhi Campus 50 km Number of computers installed at various blocks Block **Number of Computers**

	HR	250	
	Adm	30	
	Acad	70	
	Finar		
	Gore		
	dore	guon	
	(i)	Suggest the most suitable block in the Delhi Campus to host the server. Give a suitable reason with your suggestion.	
	(ii)	Suggest the cable layout among the various blocks within the Delhi Campus for connecting the blocks.	
	(iii)	Suggest the placement of the following devices with appropriate reasons:	
		a. Switch / Hub b. Repeater	
	(iv)	Suggest a protocol that shall be needed to provide Video Conferencing solution between Goregaon Office and Delhi campus.	
	(v)	Suggest the type of network to connect Goregaon Office and Delhi campus.	
32.	, ,	Vrite the output of the code given below:	2+3
	a=5		
		dd(b=2):	
	_	bal a	
		a+b	
		nt(a,'#',b)	
		urn a	
	b=ad		
		(a,'#',b)	
	b=ad	(a,'#',b)	
	print	(a, # ,U)	
	(b) T	he code given below inserts the following record in the table Employee:	
		EmpNo – integer Name – string	
		Department – string Salary – integer	
	Note	the following to establish connectivity between Python and MYSQL:	
	•	Username is root	
	•	Password is brick	
		The table exists in a MYSQL database named organization.	
		The details (EmpNo, Name, Department and Salary) are to be accepted	
	_	from the user.	
		e the following missing statements to complete the code:	
		ment 1 – to form the cursor object	
		ment 2 – to execute the command that inserts the record in the table Student.	
	State	ment 3- to add the record permanently in the database	
	_	art mysql.connector as mysqldef	
	3qı_u	con=mysql.connect(host="localhost",user="root",password="brick",	
		database="organization")	
		mycursor= #Statement 1	
		eno=int(input("Enter Employee number :: "))	
		name=input("Enter Name :: ")	
		dept=input("Enter Name :: ")	
		sal=int(input("Enter Salary :: "))	
		sai-milimpull emer salary JJ	

```
query="insert into student values({},'{}',{},{})".format(eno,name,dept,sal)
                                                       #Statement 2
                                                       # Statement 3
            print("Data Added successfully")
                                                 OR
       (a) Predict the output of the code given below:
       a="Give me a glass of water!"
       n = len(a)
      h=" "
       for i in range(0, n):
            if a[i] >= 'a' and a[i] <= 'k':
                 b = b + a[i].upper()
            elif (a[i] >= 'l' \text{ and } a[i] <= 'z'):
                 b = b + a[i-1]
            elif a[i].isupper():
                 b = b + a[i].lower()
            else:
                 b = b + '#'
       print(b)
       (a) The code given below reads the following record from the table named items and
          displays only those records who have price greater than 100:
              ItemNo -integer
              Name – string
              Price - integer
       Note the following to establish connectivity between Python and MYSQL:
                 • Username is root
                 • Password is epic
                 • The table exists in a MYSQL database named store.
       Write the following missing statements to complete the code:
       Statement 1 – to form the cursor object
       Statement 2 – to execute the query that extracts records of items with price greater
                      than 100.
       Statement 3 - to read the complete result of the query (records whose marks are
       greater than 75) into the object named data, from the table studentin the
       database.
       import mysql.connector as mysqlcon
       def sql_data():
            con=mysqlcon.connect(host="localhost",user="root",password="epic",
            database="store")
                                               _#Statement1
            mycursor=
            print("Items with price greater than 100 are :")
                                               #Statement2
            data=
                                               #Statement3
            for i in data:
                print(i)
33.
      a. What is the advantage of using a csv file for permanent storage?
                                                                                                  2+3
       b. Write a python program to create a csv file dvd.csv and write 10 records in it Dvdid,
          dvd_name, qty, price. Display those dvd details whose dvd price is more than 25.
       a Write difference between a binary file and a csv file.
```

- b. Write a Program in Python that defines and calls the following user defined functions: (i) add() - To accept and add data of an employee to a CSV file 'empdata.csv'. Each record consists of a list with fieldelements as eid, ename and salaryto store empid, emp name and emp salary respectively. (ii) search()- To display the records of the emp whose salary is more than 10000. खंड / SECTION-E 34. Mubarak creates a table Items with a set of records to maintain the details of items. 1+1+ After creation of the table, he has entered data of 5 items in the table. 2 Table: items ItemNo Item Scode Qty Rate LastBuy 2005 31-JUN-09 Sharpener 23 60 8 Classic 2003 Balls 22 50 25 01-FEB-10 21 150 2002 Gel Pen Premium 12 24-FEB-10 2006 Gel Pen Classic 21 250 20 11-MAR-09 19-JAN-09 2001 **Eraser Small** 22 220 6 Based on the data given above answer the following questions: Identify the most appropriate column, which can be considered as Primary (i) (ii) If 3 columns are added and 2 rows are deleted from the table, what will be the new degree and cardinality of the above table? Write the statements to: (iii) Insert the following record into the table as (2024, Point Pen, 20, 11, 350, 15-NOV-2022). Increase the rate of the items by 2% whose name ends with 'c'. **OR** (Option for part iii only) (iii) Write the statements to: **a.** Delete the record of items having rate greater than equal to 10. b. Add a column REMARKS in the table with datatype as varchar with 50 characters Anamika is a Python programmer. She has written a code and created a binary file data.dat with sid, sname and marks. The file contains 10 records.
- 35. She now has to update a record based on the sid entered by the user and update the

marks. The updated record is then to be written in the file extra.dat. The records which are not to be updated also have to be written to the file extra.dat. If the sid is not found, an appropriate message should to be displayed.

As a Python expert, help him to complete the following code based on requirement given above:

#Statement 1		import
		def update_data():
		rec={}
	')	fin=open("data.dat","rb")
#Statement 2	")	fout=open("
		found=False
eir marks :: "))	dent id to update their n	eid=int(input("Enter stud
	-	while True:
		try:
#Statement 3		rec=
	==sid:	if rec["student id"]=
	9	found=True
new marks:: "))	"]=int(input("Enter new	rec["marks"]
#Statement 4		pickle.

except: break if found==True: print("The marks of student id ",sid," has been updated.") else: print("No student with such id is not found") fin.close() fout.close() Which module should be imported in the program? (Statement1) (i) (ii) Write the correct statement required to open a temporary file named extra.dat. (Statement 2) Which statement should Anamika fill in Statement 3 to read the data from the (iii) binary file, data.dat and in Statement 4 towrite the updated data in the file, extra.dat?

KENDRIYA VIDYALAYA SANGATHAN, JAIPUR REGION

I-Pre Board Examination 2023-24

Class-12 Subject: Computer Science (083) Answer Key

	SECTION-A	
QN.	Answer of Question	
1.	False	1
2.	False	1
3.	True#False	1
4.	False	1
5.	(b)Python. is amazing.	1
6.	(c) w+	1
7.	(a) foreign key	1
8.	(d) UPDATE	1
9.	(b) Statement 4	1
10	(b) global p	1
11	(a) split()	1
12	(a) mango*banana*grapes	1
13	(b) SMTP	1
14	Ans. (a) 16	1
15	(d) flush()	1
16	(a) cursor.rowcount	1
17	Ans. (c) A is True but R is False	1
18	Ans: (a) Both A and R are true and R is the correct explanation for A	1
	SECTION-B	
19.	Num=int(<u>input</u> ("Number greater than 10 :")) sum=0	2
	for i in range(10,Num,3) <u>:</u>	
	Sum+=1	
	if i%2==0:	
	print(i*2)	
	else:	
	print(i*3)	
20	print(Sum) 1 mark for any correct advantage and disadvantage each	2
20.	OR	2
	Hyper Text Markup Language. Yes it has pre defined tags.	
21.	(a) Ans: riya riya	1
	(b) dict_keys(['empname', 'address', 'salary'])	
	(4) 41-1-1-1-1 = 41-1-1 = 41-1-1 = 41-1-1	1
22.	Ans. GROUP BY clause is used to get the summary data based on one or more	2
	groups. The groups can be formed on one or more columns. For example, the	
	GROUP BY query will be used to count the number of employees in each	
	department, or to get the department wise total salaries.	
	SELECT COUNT(ENAME), SUM(SALARY), DEPT	
	FROM EMPLOYEES	
	GROUP BY DEPT;	
23.	(i) Post office Protocol 3	2
	(ii) Voice over Internet Protocol	
	(b) Ans: Registered Jack-45 is used as connector to connect ethernet cable	
	to ethernet Port in the CPU	

	Т			1
24.	Ans:			2
	20000 # 100.0			
	100.0 \$ 200			
	2000 # 200.0			
	100.0 \$ 200.0			
	100.0 \$ 200.0			
	1000.0 # 100.0			
	100.0 \$ 200.0		OR	
			ON .	
	Ans:			
	('Python')			
	6			
	3			
25.		se is used to filter	the records from a table	2
	that is based on a	specified condition	on, then the "Having" clause	
		•	groups based on the	
	specified conditio		OR	
	Specifica conditio		OIT	
	Ans Aggregate f	unction are group	functions which works on group of	
			nax(), avg(), count() etc.	
	TOWS. Examples of	are surii(), iiiiii(), ii	SECTION-C	
26.	a)		SECTION-C	1+2
20.	- '	David	1	112
	Name	Dept		
	Lakshya	Computer		
	Ravi	Physics		
	Neeraj	Sports		
	Brijesh	English		
	b)			
	(2) \ (2)	4		
	(i) Vice principal	1		
	/::/ \/ACLIDAI			
	(ii) YASHRAJ			
	UMESH			
27.	Ans:			3
	def beginA():			3
	f=open('Noteb	ook TXT')		
	l=f.readlines()	OOK.TAT J		
	for i in l:			
		:[0]		
	if i[0]=='A' or			
	#or if i[0] in ['A'', 'a']		
	print(i)			
	f.close()			
			OR	
	fr=open("PYTHON	•		
	fw=open("PYTHO	N1.TXT", 'w')		
	d=fr.read()			
	for i in d:			
	if not i.isdigit()	:		
	fw.write(i)			
	fr.close()			
	fw.close()			

```
½ marks each for correct piece of code
28.
     Ans. (a)
                                                                                      3
     i) Give 1 mark each correct output
     SPORTS
                  MIN(PAY)
     Karate
                 1000
     Squash
                  2000
     Basketball 1500
     Swimming 750
     ii) Give 1 mark each correct output
     MAX(DATEOFAPP),
                          MIN(DATEOFAPP)
     24/02/1998
                            27/03/1996
     iii) Give 1 mark each correct output
                         PAY
                                    C.COACHID
         CNAME
                                                       SPORTS
         TARUN
                         1500
                                      4
                                                       BASKETBALL
          SHAILYA
                         1700
                                      10
                                                      BASKETBALL
     iv) Give 1 mark each correct output
       SNAME
                       CNAME
       ANUJ
                       KATAKI
     b) Show databases;
29.
      def shiftn(L,n):
                                                                                      3
          return L[n:]+L[:n]
      visitors=[['305', '10/11/2022', 'Geeta','F', 15],['306', '10/11/2022', 'Arham','M',
                                                                                      3
30.
      15],\['307', "11/11/2022", 'David','M', 18],['308', "11/11/2022", 'Madhuri','F',
      17]]
      status=[]
      def Push Element(visitors):
          global status
          for i in visitors:
               if i[4] >= 15 and i[4] <= 20:
                   status.append(i[3])
      def Pop Element():
            global status
            m,f=0,0
            if status!=[]:
               r=status.pop()
               if r== 'F':
                   f+=1
               else:
                   m+=1
           else:
               print("Female :",f)
               print("Male :",m)
               print("Done")
                                       OR
     def Push(EventDetails):
        BigEvents=[]
        count=0
        for i in EventDetails:
           if EventDetails[i]>200:
               BigEvents.append(i)
               count+=1
         print("The count of elements in the stack is",count)
                                        SECTION-D
```

21			Г*1
31.	Ans. (i) HR because it has maximum nur	•	5*1
	(ii) Star topology with HR at centre (any		
	(iii) Switch need to be installed in each of	of the block repeater where distance is	
	greater than 100m		
	(iv) VoIP		
	(v) WAN		
32.	Ans. (a)		2+3
	10 # 5		
	10 # 10		
	20 # 10		
	20 # 20		
	Ans: (b)		
	Statement 1:		
	con.cursor()		
	Statement 2:		
	mycursor.execute(query)		
	Statement 3:		
	con.commit()	.D	
		R	
	Ans. (a) gliE# E#A#GgAas# F# AaEe#		
	Ans. (b)		
	Statement 1: con.cursor()		
	1	Name from items where price>100")	
	Statement 2: mycursor.execute("select	Name from items where price>100")	
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall()	Name from items where price>100")	2+3
33.	Statement 2: mycursor.execute("select		2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file:		2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in	Excel and Notepad applications	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of co	Excel and Notepad applications de.	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of co	Excel and Notepad applications de.	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of coordinates. O Ans: Difference between binary file and	Excel and Notepad applications de.	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of co	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of co-	Excel and Notepad applications de. R I csv file: (Any one difference may be <u>csv</u>	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of coordinates and given) Binary file: Binary Extension is .dat	Excel and Notepad applications de. R I csv file: (Any one difference may be CSV Extension is .csv	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of comparts of the	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of comparts. Difference between binary file and given) Binary file: Binary Extension is .dat Not human readable Stores data in the form of 0s and 1s	Excel and Notepad applications de. R I csv file: (Any one difference may be CSV Extension is .csv	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of comparts of the	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of comparts of the second of the seco	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of condition of the condi	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of coordinate of the second sec	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of coordinate of the second sec	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of comparts of the correct piece of comparts of the correct piece of comparts of the correct piece of correct	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (d) ½ marks for each correct piece of complete in It is just like text file (d) ½ marks for each correct piece of complete in It is just like text file (d) ½ marks for each correct piece of complete in It is just like text file (d) ½ marks for each correct piece of complete in It is just like text file (d) ½ marks for each correct piece of complete in It is just like text file (d) ½ marks for each correct piece of complete in It is just like text file (d) ½ marks for each correct piece of complete in It is	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (d) ½ marks for each correct piece of complete in It is just like text file (d) ½ marks for each correct piece of complete in It is	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file Binary Extension is .dat Not human readable Stores data in the form of 0s and 1s CSV file Program: import csv def add(): fout=open("empdata.csv","a",newling wr=csv.writer(fout) fid=int(input("Enter Emp Id :: ")) fname=input("Enter Emp name :: ") fprice=int(input("Enter psalary :: "))	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file Binary Extension is .dat Not human readable Stores data in the form of 0s and 1s CSV file Program: import csv def add(): fout=open("empdata.csv","a",newling wr=csv.writer(fout) fid=int(input("Enter Emp Id :: ")) fname=input("Enter Emp name :: ") fprice=int(input("Enter psalary :: ")) FD=[eid,ename,salary]	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file Binary Extension is .dat Not human readable Stores data in the form of 0s and 1s CSV file Program: import csv def add(): fout=open("empdata.csv","a",newling wr=csv.writer(fout) fid=int(input("Enter Emp Id :: ")) fname=input("Enter Emp name :: ") fprice=int(input("Enter psalary :: ")) FD=[eid,ename,salary] wr.writerow(FD) fout.close()	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3
33.	Statement 2: mycursor.execute("select Statement 3: mycursor.fetchall() (a) Advantage of a csv file: It is human readable – can be opened in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (b) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is just like text file (c) ½ marks for each correct piece of complete in It is	Excel and Notepad applications de. R I csv file: (Any one difference may be	2+3

```
found=False
       print("The Details are")
       for i in data:
           if int(i[2])>10000:
              found=True
              print(i[0],i[1],i[2])
        if found==False:
              print("Record not found")
        fin.close()
     add()
     print("Now displaying")
     search()
                                          SECTION-E
                                                                                          1+1
34.
     Ans. (i) ItemNo
                                                                                          +2
     (ii) Cardinality=3 and Degree=9
     (iii)
     a) Insert into items values (2024, 'point pen', 20, 11, 350, '2022-NOV-15');
     b) Update items
        Set rate=rate+(rate*0.02)
        Where Item like '%c';
             OR
     iii) Delete From items where rate>=10;
     b) Alter table items Add column (Remarks Varchar(50));
35.
       (i)
              pickle
                                                                                         1
              fout=open('extra.dat', 'wb')
                                                                                         1
      (ii)
                                                                                         1
      (iii)
              pickle.load(fin)
                                                                                         1
      (iv)
              pickle.dump(rec,fout)
```

केंद्रीय विद्यालय संगठन, जयपुर संभाग Kendriya Vidyalaya Sangathan, Jaipur Region

प्रथम प्री-बोर्ड परीक्षा 2023-24

First Pre-Board Exam 2023-24

कक्षा/Class: XII विषय/Subject : Computer Science (083) समय : 3 घंटे पूर्णीक/Max Marks: 70

सामान्य निर्देश / General Instructions:

- 1. This question paper contains five sections, Section A to E.
- 2. All questions are compulsory.
- 3. Section A has 18 questions (1 to 18) carrying 01 mark each.
- 4. Section B has 07 Very Short Answer type questions (19 to 25) carrying 02 marks each.
- **5.** Section C has 05 Short Answer type questions (26 to 30) carrying 03 marks each.
- **6.** Section D has 02 Long Answer type questions (31 to 32) carrying 04 marks each.
- 7. Section E has 03 questions (33 to 35) carrying 05 marks each.
- **8.** All programming questions are to be answered using Python Language only.

	खंड / SECTION-A	
प्रश्न सं Q. No.	प्रश्न / Question	अंक / Marks
1.	State True or False " continue keyword is not a jump statement in a loop."	1
2.	Fill in the blank:command is used to remove a column from a table in SQL. (a)update (b)remove (c) alter (d)drop	1
3.	Given the following dictionaries	1
	dict_stud = {"rno" : "53", "name" : 'Rajveer Singh'}	
	dict_mark = {"Accts" : 87, "English" : 65}	
	Which statement will merge the contents of both dictionaries in dict_stud?	
	(a) dict_stud + dict_mark (b) dict_stud.add(dict_mark) (c) dict_stud.merge(dict_mark) (d) dict_stud.update(dict_mark)	
4.	print(True or not True and False)	1
	Choose one option from the following that will be the correct output after executing the above python expression. a) False b) True c) or d) not	
5.	a) False b) True c) or d) not Which of the following commands will delete the rows of table? (a) DROP command (b) DELETE Command (c) REMOVE Command (d) ALTER Command	1
6.	Fill in the blank:is the first page that normally view at a website. (a) First Page (b) Master Page (c) Home Page (d) Login Page	1
7.	When a Python function does not have return statement then what it returns?	1
	(a) int (b) float (c) None (d) Give Error	
8.	Select the correct output of the code:	1
	>>> a= "Year 2022 at All the best"	
	>>> a = a.split('2')	
	>>> a = a[0] + ". " + a[1] + ". " + a[3]	

	>>> print (a)		
	(a) Year . 0. at All the best	(b) Year 0. at All the best	
0	(c) Year . 022. at All the best	(d) Year . 0. at all the best	1
9.	Which of the following statement(s) would following code?	give an error after executing the	1
		ement 1	
		ment 2	
	1 ()	ement 3	
		ement 4	
	S=S+"Thank you" # State	ement 5	
	(a) Statement 3	(b) Statement 4	
	(c) Statement 5	(d) Statement 4 and 5	
10.	What will the following expression be evalu print(2**3**2)	ated to in Python?	1
	a) 64 b) 256 c) 512 d) 32	2	
11.	Which is the smallest network?		1
	a) WAN (b) LAN		
	c) MAN (d) PAN		
12.	Write the possible outputs(s) when this co	de is executed?	1
	import random		
	n=random.randint(0,3)		
	color=["Y","W","B","R"]		
	for i in range (1,n):		
	print(color[i], end="*")		
	print()		
	a) R* b) W*		
	W* B*		
	B*		
	c) W* W* d) Y*		
	B* B* W* W*		
	B* B* B*		
13.	Which Python approach is used for object so	arialization in handling of Rinary File?	1
15.		Un-pickling	1
		None of these	
14.	Fill in the blank:		1
	Keyword is used to obtain Non-dupli	cated values in a SELECT guerv.	
		HAVING	
15.	Fill in the blank:		1
	is the way of connecting the network	ing devices.	
16.	Which of the following is not valid cursor fur		1
	operations using python. Here Mycur is the o	• •	
	(a) Mycur.fetch() (b) Mycur.fe	tchone()	
	(c) Mycur.fetchmany(n) (d) Mycur.fe	tchall()	
Q17 a	and 18 are ASSERTION AND REASONING base		1
(a) Bo	oth A and R are true and R is the correct explai	nation for A	
	oth A and R are true and R is not the correct ex	xplanation for A	
	is True but R is False is false but R is True		
(a) A 17.	Assertion (A): A variable declared as global i	nside a function is visible with	1
-/-		note a function to violate with	
	changes made to it outside the function.		

	Reasoning (R): All variables declared outside are not visible inside a function	
	till they are redeclared with global keyword.	
10		1
18.	Assertion (A): A binary file in python is used to store collection objects like lists and	1
	dictionaries that can be later retrieved in their original form using pickle module.	
	Reasoning (R): A binary files are just like normal text files and can be read	
	using a text editor like notepad.	
	खंड / SECTION-B	
19.	(i) Write the full forms of the following: (a) IP (b) URL	1+1=
	(ii) What is the use of VoIP?	2
	OR	
	(i) Mention one advantage of Star Topology.	
	(ii) Mention one difference between a Hub and switch in networking.	
20.	Observe the following Python code very carefully and rewrite it after removing all	2
	syntactical errors with each correction underlined.	
	Define reverse(num):	
	rev = 0	
	While num > 0:	
	rem == num %10	
	rev = rev*10 + rem	
	num = num//10	
	return rev	
	print(reverse(1234))	
21.	Write a function INDEX_LIST(L), where L is the list of elements passed as argument to	2
	the function. The function returns another list named 'indexList' that stores the	-
	indices of all Non-Zero Elements of L.	
	For example:	
	If L contains: [2, 0, 5, 0, 1, 0, 0]	
	11 2 0011001115: [2, 0, 0, 0, 1, 0, 0]	
	The indexList will have: [0,2,4]	
	OR	
	Write definition of a function Count_How_Many(Data, item) to count and display number	
	of times the value of item is present in the list Data. (Note: don't use the count() function)	
	For example:	
	If the Data contains [101,102,107,105,102,103,104,102] and item contains 102	
	The function should display 102 found 3 Times.	
22.	Predict the output of the Python code given below:	2
	def foo(s1,s2):	
	11=[]	
	12=[]	
	for x in s1:	
	l1.append(x)	
	for x in s2:	
	101 x 111 52. 12.append(x)	
	return l1,l2	
	a,b=foo("HAPPY",'BIRTHDAY')	
22	print(a,b)	1.1 3
23.	Write the Python statement for each of the following tasks:	1+1=2
	(i) str="PYTHON@LANGUAGE"	
	To print the above string from index 2 onwards using a single statement.	
	(ii)To initialize an empty dictionary named as d using BUILT_IN	
	fuctions/ methods only.	
	OR	
	Write the Python statement for each of the following tasks using BUILT_IN fuctions/	
	methods only:	1

	(i) a="I ANICH	ACE"					
	(i) s="LANGU	AGE t the above str	ing into list				
			•				
24.			ple named as t. rows with many col	umna ono golumi	nomo io		2
24.			s were executed on		i name is		
	SELECT COUNT			sales table.			
		<u> </u>	3,				
	COUNT(*)					
	10						
	SELECT COUNT		ROM sales;				
	COUNT(1	DISCOUNT)					
	6						
	Write a stateme	ent to explain a	${1}$ as to why there is a α	lifference in resul	t of both qu	ueries.	
		_	OR		_		
	Write command	ds to open dat	abase 'KVS' and sho	w all tables in this	database.	And	
		•	ture of the table EM		inside this		
			records of table EM				
25.	_	•	n code given below:				2
	data = [20,19,19	9,17,20,19,17,	20]				
	d = {}						
	for x in data:						
	if x in d:	1					
	d[x]=d[x]+	1					
	else:						
	d[x]=1						
	print(d)		• • • • • • • • • • • • • • • • • • • •				
26	TA7-11-11	- C 1 1 1	खंड / SECTIO	ON-C			1 2
26.	Write the output	_	ven below:				3
	<pre>def change(Line): alpha=str()</pre>						
	digi=str()						
	for ch in Line:						
	if(ch.isalpha	()):					
	if(ch.islow						
		pha+ch.upper	.()				
	elif(ch.isu						
	alpha=al	pha+ch.lower	0				
	elif(ch.isdigi	.,,					
	alpha=alpl	na+ch+ch					
	print(Line)						
	print(alpha)	D1 0 =	4.115				
27	change("Vande 0		•	. 11 2			140
27.	Write the output		to (iii) based on the	table Sportsclub	given belov	w:	1*3=
	playarid		ortsclub	oouptr/	untine-	color:	3
	playerid 10001	pname PELE	sports SOCCER	BRAZIL	rating A	salary 50000	
	10001	FEDERER	TENNIS	SWEDEN	A	20000	
	10002	VIRAT	CRICKET	INDIA	A	15000	
	10004	SANIA	TENNIS	INDIA	В	5000	
	10005	NEERAJ	ATHLETICS	INDIA	A	12000	
	10006	BOLT	ATHLETICS	JAMAICA	Α	8000	
	10007	PAUL	SNOOKER	USA	В	10000	
	(i) SELE	CT DISTINCT	sports FROM Sports	sclub;			
			AX(salary) FROM Sp		BY sports		
	1, 5200		(22222)				1

		HAVING sports<	>'SNOOKER';					
	(iii)	SELECT pname,	sports, salary FROM S _I ORDER BY salary DESO		WHERE			
28.	displayw If the cor A man alv	sting text file data rords() that will patents of file is:	txt has some words wr orint all the words that we higher in his life	itten in it		1 5		3
	The output should be: always wants strive higher life wants perfect.							
	display the		OR () in Python to read lin ine in file and lines whi					
	An apple in We should India is on The count The number The number 1997.	e of the biggest co Lines() function er of lines in file a er of lines ending	doctor away. ne's safety and security untry in word. should display the ou	itput as:				
29.	keep ready	y for tax calculatio s in the table.	MNC. She created a tab n. After creation of the	table, she	e has ente			1*3= 3
	emp_id		emp_desig	+ basic		+ hra	++ nps	
	E01 E02 E03	Naveen Roy Pawan Ahuja Kalpana Rani Govind Mishra	Manager Junior Clerk Public Expert	70000 20000 50000 90000 80000	2000 5000 40000	2500 4500 11500	7000 2000 2500 900 850	
			ove write the SQL Queri e Emp_Name and Gross hra+nps)		each em	ployee. (Gross=	
		(ii) Increase th	ne DA by 3% of respecti	ve basic :	salary of	all emplo	yees.	
		(iii) Delete the	Attribute emp_desig fro	om the ta	ble.			
30.	data) wh push all t Also writ	ere stack is an em	populate the contents of apty list and data is the re even to the stack. p(stack) that removes	list of nu	ımbers.T	he functi	on should	3
	Also write	e the function calls	5.					

31.	Muitat	ho COL guaria	na (i) ta (i		SECTION-D	UOOL and	ADMIN given below:	1*4_4
31.	write t	ne SQL querie	28 (1) to (1			nool and .	ADMIN given below:	1*4=4
	200				SCHOOL		49	
	CODE TEACHERNAME SUBJECT DOJ PERIODS EXPERIENCE							
	1001	RAVI SHAN	KAR	ENGLISH	12/03/2000	24	10	
	1009	PRIYA RAI	D	PHYSICS	03/09/1998	26	12	
	1203	LISA ANAN YASHRAJ	D	ENGLISH MATHS	09/04/2000 24/08/2000	27	15	
	1123	GANAN		PHYSICS	16/07/1999	28	3	
	1167	HARISH B		CHEMISTR		27	5	
	1215	UMESH		PHYSICS	11/05/1998	22	16	
				TABLE:	3			
			CODE	GENDER	DESIGNATION	1		
			1001	MALE	VICE PRINCIP	AL		
			1009	FEMALE	COORDINATO	R		
			1203	FEMALE	COORDINATO	R		
			1045	MALE	HOD			
			1123	MALE	SENIOR TEAC	HER		
			1167	MALE	SENIOR TEAC	HER		
			1215	MALE	HOD	3.9		
		L queries for		_				
	-	y total period	•					
	, ,				num code from			
		gnation "COO			both tables on t	iie basis oi	f CODE attribute for	
	•	_			ıbjects in school	relation.		
32.	Write a l		ython tha	t defines and	d calls the follow	ing user d	efined functions:	4
	_	To accept re					he record of player	
		_	, P_name	and P_runs i	n form of pytho	n list.		
	Displa	y_Record():	maaamda a	f Dlarray fyan	n (plassandata aar	J filo and a	diamless the meaned of	
		player whos		-	• •	/ file and (display the record of	
				खंड / S	ECTION-E			
33					omputer networ			1*5=5
	campus having four buildings. Each block has a number of computers that are required							
					, resource sharii	_	_	
	rou as a	network exp	ert nave	to suggest an	iswers to these j	parts (a) to	o (e) raised by them.	
				\neg				
		DEVE	LOPMEN'	Γ	HUMAN	RESOURCI	<u> </u>	
			LOGISTIC	S	ADM			
	O		.					
		st distances			o cks ESOURCE 50	l m		
		EVELOPMEN EVELOPMEN				5 m		
	2100H D		. 1 00 2100	· • •• • • •	7.5			

	Block DEVELOPMENT to Block LOGISTICS 80 m	
	Block HUMANRESOURCE to Block ADM 110 m	
	Block ADM to Block LOGISTICS 140 m	
	Number of computors installed at various blocks	
	Number of computers installed at various blocks	
	Block Number of Computers DEVELOPMENT 105	
	HUMANRESOURCE 130	
	ADM 190	
	LOGISTICS 55	
	a) Suggest the most suitable block to host the server. Justify your answer.	
	b) Suggest the wired medium and Draw the cable layout (Block to Block) to	
	economically connect various blocks.	
	c)Suggest the placement of the following devices with justification:	
	(i) Hub/Switch (ii) Repeater	
	d)Suggest the device that should be placed in the Server building so that they can	
	connect to Internet Service Provider to avail Internet Services.	
	e) Suggest the high-speed wired communication medium between Bangalore Campus	
	and Mysore campus to establish a data network.	
34	(i) What is CSV means? Which packages/modules are imported for using Binary Files	2+3= 5
	and CSV files in Python?	
	(ii) Abhay have a binary file called library.dat containing book information- B_id, B_name	
	and B_price of each book.	
	[[B_id, B_name, B_price],[B_id, B_name, B_price],]	
	Write the user defined function Trace_Book() to show the records of books having the	
	price less than 1000. In case there is no book having price <1000 the function displays	
	message "Such Record not found".	
	OR	
	(i) Write any two difference between text file and binary file.	
	(1) Write any two difference between text me and binary me.	
	(ii) Mayur is a student, who have a binary file called STUDENT.DAT containing employee	
	information- sid, name and age of each student.	
	[sid, name, age]	
	Write the user defined function Get_Stud() to display the name and age of those student	
	who have a age greater than 18 year. In case there is no student having age >18 the	
	function displays message "There is no student who is greater than 18 year".	
35	(i) What is the difference between a Candidate Key and an Alternate Key.	1+4=5
	(ii) Virat has created a table named TRAVELS in MySQL:	
	Tour_ID – string	
	Destination – String	
	Geo_Cond- String	
	Distance – integer (In KM)	
	Note the following to establish connectivity between Python and MYSQL:	
	Username is root	
	Password is bharat	
	• The table TRAVELS exists in a MYSQL database named TOUR. The datable Trave ID. Destination Case Cond and Distance are to be assented from the	
	• The details Tour_ID, Destination, Geo_Cond and Distance are to be accepted from the	
	user.	
	Virat wants to display All Records of TRAVELS relation whose Geographical condition	
	That mans to display All records of Travels felation whose deographical condition	<u>. </u>

is hilly area and distance less than 1000 KM. Help Virat to write program in python.

OR

- (i) Write one point of difference between PRIMARY KEY and UNIQUE KEY in SQL.
- (ii) Aarya has created a table named Emp in MySQL:

EmpNo – integer

EmpName – string

Age-integer

Salary – integer

Note the following to establish connectivity between Python and MYSQL:

- Username root
- Password tiger
- Host localhost
- The Emp table exists in a MYSQL database named **company**.
- The details of Emp table (EmpNo, EmpName, Age and Salary)

Aarya wants to display All Records of Emp relation whose age is greater than 55. Help Aarya to write program in python.

KENDRIYA VIDYALAYA SANGATHAN, JAIPUR REGION

PreBoard-I Examination 2023-24

Class-XII


Subject: Computer Science (083) Answer Key

	SF	CTION-A		
QN.	Answer of Question	CHON-A		
1.	Ans. False		1	
2.	Ans. (c) alter			
3.	Ans: (d) dict_student.update(dict_marks)			
4.	Ans. (b) True			
5.	Ans. (b) DELETE Command		1	
6.	Ans: (c) HomePage		1	
7.	Ans. (c) None		1	
8.	Ans. (a) Year . O. at All the best			
9.	Ans. (b) Statement 4		1	
10.	Ans. (c) 512		1	
11.	Ans: (d) PAN		1	
12.	Ans. (b) W*		1	
	B*			
13.	Ans. (a) Pickling		1	
14.	Ans. (b) DISTNICT		1	
15.	Ans. Topology		1	
16.	Ans. (a) Mycur.fetch()			
17.	Ans. (c) A is True but R is False			
18.	·			
		CTION-B		
19.	(i) Advantage: The network remains of stopsworking. (1 mark for any ONE a	oice) and video over internet(1 mark) OR Operational even if one of the nodes	2	
	(ii) Hub	Switch		
	Hub is a passive Device	Switch is an active device	_	
	Hub broadcasts messages to all nodes Or any other valid difference betwee	Switch sends the messages to intended node.		
	(1 mark for ANY ONE difference)	ii tile two.		
20.	<pre>def reverse(num): rev = 0 while num > 0: rem == num %10 rev = rev*10 + rem num = num//10 return rev print(reverse(1234)) (% Mark for each correction up to any)</pre>	«A corrections)	1+1 =2	

```
def INDEX LIST(L):
21.
                                                                               1+1=
               indexList=[]
                                                                              2
               for i in range (len(L)):
                     if L[i]!=0:
                           indexList.append(i)
               return indexList
         (1/2 mark for correct function header
         1 mark for correct loop
         1 mark for correct if statement
         1/2 mark for return statement)
         Note: Any other relevant and correct code may be marked
                                         OR
    def Count How Many(Data, item):
      count=0
      for n in Data:
        if(n==item):
          count+=1
      print(item, " found ", count, "times")
    d=[101,102,107,105,102,103,104,102]
    i=102
    Count_How_Many(d,i)
         or any other correct logic
22.
     ['H', 'A', 'P', 'P', 'Y'] ['B', 'I', 'R', 'T', 'H', 'D', 'A', 'Y']
     (i) str="PYTHON@LANGUAGE"
23.
                                                                                2
        print(str[2::])
     (ii) d=dict()
                                       OR
     (i) s="LANGUAGE"
        l=list(s)
     (ii) t=tuple()
                                                                                2
24.
     COUNT(*) returns the count of all rows in the table, whereas COUNT
     (COLUMN NAME) is used with Column Name passed as argument and
     counts the number of non-NULL values in a column that is given as
     argument. Here discount column is having 4 rows with NULLvalues.
                                       OR
        Use KVS; (1/2 mark)
        Show Tables; (1/2 mark)
        Desc EMPLOYEE;
        (1/2 MARK)
        Select * from EMPLOYEE; (1/2 MARK)
                                                                                2
25.
     {20: 3, 19: 3, 17: 2}
                                     SECTION-C
                                                                                 3
26.
    Vande 0 Bharat 9 Train 1
    vANDE00bHARAT99tRAIN11
    (3 marks for correct answer. Partial marks may be given for partially
    correct answer.)
    (1 mark for each correct output)
                                                                                1*3
                                                                                =3
```

```
(i)
     sports
      SOCCER
      TENNIS
      CRICKET
      ATHLETICS
      SNOOKER
    ii)
     Sports
                      MAX(salary)
      SOCCER
                           50000
                           20000
      TENNIS
      CRICKET
                           15000
     ATHLETICS
                           12000
     iii)
                                       salary
      pname
                      sports
                                       15000
      VIRAT
                      CRICKET
     NEERAJ
                      ATHLETICS
                                       12000
     SANIA
                      TENNIS
                                       5000
28.
    def displaywords ():
                                                                                   3
        file = open('data.txt','r')
        st=file.read()
        lst=st.split()
        for k in lst:
           if len[k] > 3:
              print(k, end=" ")
        file.close()
    displaywords ()# Call the displaywords
    (½ mark for function header, 1 mark for opening file,
     1 mark for correct for loop and condition, ½ mark for closing file)
                                        OR
    def count lines():
         f=open("student.txt",'r')
         rows=f.readlines()
         end y=not y=0
         for rec in rows:
           if(rec[-1]=='y'):
             end y+=1
           else:
             not_y+=1
         print("The number of lines in file are", len(rows))
         print("The number of lines ending with alphabet 'y' are:",end y)
         print("The number of lines not ending with alphabet 'y' are:",not y)
    count lines()
    #call the function
    (½ mark for function header, 1 mark for opening file,
    1 mark for correct for loop and condition,½ mark for closing file)
                                                                                   1*3
    (i) SELECT EMP_NAME, BASIC+DA+HRA+NPS AS "GROSS SALARY" FROM
                                                                                   =3
    SALARY:
    (ii) UPDATE SALARY SET DA=DA+0.03*BASIC;
    (iii) ALTER TABLE SALARY DROP COLUMN EMP_DESIG;
```

```
30.
                                                                                    3
      data = [1,2,3,4,5,6,7,8]
      stack = []
      def push(stack, data):
         for x in data:
           if x \% 2 == 0:
             stack.append(x)
      def pop(stack):
        if len(stack)==0:
           return "stack empty"
           return stack.pop()
      push(stack, data)
      print(pop(stack))
      (½ mark should be deducted for all incorrect syntax. Full marks to beawarded
      for any other logic that produces the correct result.)
                                       SECTION-D
                                                                                    1*4
31.
     i)SELECT SUM (PERIODS), SUBJECT FROM SCHOOL GROUP BY SUBJECT;
                                                                                    =4
     ii) SELECT MIN(EXPERIENCE), MAX(CODE) FROM SCHOOL:
     iii) SELECT TEACHERNAME, GENDER FROM SCHOOL, ADMIN WHERE
        DESIGNATION = 'COORDINATOR' AND SCHOOL.CODE=ADMIN.CODE;
     iv)SELECT COUNT(DISTINCT SUBJECT) FROM SCHOOL;
     (1 mark for each correct query)
32.
                                                                                   2+2=
     import csv
     def Add New():
           fout=open("playerdata.csv ","a",newline='\n')
           wr=csv.writer(fout)
           P id=int(input("Enter Player Id :: "))
           P name=input("Enter Player name :: ")
           P runs=int(input("Enter price :: "))
           playerlist=[P-id,P_name,P_runs]
           wr.writerow(playerlist)
           fout.close()
     def Display Record():
           fin=open("playerdata.csv ","r")
           data=csv.reader(fin)
           found=False
           print("The Player Records are: ")
           for Rec in data:
                 if int(rec[2])>5000:
                     found=True
                     print(rec[0],rec[1],rec[2])
           if found==False:
                print("Such Record not found")
     Add New():
     Display Record():
     (½ mark for importing csv module)
     (11/2 marks each for correct definition of Add New() and
     Display Record ())
     (½ mark for function call statements)
```



	Get_Stud()			
35.	(i)Any one difference:			1+4=
	CANDIDATE KEY		ALTERNATE KEY	5
	All attributes in a relation thathave pote	ential to	All the leftover candidate keys	
	become a Primary key		after selecting the primary key	
	(ii) import mysql.connector as BD def Emp_Database(): con=BD.connect(host="localhost"	ne dista AVELS V	nce more than 1000 KM.:")	
	OF (i)Any one difference:	R		
	PRIMARY KEY		UNIQUE KEY	
	There can be only one primary key in a table		can be more than one unique a a table	
	The primary key cannot have null values	Uniqu	e can have null values	
	(ii) import mysql.connector as cnt def Emp_Database():	any") ge is m	ore than 55 years:")	

केंद्रीय विद्यालय संगठन, जयपुर संभाग

Kendriya Vidyalaya Sangathan, Jaipur Region प्रथम प्री-बोर्ड परीक्षा 2023-24

First Pre-Board Exam 2023-24

कक्षा/Class: XII विषय/Subject : Computer Science (083)

समय : 3 घंटे पूर्णांक/**Max Marks: 70**

सामान्य निर्देश / General Instructions:

- Please check this question paper contains 35 questions.
- The paper is divided into 5 Sections- A, B, C, D and E.
- Section A, consists of 18 questions (1 to 18). Each question carries 1 Mark.
- Section B, consists of 7 questions (19 to 25). Each question carries 2 Marks.
- Section C, consists of 5 questions (26 to 30). Each question carries 3 Marks.
- Section D, consists of 2 questions (31 to 32). Each question carries 4 Marks.
- Section E, consists of 3 questions (33 to 35). Each question carries 5 Marks.
- All programming questions are to be answered using Python Language only.

	खंड / SECT	ΓΙΟΝ-A	
प्रश्न सं Q. No.	प्रश्न / Que	estion	अंक / Marks
1	State True or False: "Lexical unit is the smallest unit of any pr	ogramming language"	1
2	Fill in the blank:command is used to remove the t (a) update (c) alter	uple from the table in SQL. (b) remove (d) delete	1
3	What will be the output of the following st print ((30.0 // 4 + (8 + 3.0)) a. 14.75 c18.0	atement: b. 18.0 d. Error	1
4	Select the correct output of the code: >>> Str= "BHASHA SANGAM @ 75" >>> S=Str.partition(" ") >>> print(S) a. (@ 75' 'BHASHA', ' ', 'SANGAM,) b. ('BHASHA', ' @', 'SANGAM , 75') c. (", ' ', 'BHASHA SANGAM @ 75') d. ('BHASHA', ' ', 'SANGAM @ 75')		1

5	In MYSQL database, if a table, Em	p has degree 10 and cardinality 5, and	1	
	another table, Dept has degree 5 at	nd cardinality 10, what will be the degree		
	and cardinality of the Cartesian prod	duct of Emp and Dept ?		
	a. 50,15 b. 1	15,50		
	c. 50,50 d. 1	15,15		
6	Ankur wants to transfer songs from	his mobile phone to his laptop. He uses	1	
	Bluetooth Technology to connect tw	o devices. Which type of network will be		
	formed in this case?			
	a. PAN	b. LAN		
	c. MAN	d. WAN		
7	Give the output: dic1={ 'r':'red','g':'green'	,'b':'blue'}	1	
	for i in dic1:			
	print (i, end =' ')			
	a.rgb	b. R G B		
	c. R B G	d. red green blue		
8	Consider the statements given below and then choose the correct output			
	from the given options:			
	MN="Bharat @G20"			
	print(MN[-2:2:-2])			
	Options:			
	a. rt@2	b. 2@tr		
	c. @G20	d. 02G@		
9	Which of the following statement(s) executing the following code?	would give an error after	1	
	S="Welcome to KVS RO JAIPUR "	# Statement 1		
	print(S)	# Statement 2		
	S="Thank you"	# Statement 3		
	S[0]= '\$'	# Statement 4		
	S=S+"Thank you"	# Statement 5		
	(a) Statement 3			
	(b) Statement 4 (c) Statement 5			
	(c) Statement 5 (d) Statement 4 and 5			
	, ,			

```
What possible outputs(s) will be obtained when the following code is
10
                                                                                1
       executed?
       import random
       Signal=['Stop','Wait','Go']
       for K in range (2,0,-1):
           R=random.randrange(K)
           print(Signal[R], end='#')
       options:
       a. Stop#Go#
       b. Wait#Stop#
       c. Go#Stop#
       d. Go#Wait#
11
       Fill in the blank:
                                                                                1
       .....is a communication methodology designed to deliver emails over
       Internet protocol.
          a. VIOP
          b. SMTP
          c. PPP
          d. HTTP
12
       Consider the code given below and find correct output:
      x=5
      def function1():
             global x
             y=x+x*2
             print(y,end=",")
      x = 7
      function1()
      print(x)
       Output:
          a. 21,7
          b. 15,5
          c. 21,5
          d. 15, 7
```

13	State whether the following statement is True or False:	1
	Exception handling can be done for both user-defined and built-in exceptions.	
14	Which of the following statements is FALSE in reference to MySQL? a. It is an RDBMS. b. It is case sensitive. c. It is an open source. d. It is ideal for both small and large applications.	1
15	Fill in the blank:	1
	In case ofswitching, each information or message to be	
	transmitted between sender and receiver is broken down into smaller pieces.	
16	Which method is used to move the file pointer to a specified position.?	1
16		'
	a.tellg()	
	b.tell() c.seek()	
	d.seekg()	
	Q17 and 18 are ASSERTION AND REASONING based questions. Mark the correct choice as (a) Both A and R are true and R is the correct explanation for A	
	(b)Both A and R are true and R is not the correct explanation for A	
	(c) A is True but R is False	
	(d)A is false but R is True	
17	Assertion(A): Access mode 'a' opens a file for appending.	1
	Reasoning(R): The file pointer is at the end of the file if the file exists.	
18	Assertion(A): A function is block of organized and reusable code that is used to perform a single, related action.	1
	Reasoning(R): Function provides better modularity for your application and a high	
	degree of code reusability.	

	खंड / <u>SECTION B</u>	
19	(i) Expand the following terms: SMTP, IMAP	1+1=
	(ii) Give one difference between Active Hub and Passive Hub.	
	OR	
	(i) Define the term Protocol with respect to networks.	
	(ii) How is Hub different from Switch?	
20	Harsh has written a code to input a number and find a table of any number. His	2
	code is having errors. Rewrite the correct code and underline the corrections made.	
	<pre>def table(): n=int(("Enter number which table U need: ") for i in (1,11):</pre>	
	<pre>print("Table of Enter no=",i*i) Table()</pre>	
21	Write a function countMy(SUBJECT) in Python, that takes the dictionary,	2
	SUBJECT as an argument and displays the names (in uppercase) of the	
	subjects whose names are longer than 5 characters. For example, Consider the following dictionary	
	SUBJECT={1:"Hindi",2:"Physics",3:"Chemistry",4:"cs",5:"Math"}	
	The output should be:	
	PHYSICS	
	CHEMISTRY	
	OR	
	Write a function, lenLines(STRING), that takes a string as an argument	
	and returns a tuple containing length of each word of a string.	
	For example, if the string is " let us learn Python", the	
	tuple will have (3, 2, 5, 6)	

```
22
       Predict the output of the following code:
       tuple1 = (11, 22, 33, 44, 55, 66)
       list1 =list(tuple1)
       new list = []
       for i in list1:
            if i%2==0 :
                 new list.append(i)
            new tuple = tuple(new list)
       print(new tuple)
       Write the Python statement for each of the following tasks using BUILT-IN
23
                                                                                      1+1=
                                                                                        2
       functions/methods only:
          (i)
                To insert an element 100 at the Second position, in the list L1.
          (ii)
                To check whether all the characters in the string S1 are digits or not.
      How the pop() function is different from remove() function working with
      list in python? Explain with example.
24
      Pooja wrote a query in SQL for student table but she is not getting desired result
       select * from student where fee = NULL;
        Rewrite the above query so that she gets desired result
                                            OR
        Categorize the following commands as DDL or DML:
        INSERT, ALTER, DROP, DELETE, UPDATE, CREATE
25
                                                                                        2
       Predict the output of the following code:
       def Diff(N1,N2):
            if N1<N2:
                 return N1-N2
            else:
                 return N2*N1
       NUM=[10,23,14,54,32]
       for CNT in range (4,0,-1):
            A=NUM[CNT]
            B=NUM[CNT-1]
            print(Diff(A,B),'#', end=' ')
```

खंड / <u>SECTION C</u> 26 Predict the output of the Python code given below: 3 def my city (L,N): for i in range (0, N): if len(L) > 4: L[i]=L[i]+L[i]L[i]=L[i] sub=['Delhi','Jaipur','Agra','Surat','Mumbai','Bhopal'] my city(sub, 6) print(sub) Write the outputs of the SQL queries (a) to (c) based on the relation Furniture 27 1*3 Itemname Dateofstock **Price** Discount No Type 3 White lotus Double Bed 23/02/2002 30000 25 1 Pink feather 7000 20 2 Baby Cot 20/01/2002 3 Dolphin Baby Cot 19/02/2002 9500 20 4 Decent Office 01/01/2002 25000 30 Table Comfort Double Bed 12/01/2002 25000 25 5 Zone Baby Cot Donald 24/02/2002 6500 15 6 7 Royal finish Office 20/02/2002 18000 30 Table Royal tiger Sofa 22/02/2002 31000 30 8 9 Econo sitting Sofa 13/12/2001 9500 25 10 paradise Dining 19/02/2002 11500 25 Table 11 Wood Double Bed 23/03/2003 25000 25 Comfort Old Fox 20/02/2003 17000 20 12 Sofa 13 Micky Baby Cot 21/02/2003 7500 15 (a) SELECT Itemname FROM Furniture WHERE Type="Double Bed"; (b) SELECT Dateofstock FROM Furniture WHERE Type="Sofa" order by Dateofstock; (c) SELECT Type, sum(Price) FROM Furniture group by Type; Define a function SHOWWORD () in python to read lines from a text file 3 28 STORY.TXT, and display those words, whose length is less than 5. OR Write a user defined function in python that displays the number of lines starting with 'H' in the file para.txt

E_ID	Name	Desig	Salary	Allowance]
- -				7 0	
E01	Ramesh	Manager	80000	5400	_
E02	Kailash	Clerk	NULL	2400	-
E03	Rudra	Supervisor	48000	NULL	
E04	Sakila	Clerk	30000	2000	_
E05	Prachi	Supervisor	NULL	2800	
€	employees. The lisplayed.	column headin	g 'Total Sala	ary and Allowand ary' should also b alary greater thai	e e
€ C	employees. The lisplayed.	column headin	g 'Total Sala	ary' should also b	e e
(iii) [Mr.Abhish python wielement authem to action to	employees. The displayed. Delete the recornect has created the functions, Find delete an elect as push and part of the functions of the functions.	column heading d of employess d a list of element from a Lement from a Lement oop operations	g 'Total Sala who have s ents. Help h ent) and P List of eleme of the Stack	ary' should also be alary greater than alary greater to alary greater than alary greater	oe n 40000 ogram i d a nev nsiderin
(iii) [Mr.Abhish python wi element and them to accelement in the second content of the	employees. The displayed. Delete the recornek has created the functions, Find delete an elect as push and push to the stack online.	column heading d of employess d a list of element from a Lement from a Lement from soop operations by when the element from t	g 'Total Sala who have s ents. Help h ent) and P List of eleme of the Stack	ary' should also be alary greater than alary greater to alary greater than alary greater	oe n 40000. ogram i d a nev nsiderin
(iii) [Mr.Abhish python wi element and them to accelement in the second content of the	employees. The displayed. Delete the recornect has created the functions, Find delete an elect as push and part of the functions of the functions.	column heading d of employess d a list of element from a Lement from a Lement from soop operations by when the element from t	g 'Total Sala who have s ents. Help h ent) and P List of eleme of the Stack	ary' should also be alary greater than alary greater to alary greater than alary greater	oe n 40000. ogram i d a nev nsiderin
Mr.Abhish python wi element at them to ac element in	employees. The displayed. Delete the recornek has created the functions, Find delete an elect as push and push to the stack online.	column heading d of employess d a list of element from a Lement from a Lement from soop operations by when the element from t	g 'Total Sala who have s ents. Help h ent) and P List of eleme of the Stack	ary' should also be alary greater than alary greater to alary greater than alary greater	oe n 40000. ogram i d a nev nsiderin
Mr.Abhish python wi element at them to ac element in	employees. The displayed. Delete the recornect has created the functions, Find delete an elet as push and push to the stack onlete for	column heading d of employess d a list of element from a Lement from a Lement from soop operations by when the element from t	g 'Total Sala who have s ents. Help h ent) and P List of eleme of the Stack	ary' should also be alary greater than alary greater to alary greater than alary greater	n 40000. ogram i d a nev

			ख	is / S	ECTIO	N D			
31	Consider the	doctor an					output of (i) to	o (iv)	1*4=
			-				. ,	. ,	4
				_	octor				
			Dname		cializati		Outdoor		
			MANISH PARESH	EYE	<u>/SICIAN</u>		MONDAY FRIDAY		
			KUMAR	ENT			SATURDAY		
			AKASH	ENT			TUESDAY		
		2.	7 11 0 1011				10202711		
		Did	Dnome	Pa	atient	Dot	a viait	۱	
		Pid P1	Pname Lal singh	,	did D2		e_visit 2-04-25	_	
		P2	Arjun	l	D1		2-04-25 2-05-05	_	
		P3	Narende	r	D4		2-03-13	-	
		P4	Mehul	<u> </u>	D3	_	2-07-20	_	
		P5	Naveen		D2	202	2-05-18		
		P6	Amit		D1	202	2-01-22		
							(2/ 2 .		
	(I) sele	ect count(*) from patie	ent wh	nere dat	e_vis	sit like '%2_';		
	(II) sele	ect specia	ılization ,coບ	ınt(*)	from do	ctor	group by spe	cialization;	
	, ,	•		` ,				e a.docid=b.did;	
	(IV) sele	ect dname	e from docto	r,pati	ent whe	re do	cid=did and	pname='Arjun';	
32	A csv file " res [rollno,		ontains reco b1,sub2,sub			t in fo	llowing order		4
	['2', '	Anil', '40', Sohan', '7	ld is empty s , '34', '90', "] 78', '34', '90' 40', '45', '9',	, "]	as exa	mple	data is given	below	
	A another file records after of should be							csv" and copy all of final.csv	
	['1', 'Anil', '40', '34', '90', '164'] ['2', 'Sohan', '78', '34', '90', '202'] ['3', 'Kamal', '40', '45', '9', '94']								
	(a) Define a function createcsv() that will create the result.csv file with the sample data given above.								
	(b) Define a function copycsv() that reads the result.csv and copy the same data after calculating total field into final.csv file.								

खंड / <u>SECTION E</u>	
M/s Computer Solutions is a professional consultancy company. The company is planning to set up their new offices in India with its hub at Hyderabad. As a network adviser, you have to understand their requirement and suggest them the best available solutions. Their queries are mentioned as (i) to (v) below.	1*5= 5
Physical locations of the blocks of M/s Computer Solutions	
HR BLOCK MEETING BLOCK	
FINANCE BLOCK	
Block to block distance (in m) Block (From) Block (To) Distance HR Block MEETING 110 HR Block Finance 40 MEETING Finance 80 Expected number of computers Block Computers HR 25 Finance 120 MEETING 90	
(i) Which will be the most appropriate block, where M/s Computer Solutions should plan to install their server?	
(ii) Draw a block to block cable layout to connect all the buildings in the most appropriate manner for efficient communication.	
 (iii) What will be the best possible connectivity out of the following, you will suggest to connect the new set up of offices in Bengalore with its London based office. Satellite Link Infrared Ethernet 	
 Ethernet (iv) Which of the following device will be suggested by you to connect each computer in each of the buildings? Switch Modem Gateway 	
(v) Company is planning to connect its offices in Hyderabad which is less than 1 km. Which type of network will be formed?	

34		2+3= 5
	(i) Differentiate between rb+ and wb+ file modes in Python.(ii) Consider a binary file "employee.dat" containing details such as	
	(empno, ename, salary). Write a python function to	
	display details of those employees who are earning between 20000 and	
	30000 (both values inclusive).	
	OR (i) Differentiate between dump and load functions in binary files?	
	(ii) Write a Python function in Python to search the details of the employees	
	[name, designation, salary] whose salary is greater than 5000. The	
	records are stored in the file "emp.dat". consider each record in the file	
	emp.dat as a list containing name, designation and salary.	
35	(i) How many candidate key and primary key a table can have in a Database?	1+4= 5
	 (ii) Manish wants to write a program in Python to create the following table named "EMP" in MYSQL database, ORGANISATION: Eno (Employee No)- integer, Ename (Employee Name) - string Edept (Employee Department)-string, Sal (salary)-integer Note the following to establish connectivity between Python and MySQL: Username – root, Password – admin, Host - localhost The values of fields eno, ename, edept and Sal has to be accepted from the user. Help Manish to write the program in Python to insert record in the above table 	
	OR	
	(i) Differentiate between degree & cardinality key in RDBMS?	
	(iii) Vihaan wants to write a program in Python to create the following table named "EMP" in MYSQL database, ORGANISATION: Eno (Employee No)- integer, Ename (Employee Name) - string Edept (Employee Department)-string, Sal (salary)-integer Note the following to establish connectivity between Python and MySQL: Username – root, Password – admin, Host - localhost Help Vihaan to write the program in Python to Alter the above table with new column named Bonus (int).	

Class XII

Computer Science (083)

Marking Scheme

Time Allowed: 3 hours MM: 70

Ques No	Question and Answers	Distribution of Marks	Total Marks			
	SECTION A					
1	True	1 mark for	1			
		correct				
		answer				
2	Option d	1 mark for	1			
		correct				
	delete	answer				
3	Option b	1 mark for	1			
		correct				
	18	answer				
4	Option d	1 mark for	1			
	('BHASA', ' ', 'SANGAM@75')	correct				
		answer				
5	Option b	1 mark for	1			
		correct				
	15,50	answer				
6	Option a	1 mark for	1			
	PAN	correct				
	FAIN	answer				
7	Option a	1 mark for	1			
		correct				
	r g b	answer				
8	Option b	1 mark for	1			
	2@tr	correct	_			
		answer				

9	Option b	1 mark for	1
		correct	
	Statement 4	answer	
10	Option b	1 mark for	1
		correct	
	Wait#Stop#	answer	
11	Option b	1 mark for	1
		correct	
	SMTP	answer	
12	Option a	1 mark for	1
		correct	
	21	answer	
	7		
13	True	1 mark for	1
		correct	
		answer	
14	Option b	1 mark for	1
		correct	
	It is case sensitive	answer	
15	Packet	1 mark for	1
		correct	
		answer	
16	Option c	1 mark for	1
		correct	
	seek()	answer	
17	Option a	1 mark for	1
	Both A and R are true but R is the correct explanation for A	correct	
	1	answer	

18	Option a	1 mark for	1
	Both A and R are true but R is the correct explanation for A	correct answer	
	SECTION B		
19	(i) SMTP – Simple Mail Transfer Protocol IMAP – Internet Message Access Protocol (ii)	½ mark for each correct expansion	1+1=2
	Active hubs amplify the incoming electric signal, whereas passive hubs do not amplify the electric signal. (Any other valid difference may be considered)	1 mark for any one correct difference	
	OR		
	 (i) A network protocol is an established set of rules that determine how data is transmitted between different devices in the same network. (ii) Hub is an electronic device that connects several nodes to form a network and redirect the received information to all the nodes in a broadcast mode. Whereas Switch is an intelligent device that connects several nodes to form a network and redirect the received information only to the intended node(s). (Any other valid difference may be considered) 	1 mark for correct definition 1 mark for any one correct difference	
20	<pre>def table (): n=int (input ("Enter number which table U need: ")) for i in range (1,11): print ("able of Enter no=",i*n) table ()</pre>	½ mark for each correction made	2

21		½ mark for	2
	SUBJECT={1:"Hindi",2:"Physics",3:"Chemistry",4:"CS",5:"MATH"}	correct	
		function	
	def countMy (SUBJECT):	header	
	for S in SUBJECT.values(): if len(S)>5:	½ mark for	
	print(S.upper())	correct loop	
	countMy()	½ mark for	
	Countiny()	correct if	
		statement	
		½ mark for	
		displaying	
		the output	
	OR		
		½ mark for	
	1.C1 L' (CTDDLC)	correct	
	def lenLines (STRING):	function	
	t=() L=STRING.split()	header	
	for line in L:	½ mark for	
	length=len(line)	using split()	
	t=t+(length,)	½ mark for	
	return t	adding to	
		tuple	
		½ mark for	
		return	
		statement	
22	Note: Any other correct logic may be marked	1½ mark for	2
	(22, 44, 66)	each correct	~
		digit	
		½ mark for	
		parenthesis	

23	(i) L1.insert(1,100)	1 mark for	1+1=2
	(ii) S1.isdigit()	each correct statement	
	pop() function removes the last value and returns the same. >>>L=[10,20,30,20] >>> L.pop () 20 The remove() method removes the first matching value from the list. >>>L.remove (20) [10, 30, 20]	1 mark for correct difference and 1 mark for suitable example	
24	SQL Command to add primary key: select * from student where fee IS NULL	2 mark for correct Command	2
	OR	4	
	DDL : CREATE, ALTER DROP DML: INSERT UPDATE DELETE	1 mark for each correct DDL & DML Categorized commands	
25	-22 # 756 # -9 # 230 #	½ mark for each correct number and ½ mark for each correct # symbol	2
	SECTION C		
26	['DelhiDelhi', 'JaipurJaipur', 'AgraAgra', 'SuratSurat', 'MumbaiMumbai', 'BhopalBhopal']	½ mark for each correct output	3

27	(a) Item Name White lotus Comfort Zo Wood Com	13/12/2001 one 22/02/2002	(c) Type Sum(Price) Double Bed 80000 Baby Cot 30500 Office Table 43000 Sofa 57500 Dining Table 11500	1 mark for each correct output.	=3
28	line = file.rea word = line.s for w in word if len(w) print(w) file.close() def count H(): f = open ("palines =0 L=f. readlines for i in L: if i [0]== ' lines +:	STORY.TXT,'r') ad() split() d: <5:) ara.txt", "r") es () H':	OR	(½ Mark for opening the file) (½ Mark for reading line and/or splitting) (½ Mark for checking condition) (½ Mark for printing word)	
29	(ii) UP SE WH (iii) SE "T	DATE EMP T Salary=Sala ERE Allowance	lary + Allowance AS FROM EMP;	1 mark for each correct query	:3

30 N=[12, 13, 34, 56, 21, 79, 98, 22, 35, 38]	1½ marks for	3
def PUSHEl(S,N):	each Push	
S.append(N)		
<pre>def POPEl(S):</pre>	and Pop	
if S!=[]:	operation	
return S.pop()		
else:		
return None		
ST=[]		
for k in N:		
if k%4==0:		
PUSHEl (ST, k)		
while True:		
if ST!=[]:		
<pre>print(POPEl(ST),end=" ")</pre>		
else:		
break		
CECTION D		

SECTION D

31	(i)	1 r	mark for 1*4=4
	3		nch correct
		ou	ıtput
	(ii)		
	1		
	1		
	2		
	(iii)		
		Dname Pname	
		PARESH Lal singh	
		MANISH Arjun	
		AKASH Narender	
		KUMAR Mehul	
		PARESH Naveen	
		MANISH Amit	
	(iv)		
	Manish		

```
½ mark for
32
                                                                                        4
      import csv
                                                                        accepting
      def createcsv():
                                                                        data
            f=open("result.csv","w", newline="")
                                                                        correctly
            w=csv.writer(f)
            w.writerow([1,'Anil',40,34,90,""])
                                                                        ½ mark for
            w.writerow([2, 'Sohan', 78, 34, 90, ""])
                                                                        opening and
            w.writerow([3,'Kamal',40,45,9,""])
            f.close()
                                                                        closing file
                                                                        ½ mark for
      import csv
      def copycsv():
                                                                        writing
            f=open("result.csv","r")
                                                                        headings
            f1=open("final.csv","w",newline="")
            w1=csv.writer(f1)
                                                                        ½ mark for
            r=csv.reader(f)
                                                                        writing row
            for x in r:
                  x[5] = int(x[2]) + int(x[3]) + int(x[4])
                                                                        ½ mark for
                  w1.writerow(x)
      f.close()
                                                                        opening and
      f1.close()
                                                                        closing file
                                                                        ½ mark for
                                                                        reader object
                                                                        ½ mark for
                                                                        print heading
                                                                        ½ mark for
                                                                        printing data
                                     SECTION E
      (i) M/s Computer Solutions should install its server in finance block as it 1 Mark of
33
                                                                                     1*5=5
                                                                       each correct
         is having maximum number of computers.
                                                                       answer
      (ii) Any suitable layout
      (iii) Satellite Link.
      (iv) Switch.
      (v) LAN
```

2.4	(*)	4	2.2.5
34	(i) rb+ Opens a file for both reading and writing in binary format. (+) the file	1 mark for	2+3=5
	pointer will be at the beginning of the file.	each correct	
		difference	
	wb+ Opens a file for both reading and writing in binary format. Overwrites	½ mark for	
	the existing file If the file exists. If the file does not exist, creates a new		
	file for reading or writing.	correctly	
	(ii) def Readfile():	opening and	
	s=open("Employee.dat", "rb+")	closing files	
	try:		
	while True:		
	r=pickle.load(s)		
	if r[2]>=20000 and r[2]<=30000:		
	print(r)		
	except:	½ mark for	
	print("end of file")	correct loop	
	OR	½ mark for	
	OK .	correct split	
		1 mark for	
		correctly	
	(i)	•	
		reading /	
	In pickle module, dump () method is used to convert (pickling) Python objects for writing data in a binary file	writing data	
	T ythor objects for writing data in a binary file	½ mark for	
	Whereas the load () function is used to read data from a binary	printing	
	file or file object.	data	
	(**)		
	(ii)		
	<pre>import pickle as p L=[]</pre>		
	<pre>with open('emp.dat','rb') as f:</pre>		
	L=p.load(f)		
	for r in L:		
	if r[2]>5000:		
	<pre>print("name=",r[0])</pre>		
	<pre>print("designation=",r[1])</pre>		
	<pre>print("salary=",r[2])</pre>		
	Note: Any other correct logic may be marked		
	110to. They other correct togic may be marked		

(i) A table can only have one primary key, but it can have multiple candidate key in a database. (any suitable example)	½ mark for correct definition	1+4=5
(ii) import mysql.connector mydb=mysql.connector.connect(host="localhost",user="root",passwd="admin",dat abase="SCHOOL") mycursor=mydb.cursor() while 1: ch=int(input("enter -1 to exit / any other no to insert record into student table")) if ch==-1: break eno=int(input("Enter Employee no")) ename=input("Enter Employee Name") edept=input("Enter dept name") sal=int(input("Enter salary")) mycursor.execute("insert into EMP values (""+str(eno)+"",""+ ename+"","" +edept + "",""+str(sal)+"")")	½ mark for correct example ½ mark for importing correct module	
mydb.commit() for x in mycursor: print(x)	correct connect()	
OR	½ mark for	
(i) Degree: The total number of attributes which in the relation is called the	correctly accepting the input	
degree of the relation. Cardinality: Total number of rows present in the Table. (any suitable example) (ii)	1½ mark for correctly displaying data	
import mysql.connector mydb=mysql.connector.connect(host="localhost",user="root",passwd="admin",databas e="SCHOOL") mycursor=mydb.cursor() mycursor.execute("alter table emp add (bonus int(3))") mycursor.execute("desc emp")		
for x in mycursor: print(x) Note: Any other correct logic may be marked		

(SET 1) Computer Science (083) PRE BOARD EXAMINATION 2023-24

Maximum Marks: 70 Time Allowed: 3 hours

General Instructions:

- 1. This question paper contains five sections, Section A to E.
- 2. All questions are compulsory.
- 3. Section A have 18 questions carrying 01 mark each.
- 4. Section B has 07 Very Short Answer type questions carrying 02 marks each.
- 5. Section C has 05 Short Answer type questions carrying 03 marks each.
- **6.** Section D has 03 Long Answer type questions carrying 05 marks each.
- 7. Section E has 02 questions carrying 04 marks each. One internal choice is given in Q35 against part c only.
- **8.** All programming questions are to be answered using Python Language only.

SECTION A				
1.	State True or False "Dictionaries in python are mutable."	1		
2.	Which of the following is an invalid identifier a)myname b)p9tv c)def d)_new	1		
3.	Which one of the following is the function to get list of keys from a dictionary dict in python? a. dict.getkeys() b. dict.getvalues() c. dict.keys() d. None Of These	1		
4.	Consider the given expression: True OR NOT False AND True Which of the following will be correct output if the given expression is evaluated? (a) True (b) False (c) NONE (d) NULL	1		
5.	Select the correct output of the code: Str="I will Succeed"	1		

	lis=str.split(" ") print(lis[-1])	
	(a) I (b) will (c) Succeed (d) "I will Succeed"	
6.	Which of the following methods will give the current position of the file pointer?	1
	(a)seek() (b)tell() (c)getloc()(d) None of the above	
7.	Fill in the blank:	1
	Command is used to change the structure of the table in SQL.	
	(a)update (b)remove (c)alter (d)drop	
8.	Which of the following commands will delete the row of the table from MYSQL database? (a) DELETE (b) DROPTABLE (c) REMOVETABLE (d) ALTERTABLE	1
9.	Which of the following statement(s) would give an error after executing the following code?	1
	T=(8,9,7,6) # Statement 1 print(T) # Statement2 T=(7,9,7,6) # Statement3 T[1]=8 # Statement4 T=T+(1,2,3) # Statement5	
	(a) Statement3(b) Statement4(c) Statement5(d) Statement 4 and 5	
10.	Fill in the blank:	1
	is an attribute or set of attributes eligible to become primary key. (a) PrimaryKey (b) ForeignKey (c) CandidateKey	

	(d) Alternate Key	
11.	The default mode of opening a file in pyhton	1
	(a) append	
	(b) read	
	(c) write	
	(d) both b and c	
12.	Which of the following can be used as command to get the structure of a table in	1
	mysql	
	(a) DESCRIBE	
	(b) UNIQUE	
	(c) DISTINCT	
	(d) NULL	
12	Fill in the blank:	1
13.	Is the protocol used for server to server mail transfer?	1
	is the protocol used for server to server man transfer?	
	(a)VoIP (b)SMTP (c)PPP (d)HTTP	
	(a) voii (b) (b) (iii (a) iii (a) iii (a)	
14.	What will the following expression be evaluated to in Python?	1
	print(2**3**2//8)	
	(a)64.0 (b)64 (c)8 (d)None Of These	
1.7	William I and I an	1
15.	Which clause is used to apply conditions with GROUP BY	1
	(a) WHERE	
	(b) HAVING	
	(c) LIKE	
	(d) None Of These	
1.0	Williah Gangdian in and to actablish an anation between mode and COI	1
16.	Which function is used to establish connection between python and SQL database?	1
	database:	
	(a) connection	
	(b) connect	
	(c) getconnection	
	(d) getconnect	
	(a) geteomicet	
017	and 18 are ASSERTION AND REASONING based questions. Mark the correct	
choic	=	
	a) Both A and R are true and R is the correct explanation for A	
(, 	

,	b) Both A and R are true and R is not the correct explanation for A c) A is True but R is False	
,	d) A is false but R is True	
17.	Assertion (A):-Functions in a program increases the modularity and readability of the program Reasoning (R):-Usage of Functions increases the execution speed of the program	1
18.	Assertion (A): If a file is opened in binary mode its contents are viewed as a sequence of bytes. Reason (R): A text file also can be opened in binary mode	1
	SECTION B	
19.	Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ")	2
	rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10 return rev	
20.	What do you mean by protocol? Give two examples	2
	OR	
	What is a MODEM? Explain its use?	
21.	(a) Given is a Python string declaration: Mystr="I will win" Write the output of: print(Mystr[2:6])	1
	(b) Write the output of the code given below: dictcount={"age1":26,"age2":32,"age3":40} sum=0 for key in dictcount: sum=sum+dictcount[key] print(sum)	1
22.	Explain the use of 'Primary Key' in a Relational Database Management System. Give example to support your answer.	2
23.	(a) Write the full forms of the following: (i) FTP (ii)TCP	2

```
(b) What is the use of POP3?
     Predict the output of the Python code given below:
24.
    def product(L1,L2):
     p=0
     for i in L1:
       for j in L2:
        p=p+i*j
     return p
    LIST=[1,2,3,4,5,6]
    11=[]
    12=[]
    for i in LIST:
     if(i\% 2==0):
      11.append(i)
     else:
       12.append(i)
    print(product(11,12))
                                          OR
     Predict the output of the Python code given below:
    tuple1 = (33, 24, 44, 42, 54, 65)
    list1 =list(tuple1)
    new_list = []
    for i in list1:
     if i>40:
      new_list.append(i)
    new_tuple = tuple(new_list)
    print(new_tuple)
     Explain the use of DISTINCT keyword in python with appropriate example
25.
                                                                                     2
                                        OR
     What is called DDL commands in mysql? Give examples?
                                        SECTION C
     a)Consider the following tables -Product and Supplier:
26.
                                                                                     1+2
     Table:Product
      Pid
                                  sid
                    pname
      P1
                     pen
                                  S1
      P2
                    ball
                                  S2
      P3
                    pencil
                                  S3
      Table:Supplier
      Sid
                    sname
      S1
                     Anmol
      S2
                     Aradhya
      S3
                     Sunil
       S4
                     Vishal
```

ı Hmnıd	Empname	Salary	Deptid	
Empid E1	Prabhath	12000	D1	
E1 E2	Nikhil	14000	D1	
	Devansh			
E3		10000	D2	
E4	Debraj	15000	D3	
E5	Aron	18000	D1	
MYSTORY Example:if to Trees are the We should p		he count of lin		3
The COUN	TLINES() function of lines starting w		output as:	
The COUN			output as:	
The COUNT The number Write a func		OR CL() IN PYTHO	ON which should	
The COUNT The number Write a func	of lines starting water	OR CL() IN PYTHO	ON which should	
The COUNT The number Write a function of Example:	of lines starting water tion COUNTOWE a text file CHARA	OR CL() IN PYTHO CTER.TXT an	ON which should	
The COUNT The number Write a function of Example: If the file co Exam is going.	of lines starting water tion COUNTOWE a text file CHARA	OR CL() IN PYTHO CTER.TXT an	ON which should along the con	

BOOK

Book_id	Book_name	Price	Qty	Author_id
1001	My first C++	323	12	204
1002	SQL basics	462	6	202
1003	Thunderbolts	248	10	203
1004	The tears	518	3	204

AUTHOR

Author_id	Author_name	Country
201	William Hopkins	Australia
202	Anita	India
203	Anna Roberts	USA
204	Brain Brooke	Italy

- (i) SELECT Author_id, avg(price) from BOOK GROUP BY Author_id;
- ii) SELECT MAX(price),MIN(price) from BOOK;
- ii) SELECT Book_name,Author_name,country from BOOK B, AUTHOR A WHERE B.Author_id = A.Author_id AND price>300;
- iv) SELECT Author_name from AUTHOR WHERE Author_name LIKE "A%";
- 29. Write a function EVEN_LIST(L), where L is the list of elements passed as argument to the function. The function returns another list named 'even list' that stores even numbers in the list.

 For example:

If L contains [1,2,3,4,5,6,7,8]

The even list will have -[2,4,6,8]

30. A list contains following record of a student: [student_name, age, hostel]

Write the following user defined functions to perform given operations on the stack named 'stud details':

- (i) Push_element() To Push an object containing name and age of students who live in hostel "Ganga" to the stack
- (ii) Pop_element() To Pop the objects from the stack and display them. Also, display "Stack Empty" when there are no elements in the stack.

For example:

If the lists of customer details are:

["Barsat",17,"Ganga"]

["Ruben", 16,"Kaveri"]

["Rupesh",19,"Yamuna"]

The stack should contain

["Barsat",17,"Ganga"] The output should be: ["Barsat",17,"Ganga"] Stack Empty OR A list named as Record contains following format of for students: [student_name, class, city]. Write the following user defined functions to perform given operations on the stack named 'Record': (i) Push_record(Record) – To pass the list Record = [['Rahul', 12,'Delhi'], ['Kohli',11,'Mumbai'], ['Rohit',12,'Delhi'] and then Push an object containing Student name, Class and City of student belongs to 'Delhi' to the stack Record and display and return the contents of stack (ii) Pop_record(Record) – To pass following Record [["Rohit","12","Delhi"] ["Rahul", 12,"Delhi"] and then to Pop all the objects from the stack and at last display "Stack Empty" when there is no student record in the stack. Thus the output should be: -["Rohit","12","Delhi"] ["Rahul", 12,"Delhi"] Stack Empty **SECTION D** 31 Hi-tech Training center, a Mumbai based organization is planning to expand their training institute to Chennai. At Chennai compound, they are planning to have three different blocks for admin, training and accounts related activities. As a network consultant you have to suggest some network related solutions to the organization **CHENNAl Office** MUMBAI Admin Accounts Head Office Block Block Training Block Shortest distance between the blocks Number of computers installed are given below: in each block are as follows: Admin → Accounts 300 meters Training 150 Block Accounts 150 meters 30 Accounts →training block

	I	Admin → Training Mumbai → Chennai office	200 meters 1300 KM	Admin Block	20		
	i)	Suggest the most suitab	le block to house	the server at Che	ennai block for	1	
		best and effective conne	ectivity.				
		Suggest the type of netv	work for the new	training institute	and draw		
	ii)	the cable layout for the	Chennai office			1	
		Suggest a hardware/soft	tware that would	provide the data	security for entire	network o	f Chennai
	iii)	region.				1	
		Suggest a device that sh	nall be needed to p	provide wireless	internet access to	all smart	
	iv)	phones/laptop users in (Chennai office.			1	
		Suggest the protocol use	ed for video confe	erencing between	n Chennai	1	
	v)	office and Mumbai office	ce			1	
32.	(a) W	Vrite the output of the	code given below	7:		2+3	
	val=4	dval(m n=10):					
	val=0	dval(m,n=10):					
		al+m*n					
	a=10						
	b=20	1/ 1)					
	findval	al(a,b) al,end="-")					
	findval						
		ral,end="-")					
	Empl Empi Note	he code given below in loyee: id – integer Name – str the following to establ	ring salary-float ish connectivity	ng record in the	table		
	betwo	een Python and MYSQ	-				
		☐ Username is n☐ Password is the					
		☐ The table exis	O	database named	l Empolvee.		
		☐ The details (F	Empid, Name, sa				
	Write	the user. e the following missing	statements to				
		lete the code:	; statements to				
	_	ment 1 – to form the co	ursor object				
		ment 2 – to execute the					
		ts the record in the tab		•			
		ment 3- to add the reco	ora permanently	III			

```
import mysql.connector
from mysql.connector import Error
connection = mysql.connector.connect(host='localhost',
                      database='Employee',
                      user='root',
                      password='tiger')
cursor=
                               __#STATEMENT1
empid=int(input("enter Empid"))
name=input("enter name")
salary=float(input("ENTER SALARY"))
result = _____#STATEMENT2
                            #STATEMENT3
                                   OR
  (a) Predict the output of the code givenbelow:
s="PREboardCS*2022!"
i=2
for i in s.split('*'):
  k = i [:j]
  if k.isupper():
    j=j+1
  elif k.isdigit():
    i=i+2
  else:
    j=j+3
print(s [ j : : j ] )
```

(b) The code given below reads the following record from the table named Employee and displays only those records who have Salary greater than 25000:

Note the following to establish connectivity between Python and MYSQL:

- Username is root
- Password is tiger
- The table exists in a MYSQL database named Employee.

Write the following missing statements to complete the code: Statement 1 - to form the cursor object

Statement 2 – to execute the query that extracts records of those Employees who have salary greater than 25000.

Statement 3- to read the complete result of the query (records whose salary greater than 25000) into the object named records, from the table Employee in the database.

import mysql.connector

	connection — mysel connector connect/heat "legall-act"	
	connection = mysql.connector.connect(host='localhost',	
	database='Employee',	
	user='root',	
	password='tiger')	
	cursor=#STATEMENT1	
	#STATEMENT2	
	records =#STATEMENT3	
	for row in records:	
	print("Empid",row[0],end=" ")	
	print("name",row[1],end=" ")	
	print("salary",row[2],end=" ")	
	print()	
33.	What is a csv file?	5
ارد ا	Write a Program in Python that defines and calls the following user defined]
	functions:	
	Tunctions:	
	■ INSERT() – To accept and add data of a student to a CSV file	
	'student.csv'. Each record consists of a list with field elements as sid,	
	name and marksto store student id, name and marks respectively.	
	♦ COUNTSTUDENTS() – To count the number of records present in	
	the CSV file named 'student.csv'.	
	OR	
	What is the purpose of delimiter?	
	Write a Program in Python that defines and calls the following user defined	
	functions:	
	Tunctions.	
	4 odd) To occur - 1 - 11 1-4 f 1 4 4 6037 61	
	add() – To accept and add data of a product to a CSV file	
	'product.csv'. Each record consists of a list with elements as	
	pid, pnameand priceto storeproduct id, product name and	
	pricerespectively.	
	search()- To display the records of the products whose price is	
	more than 5000.	
	CECTION E	
	SECTION E	
34.	Rahul created following table TRAVEL to store the travel details	1+1+2
		_ t

TNO	TNAME	TDATE	KM	VTYPE	NOP
101	NANDA	25-11-2019	100	VOLVO BUS	32
103	SANAL	09-12-2019	210	ORDINARY BUS	45
105	RAMU	06-12-2019	300	VOLVO BUS	40
102	SOMU	25-12-2019	120	AC DELEX BUS	35
107	NEHA	05-11-2019	250	ORDINARY BUS	25
104	SNEHA	06-11-2019	300	VOLVO BUS	32
106	KIRAN	12-12-2019	125	VOLVO BUS	43

Based on the data given above answer the following questions:

- (i) Identify the most appropriate column, which can be considered as Primary key.
- (ii) If 3 columns are added and 1rows are deleted from the table TRAVEL, what will be the new degree and cardinality of the above table?
- (iii) Write the statements to:

a. Insert the following record into the table

110	BIMAL	28-11-2022	200	VOLVO BUS	40

b. Increase KM travelled by 10 if the VTYPE is VOLVO.

OR (Option for part iii only)

- (iii) Write the statements to:
 - a. Delete the record of travel of traveler NANDA.
 - b. Add a column MILEAGE in the table with data type as integer
- 35. Biplab is a Python programmer. He has written a code and created a binary file STUDENT.DAT which has structure (admission_number, Name, Percentage). He has written an incomplete function *countrec()* in Python that would read contents of the file "STUDENT.DAT" and display the details of those students whose percentage is above 75. Also display number of students scoring above 75%.As a Python expert, help him to complete the following code based on the requirement given above:

import	_#statement1
def countrec():	
	#Statement2
records=	#Statement3
count=0	
for record in recor	ds:
if():#Statement4
count=count+1	

print("ID",record[0])
print("NAME",record[1])
print("PERCENTAGE",record[2])
print("No of students with perentage above 75",count)

(i) Which module should be imported in the program? (Statement1)
(ii) Write the correct statement required to open a file named
STUDENT.DAT in binary mode (Statement2)
(iii) Which statement should Biplab fill in Statement 3 to read the
data from the binary file, STUDENT.DATand in Statement 4 to check the
percentage?

OR
Explain various functions used in writing rows in csv file.

(SET 1)

Computer Science (083)

PRE BOARD EXAMINATION MARKING SCHEME

Maximum Marks:70 Time Allowed: 3 hours

General Instructions:

- 1. This question paper contains five sections, Section A to E.
- 2. All questions are compulsory.
- 3. Section A have 18 questions carrying 01 mark each.
- 4. Section B has 07 Very Short Answer type questions carrying 02 marks each.
- 5. Section C has 05 Short Answer type questions carrying 03 marks each.
- **6.** Section D has 03 Long Answer type questions carrying 05 marks each.
- 7. Section E has 02 questions carrying 04 marks each. One internal choice is given in Q34 against part only.
- **8.** All programming questions are to be answered using Python Language only.

	SECTION	
	A	
1.	State True or False "Dictionaries in python are mutable." Ans:True	1
2.	Which of the following is an invalid identifier a)myname b)p9tv c)def d)_new	1
3.	Ans:c def Which one of the following is the function to get list of keys from a dictionary dict in python? a. dict.getkeys() b. dict.getvalues() c. dict.keys() d. None Of These Ans: c dict.keys()	1
4.	Consider the given expression: True OR NOT False AND True Which of the following will be correct output if the given expression is evaluated? (a) True (b) False (c) NONE (d) NULL Ans: A True	1
5.	Select the correct output of the code: Str="I will Succeed"	1

	lis=str.split("")				
	print(lis[-1])				
	print(iis[1])				
	(2) I				
	(a) I				
	(b) will				
	(c) Succeed				
	(d) "I will Succeed"				
	ANS:c Succeed				
6.	Which of the following me	thods will give	the current position of	of the file	1
0.	pointer?	mods will give	the current position of	of the fife	1
	pointer.				
	(a)seek() (b)tell() (c)getloc()	(d) None of the abo	WA	
	(a)seek() (b)ten() (t	c)genoc()	(u) None of the abo	VC	
	A NS:h tall()				
7	ANS:b tell()				1
7.	Fill in the blank:				1
	1.	1 .1 .		COL	
	command is used t	to change the st	tructure of the table in	n SQL.	
	(a)update	(b)remove	(c)alter	(d)drop	
	ANS: c alter				
8.	Which of the following	commands wi	ll delete the contents of	of the table from	1
	MYSQL database?				
	(a) DELETE				
	(b) DROPTABI	LE			
	(c) REMOVET	ABLE			
	(d) ALTERTA				
	(- /				
	ANS:a DELETE				
9.	Which of the following state	tement(s) woul	d give an error after		1
•	executing the following cod		- 01.0 an onto ano		-
	. 5/100001115 010 10110 991115 000	···			
			# Statement 1		
	T=(8,9,7,6)		# Statement 1		
	T=(8,9,7,6) print(T)		# Statement2		
	T=(8,9,7,6) print(T) T=(7,9,7,6)		# Statement2 # Statement3		
	T=(8,9,7,6) print(T) T=(7,9,7,6) T[1]=8		# Statement2 # Statement3 # Statement4		
	T=(8,9,7,6) print(T) T=(7,9,7,6)		# Statement2 # Statement3		
	T=(8,9,7,6) print(T) T=(7,9,7,6) T[1]=8 T=T+(1,2,3)		# Statement2 # Statement3 # Statement4		
	T=(8,9,7,6) print(T) T=(7,9,7,6) T[1]=8 T=T+(1,2,3) (a) Statement3		# Statement2 # Statement3 # Statement4		
	T=(8,9,7,6) print(T) T=(7,9,7,6) T[1]=8 T=T+(1,2,3) (a) Statement3 (b) Statement4		# Statement2 # Statement3 # Statement4		
	T=(8,9,7,6) print(T) T=(7,9,7,6) T[1]=8 T=T+(1,2,3) (a) Statement3		# Statement2 # Statement3 # Statement4		
	T=(8,9,7,6) print(T) T=(7,9,7,6) T[1]=8 T=T+(1,2,3) (a) Statement3 (b) Statement4		# Statement2 # Statement3 # Statement4		
	T=(8,9,7,6) print(T) T=(7,9,7,6) T[1]=8 T=T+(1,2,3) (a) Statement3 (b) Statement4 (c) Statement5		# Statement2 # Statement3 # Statement4		
	T=(8,9,7,6) print(T) T=(7,9,7,6) T[1]=8 T=T+(1,2,3) (a) Statement3 (b) Statement4 (c) Statement5		# Statement2 # Statement3 # Statement4		

10.	Fill in the blank:	1				
	is an attribute or set of attributes eligible to become primary					
	key.					
	(a) PrimaryKey					
	(b) ForeignKey					
	(c) CandidateKey					
	(d) Alternate Key					
	ANS:c candidate key					
11.	The default mode of opening a file in pyhton	1				
	(a) append					
	(b) read (c) write					
	(c) write (d) both b and c					
	(a) both b and c					
	ANS:b read					
12.	Which of the following can be used as command to get the structure of a table in	1				
	mySQL					
	DEGCDIDE					
	(a) DESCRIBE					
	(b) UNIQUE (c) DISTINCT					
	(d) NULL					
	ANS:a DESCRIBE					
13.	Fill in the blank:	1				
	Is the protocol used for server to server mail transfer?					
	(a)VoIP (b)SMTP (c)PPP (d)HTTP					
	ANS:b SMTP					
	ANS.U SWITE					
14.	What will the following expression be evaluated to in Python?	1				
1 1.	print(2**3**2//8)	1				
	F(/					
	(a)64.0 (b)64 (c)8 (d)None Of These					
	ANS: b 64					
15.	Which clause is used to apply conditions with GROUP BY	1				
13.	(a) WHERE	1				
	(b) HAVING					
	(c) LIKE					
	(d) None Of These					
	ANS:b HAVING					

16.		
	Which function is used to establish connection between python and SQL database?	1
	(a) connection	
	(b) connect	
	(c) getconnection	
	(d) getconnect	
4	ANS:b connect	
_	and 18 are ASSERTION AND REASONING based questions. Mark the correct	
choic		
	Both A and R are true and R is the correct explanation for A	
	b) Both A and R are true and R is not the correct explanation for A	
,	c) A is True but R is False	
_ `	A scartion (A): Eventions in a program in groups the module sity and read chility.	1
17.	Assertion (A):-Functions in a program increases the modularity and readability of the program	1
	Reasoning (R):-Usage of Functions increases the execution speed of the	
	program	
	Program	
	ANS: c A is True but R is False	
18.	Assertion (A): If a file is opened in binary mode its contents are viewed as a	1
	sequence of bytes.	
	Reason (R): A text file also can be opened in binary mode	
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
	ANS: b Both A and R are true and R is not the correct explanation for A	
	ANS: b Both A and R are true and R is not the correct explanation for A SECTION	
19	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made.	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse()	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ")	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10 return rev	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10 return rev ANS:	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10 return rev ANS: def reverse():	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10 return rev ANS: def reverse(): n=int(input("Enter number :: ")	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10 return rev ANS: def reverse(): n=int(input("Enter number :: ") rev=0	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10 return rev ANS: def reverse(): n=int(input("Enter number :: ") rev=0 while(num>0):	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 return rev ANS: def reverse(): n=int(input("Enter number :: ") rev=0 while(num>0): rev=0 while(num>0): r=num%10	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10 return rev ANS: def reverse(): n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 return rev ANS: def reverse(): n=int(input("Enter number :: ") rev=0 while(num>0): rev=0 while(num>0): r=num%10	2
19.	ANS: b Both A and R are true and R is not the correct explanation for A SECTION B Rahul has written a code to input a number and return its reverse. His code is having errors. Rewrite the correct code and underline the corrections made. def reverse() n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10 return rev ANS: def reverse(): n=int(input("Enter number :: ") rev=0 while(num>0): r=num%10 rev=rev*10+r num=num//10	2

20.	What do you mean by protocol? Give two examples	2
	ANS:1 mark for the definition and 1 mark for the example	
	OR	
	What is a MODEM? Explain its use?	
	What is a MODEW! Explain its use:	
	ANS:MODULATOR DEMODULATOR	
	2marks for correct explanation.	
21.	(a) Given is a Python stringdeclaration:	1
	Mystr="I will win"	
	Write the output of: print(Mystr[2:6])	
	ANS:will	1
	(b) Write the output of the code givenbelow:	
	dictcount={"age1":26,"age2":32,"age3":40}	
	sum=0	
	for key in dictcount:	
	sum=sum+dictcount[key]	
	print(sum)	
	ANS:98	
22.	Explain the use of 'Primary Key' in a Relational Database Management	2
	System. Give example to support your answer.	
	1 mark for example and 1 mark for explanation	
23.	(a) Write the full forms of thefollowing:	2
	(i) FTP (ii)TCP	
	(b) What is the use of POP3?	
	ANS:FTP-FILE TRANSFER PROTOCOL ½ MARKS	
	TCP-TRANSMISSION CONTROL PROTOCOL 1/2 MARKS	
	1 MARK FOR THE EXPLANATION OF POP3	
24.	Predict the output of the Python code given below:	2
	def product(L1,L2):	
	p=0	
	for i in L1:	
	for j in L2:	
	p=p+i*j	
	return p LIST=[1,2,3,4,5,6]	
	[1]=[] 1=[]	
	12=[]	
	for i in LIST:	
	if(i%2==0):	
	l1.append(i)	
	else:	
	l2.append(i)	
	print(product(11,12))	

	ANS:108						
			OR				
			OK				
	Predict the output of the Python code given below:						
	tuple1 = (33, 24, 44, 42, 54, 65)						
	list1 =list(tuple1)						
	new_list = [] for i in list1:						
	if i>40:						
	new_list.ap	pend(i)					
	_	uple(new_list)					
	print(new_tup						
	ANS: (44, 42,	54, 65)					
25.	Explain the u	ise of DISTINC	T keyword in	python with appropriate example	2		
		NCT keyword d	_				
	1 mark for ex	xplanation and	1 mark for exa	mple			
			OR				
			OK				
	What is calle	ed DDL comma	nds in mySQL	?Give examples?			
		DEFENITION		,			
	EXAMPLE:	CREATE ,DRC	OP,ALTER				
SEC	TION C						
BEC							
26.	a)Consider tl	. a)Consider the following tables -Product and Supplier: 1-					
	Table:Product						
	-	et		nd Supplier:	1+2		
	Pid	pname	sid	nd Supplier:	1+2		
	Pid P1	pname pen	sid S1	nd Supplier:	1+2		
	Pid P1 P2	pname pen ball	sid S1 S2	nd Supplier:	1+2		
	Pid P1 P2 P3	pname pen ball pencil	sid S1	nd Supplier:	1+2		
	Pid P1 P2	pname pen ball pencil	sid S1 S2	nd Supplier:	1+2		
	Pid P1 P2 P3 Table:Suppli	pname pen ball pencil	sid S1 S2	nd Supplier:	1+2		
	Pid P1 P2 P3 Table:Suppli	pname pen ball pencil er sname	sid S1 S2	nd Supplier:	1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1	pname pen ball pencil er sname Anmol	sid S1 S2	nd Supplier:	1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1 S2	pname pen ball pencil er sname Anmol Aradhya	sid S1 S2	nd Supplier:	1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1 S2 S3 S4	pname pen ball pencil er sname Anmol Aradhya Sunil Vishal	sid S1 S2 S3		1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1 S2 S3 S4 What will be	pname pen ball pencil er sname Anmol Aradhya Sunil Vishal	sid S1 S2 S3 he following st	atement?	1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1 S2 S3 S4 What will be SELECT * F	pname pen ball pencil er sname Anmol Aradhya Sunil Vishal	sid S1 S2 S3 he following st		1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1 S2 S3 S4 What will be SELECT * F	pname pen ball pencil er sname Anmol Aradhya Sunil Vishal the output of the fROM product I	sid S1 S2 S3 ne following st	atement? DIN SUPPLIER;	1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1 S2 S3 S4 What will be SELECT * FANS: Pid	pname pen ball pencil er sname Anmol Aradhya Sunil Vishal the output of the ROM product I	sid S1 S2 S3 he following st NATURAL JC	atement? PIN SUPPLIER; Sname	1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1 S2 S3 S4 What will be SELECT * FANS: Pid P1	pname pen ball pencil er sname Anmol Aradhya Sunil Vishal the output of the ROM product I	sid S1 S2 S3 he following st NATURAL JC sid S1	atement? DIN SUPPLIER; Sname Anmol	1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1 S2 S3 S4 What will be SELECT * FANS: Pid	pname pen ball pencil er sname Anmol Aradhya Sunil Vishal the output of the ROM product I	sid S1 S2 S3 he following st NATURAL JC	atement? PIN SUPPLIER; Sname	1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1 S2 S3 S4 What will be SELECT * FANS: Pid P1 P2	pname pen ball pencil er sname Anmol Aradhya Sunil Vishal the output of the fROM product I pname Pen Ball	sid S1 S2 S3 The following st NATURAL JC sid S1 S2	atement? DIN SUPPLIER; Sname Anmol Aradhya	1+2		
	Pid P1 P2 P3 Table:Suppli Sid S1 S2 S3 S4 What will be SELECT * FANS: Pid P1 P2 P3	pname pen ball pencil er sname Anmol Aradhya Sunil Vishal the output of the ROM product I pname Pen Ball Pencil	sid S1 S2 S3 ne following st NATURAL JC sid S1 S2 S3	atement? DIN SUPPLIER; Sname Anmol Aradhya			
	Pid P1 P2 P3 Table:Suppli Sid S1 S2 S3 S4 What will be SELECT * FANS: Pid P1 P2 P3	pname pen ball pencil er sname Anmol Aradhya Sunil Vishal the output of the ROM product I pname Pen Ball Pencil	sid S1 S2 S3 The following st NATURAL JC sid S1 S2 S3 Pries (i) to (iv)	atement? PIN SUPPLIER; Sname Anmol Aradhya Sunil			

	E1	Prabhath	12000	D1		
	E2	Nikhil	14000	D1		
	E3	Devansh	10000	D2		
	E4	Debraj	15000	D3		
	E5	Aron	18000	D1		
	(ii)SELECT dep HAVING count (iii)SELECT em empname; (iv)SELECT SU BETWEEN 150 ANS:(i) Deptid D1 D2 D3	npname FROM e	(salary) from em	E salary>14000 (ORDER BY	
	1/2 marks (ii)					
	Deptid	count(*)	min(salary)			
	D1	3	12000			
	(iii) Empname Aron Debraj 1/2 marks (iv) Sum(Salary) 33000 1/2 marks					
27.	MYSTORY.TX Example:if the f Trees are the pre We should prote This way we can The COUNTLIN The number of 1 ANS: def COUNTLINE	ect trees n serve nature NES() function sl ines starting with	e count of lines we follows: nould display out a letter T :2	which are starting		3

		1				
	count=0					
	lines=fp.readlines()					
	for line in lines:					
	if(line[0]=="T"):					
	count=count+1					
	print("The number of lines starting with letter T:",count)					
	OR					
	Write a function COUNTOWEL() IN PYTHON which should read each character of a text file CHARACTER.TXT and display the count of vowels					
	Example:					
	If the file content is as follows:					
	Exam is going on well					
	Lam is going on wen					
	The COUNTOWEL() function should display the output as:					
	ANS:					
	def COUNTVOWELS():					
	v v					
	fp=open("CHARACTER.TXT","r")					
	count=0					
	characters=fp.read()					
	characters=characters.lower()					
	for character in characters:					
	if(chatacter in ['a','e','i','o','u']):					
	count=count+1					
	print(count)					
•						
28.	(a) Write the outputs of the SQL queries (i) to (iv) based on the	3				
	relations Teacher and Placement given below:					
	BOOK					
	Book_id Book_name Price Qty Author_id					
	1001 My first C++ 323 12 204					
	1002 SQL basics 462 6 202					
	1003 Thunderbolts 248 10 203					
	1004 The tears 518 3 204					
	AUTHOR					
	Author_id Author_name Country					
	201 William Hopkins Australia					
	202 Anita India					
	203 Anna Roberts USA					
	204 Brain&BrookeItaly					
	207 Diamodiookeitary					
	(') GELECT A (1 '1 (') EDOMBOOK CROVE					
	(i) SELECT Author_id, avg(price) FROMBOOK GROUP					
	BYAuthor_id;	1				

T						
ii) SELECT	Book_name, A		OM BOOK; untryFROM BOOK B, A.Author_idANDprice>300;			
iv) SELECT "A%";						
ANS:						
<u>(i)</u>						
Author_id	Avg(price)					
204	420.5					
202	462					
203	248					
(ii)						
MAX(price)	MIN(pric	e)				
518	248					
(iii)						
Book_name A	Author_nam	Country				
	Brain&Broo ce	Italy				
SQL Basics A	Anita	India				
	Brain&Broo	Italy				
(iv)						
Author_name						
Anita						
Anna Roberts						
	EVEN_LIST	(L), where L is	the list of elements passed	3		
as argument to the			rns another list named 'evenlist'			
	idinocis in th	C 113t.				
For example:						
If L contains [1,2	2,3,4,5,6,7,8]					
The evenlist will	have - [2,4,6	,8]				
ANS:	- 、					
def EVEN_LIST(L):					
evenlist=[] for i in L:						
if(i%2==0):						
evenlist.appen	d(i)	0				

```
return evenlist
30.
     A list contains following record of a student:
                                                                                        3
     [student_name, age, hostel]
     Write the following user defined functions to perform given operations on the
     stack named 'stud details':
                 (i)
                        Push_element() - To Push an object containing name and
                         age of students who live in hostel "Ganga" to the stack
                 Pop_element() - To Pop the objects from the stack and display
         (ii)
                 them. Also, display "Stack Empty" when there are no elements in
                 thestack.
     For example:
     If the lists of customer details are:
     ["Barsat",17,"Ganga"]
     ["Ruben", 16,"Kaveri"]
     ["Rupesh",19,"Yamuna"]
     The stack should contain
     ["Barsat",17,"Ganga"]
     The output should be:
     ["Barsat",17,"Ganga"]
     Stack Empty
    ANS:
    stud_details=[]
    def push_element(lis):
     if(lis[2]=="Ganga"):
       stud_details.append([lis[0],lis[1]])
    def pop element():
     while(len(stud_details)>0):
       print(stud_details.pop())
     print("Stack Empty")
                                        OR
    def Push_record(): # (1½ mark for correct push element)
       for i in List:
         if i[2] == "Delhi":
    Record.append(i)
       print(Record)
    def Pop_record(): # (1½ mark for correct push element)
       while True:
         if len(Record)==0:
            print('Empty Stack')
            break
                                             <del>10</del>
```

	else:			
	<pre>print(Record.pop())</pre>			
Push	(Dict_Product)			
(1 m	ark for correct function header			
1 mai	rk for correct loop			
1∕2 ma	ark for correct If statement			
1∕2 ma	½ mark for correct display of count)			
	SECTION D			
31	HT-1 Taining and Manufaithead an air-di	-		
	HiTech Training center, a Mumbai based organization			
	expand their training institute to Chennai. At Chenn	-		
	they are planning to have three different blocks for a			
	and accounts related activities. As a network consult			
	suggest some network related solutions to the organi	zation		
	CHENNAI Office Admin Accounts MUMBAI			
	Block Block Head Office			
	(Tolision)			
	Training Block			
		computers installed lock are as follows:		
	Admin → Accounts 300 meters Training	150		
	Accounts 150 meters Block Accounts	30		
	→ training block	30		
I	Admin → Training 200 meters Admin Blo Mumbai → 1300 KM	ock 20		
	Chennai office			
i)		1		
	Suggest the most suitable block to house the server a	at Chennai block for 1		
ii)	best and effective connectivity.			
	Suggest the type of network for the new training inst	titute and draw		
iii)	the cable layout for the Chennai office			
	Suggest a hardware/software that would provide the	data security 1		
iv)	for entire network of Chennai region.			
	Suggest a device that shall be needed to provide wire	eless 1		
v)	internet access to all smart phones/laptop users in Ch	nennai office.		
	Suggest the protocol used for video conferencing bet	tween Chennai		
	11			

	office and Mumbai office	
	ANS:	
	i)Training Block	
	ii)LAN	
	iii)FIREWALL	
	iv)ACCESS POINT	
	v)H.323 or SIP	
32.	(a) Write the output of the code given below:	2+3
	val=4	
	def findval(m,n=10): val=0	
	val=0 val=val+m*n	
	a=10	
	b=20	
	findval(a,b)	
	print(val,end="-")	
	findval(a)	
	print(val,end="-")	
	ANS:4-4-	
	(b) The code given below inserts the following record in the table Employee:	
	Empid – integer Name – string salary-float	
	Note the following to establish connectivity	
	between Python and MYSQL:	
	☐ Username is root	
	☐ Password is tiger	
	☐ The table exists in a MYSQL database named Empolyee.	
	☐ The details (Empid, Name, salary) are to be accepted from	
	the user. Write the following missing statements to	
	complete the code:	
	Statement 1 – to form the cursor object	
	Statement 2 – to execute the command that	
	inserts the record in the table Employee.	
	Statement 3- to add the record permanently in	
	the database	
	import mysql.connector	
	from mysql.connector import Error	
	connection = mysql.connector.connect(host='localhost',	
	database='Employee',	
	user='root',	
	password='tiger')	
	cursor=#STATEMENT1 empid=int(input("enter Empid"))	
	empia-mampaa emer empia))	

```
name=input("enter name")
salary=float(input("ENTER SALARY"))
result = _____#STATEMENT2
                                 #STATEMENT3
ANS:
STATEMENT1:connection.cursor()
STATEMENT2:cursor.execute("insert into employee
values(%s,%s,%s)",(empid,name,salary))
STATEMENT3:connection.commit()
                                    OR
  (a) Predict the output of the code givenbelow:
s="PREboardCS*2022!"
i=2
for i in s.split('*'):
  k = i [:i]
  if k.isupper():
    j=j+1
  elif k.isdigit():
    i=i+2
  else:
    j=j+3
  print(s [ j : : j ] )
ANS:
brS0!
  (b) The code given below reads the following record from thetable
      named Employeeand displays only those records who have Salary
      greater than 25000:
 Note the following to establish connectivity between Python and
 MYSOL:
           • Username isroot
           • Password istiger
              The table exists in a MYSQL database namedEmployee.
 Write the following missing statements to complete the code: Statement 1 - to
 form the cursor object
 Statement 2 – to execute the query that extracts records of those
 Employees who have salary greater than 25000.
 Statement 3- to read the complete result of the guery (records whose
 salary greater than 25000) into the object named records, from the table
 Employeein the database.
import mysql.connector
connection = mysql.connector.connect(host='localhost',
                       database='Employee',
                       user='root',
                       password='tiger')
```

#STATEMENT2

#STATEMENT1

cursor=

```
#STATEMENT3
    records =
    for row in records:
       print("Empid",row[0],end=" ")
       print("name",row[1],end=" ")
       print("salary",row[2],end=" ")
    print()
     ANS:
     Statement 1 :connection.cursor()
    Statement 2 :cursor.execute("select * from employee where salary>25000")
     Statement 3:cursor.fetchall()
3\overline{3}.
      What is a csv file?
                                                                                       5
      Write a Program in Python that defines and calls the following user defined
      functions:
           INSERT() – To accept and add data of a student to a CSV file
             'student.csv'. Each record consists of a list with field elements as sid,
             name and marksto store student id, name and marks respectively.
            COUNTSTUDENTS() – To count the number of records present in
             theCSV file named'student.csv'.
         ANS:
    import csv
    def INSERT():
      studlist=[]
      while(choice=="y"):
       sid=int(input("Enter Student id"))
       name=input("Enter name")
       marks=input("Enter Marks")
       choice=input("Enter y to continue or press any to exit")
       student=[sid,name,marks]
       studlist.append(student)
      file=open("student.csv","w")
      writer=csv.writer(file)
      writer.writerows(studlist)
     def COUNTSTUDENTS():
      file=open("student.csv","r")
      reader=csv.reader(file)
      print("No of students",len(reader))
                                    OR
      What is the purpose of delimiter?
      Write a Program in Python that defines and calls the following user defined
      functions:
                    add() – To accept and add data of a product to a CSV file
                    'product.csv'. Each record consists of a list with elements as
                    pid, pnameand priceto storeproduct id, product name and
                    pricerespectively.
                    search()- To display the records of the products whose price is
                    more than 5000.
```

```
ANS:
    import csv
    def add():
     prodist=[]
     while(choice=="y"):
      pid=int(input("Enter product id"))
      pname=input("Enter name")
      price=input("Enter price")
      choice=input("Enter y to continue or press any to exit")
      product=[pid,pname,price]
      prodlist.append(product)
     file=open("product.csv","w")
     writer=csv.writer(file)
     writer.writerows(prodlist)
     def search():
     file=open("product.csv","r")
     reader=csv.reader(file)
     for record in reader:
      if(record[2]>5000):
        print("Product id",record[0])
        print("Product name",record[1])
        print("Product price",record[2])
    1 mark for correct explanation of question
    ½ marks for correctly opening the file
    ½ marks for creating reader and writer objects
    Full marks for correct code
                              SECTION E
34. Rahul created following table TRAVEL to store the travel details
                                                                                   1+1+2
       TNO
                  TNAME
                            TDATE
                                              KM
                                                   VTYPE
                                                                      NOP
       101
                  NANDA
                            25-11-2019
                                              100
                                                   VOLVO BUS
                                                                      32
       103
                  SANAL
                            09-12-2019
                                              210
                                                   ORDINARY BUS
                                                                      45
       105
                                              300
                                                   VOLVO BUS
                                                                      40
                  RAMU
                            06-12-2019
                  SOMU
       102
                            25-12-2019
                                              120
                                                   AC DELEX BUS
                                                                      35
       107
                  NEHA
                            05-11-2019
                                              250
                                                   ORDINARY BUS
                                                                      25
                  SNEHA
       104
                            06-11-2019
                                              300
                                                   VOLVO BUS
                                                                       32
       106
                  KIRAN
                            12-12-2019
                                              125
                                                   VOLVO BUS
                                                                       43
     Based on the data given above answer the following questions:
      (i)
            Identify the most appropriate column, which can be considered as
            Primary key.
```

If 3 columns are added and 1rows are deleted from the table TRAVEL,

(ii)

what will be the new degree and cardinality of the above table? (iii) Write the statements to: (a) Insert the following record into the table 28-11-2022 VOLVO BUS 110 **BIMAL** 20 40 0 (b) Increase KM travelled by 10 if the VTYPE is VOLVO. ANS: a)(i)TNO (ii)degree-9 cardinality-6 iii)a.INSERT INTO TRAVEL VALUES(110,'BIMAL','28-11-2022',200,'VOLVOBUS',40) b.UPDATE TRAVEL SET KM=KM+10 WHERE VTYPE='VOLVO BUS' OR (Option for part iii only) (iii) Write the statements to: a. Delete the record of travel of traveler NANDA. **b.** Add a column MILEAGE in the table with data type as integer ANS: a)DELETE FROM TRAVEL WHERE TNAME='NANDA' b)ALTER TABLE TRAVEL ADD(MILEAGE int) 35. Biplab is a Python programmer. He has written a code and created a binary file STUDENT.DAT which has structure (admission_number, Name, Percentage). He has written an incomplete function *countrec()* in Python that would read contents of the file "STUDENT.DAT" and display the details of those students whose percentage is above 75. Also display number of students scoring above 75%. As a Python expert, help him to complete the following code based on the requirement given above: import __ #statement1 def countrec(): #Statement2 records= ____#Statement3 count=0 for record in records:):#Statement4 count=count+1 print("ID",record[0]) print("NAME",record[1]) print("PERCENTAGE",record[2]) print("No of students with perentage above 75",count) Which module should be imported in the program? (Statement1) (i) Write the correct statement required to open a file named (ii) STUDENT.DAT. in binary mode (Statement2)

(iii) Which statement should Biplab fill in S data from the binary file, STUDENT.DAT percentage?	
ANS (i) pickle (ii)fp=open("STUDENT.DAT","rb")	2
(iii)records=pickle.load(fp) if(record[2]>75)	

12COM03QP

KENDRIYA VIDYALAYA SANGATHAN , CHENNAI REGION PRE-BOARD-I EXAMINATION 2023-2024

CLASS XII-COMPUTER SCIENCE (083)

TIME: 03 HOURS M.M.: 70

General Instructions:

- 1. This question paper contains five sections, Section A to E.
- 2. All questions are compulsory.
- 3. Section A has 18 questions carrying 01mark each.
- 4. Section B has 07 Very Short Answer type questions carrying 02 marks each.
- 5. Section C has 05 Short Answer type questions carrying 03 marks each.
- 6. Section D has 02 Long Answer type questions carrying 04 marks each.
- 7. Section E has 03 questions carrying 05 marks each.

8. All programming questions are to be answered using Python Language only.

	SECTION A	
1.	Assign a tuple containing an Integer?	(1)
2.	Which of the following data type in Python supports concatenation? a) int b) float c) bool d) str	(1)
3.	What will be output of the following code: d1={1:2,3:4,5:6} d2=d1.popitem() print(d2) a){1:2} b){5:6} c)(1,2) d)(5,6)	(1)
4.	The correct output of the given expression is: True and not False or False (a)False (b)True(c)None (d) Null	(1)
5.	Fill in the blank: Command is used to add a new column in a table in SQL. a)update b)remove c)alter d)drop	(1)
6.	Consider the Python statement: f.seek(10, 1) Choose the correct statement from the following: (a) File pointer will move 10 byte in forward direction from beginning of the file (b) File pointer will move 10 byte in forwarddirection from end of the file (c) File pointer will move 10 byte inforwarddirection from current location (d) File pointer will move 10 byte in backward direction from current location	(1)
7.	Choose correct SQL query which is expected to delete all rows of a table emp without deleting its structure. a) DELETE TABLE; b) DROP TABLE emp; c) REMOVE TABL emp; d) DELETE FROM emp;	(1)
8.	Which of the following is NOT a DML Command? (a)Insert (b)Update (c)Drop (d)Delete	(1)

9. Select the correct outpu to the	e code:	(1)
a="Year2022atallthe b	pest"	
a=a.split('a') b=a[0]+"-"+a[1]+"-"+a	a[3]	
print (b)		
a) Year–0-atAllthebest		
b) Ye-r2022-llthe best		
c) Year–022-at Allthebest		
d) Year–0-atallthebest		
10. Which of the following staten	nent(s) would give an error during execution?	
S="Lucknow is the Capital of		
print(S)	#Statement2	
S[4]='\$'	#Statement3	
S="Thankyou"	#Statement4	
S=S+"Thankyou"	#Statement5	
S-S Thankyou	"Statements	
(a)Statement3 (b)Statement4	(c)Statement5 (d)Statement4and5	
11 Which of the following functi	ion returns a list datatyne?	(1)
11.	f.read(10) c) d=f.readline() d)d=f.readlines()	(1)
12. Select the correct statement,w	vith reference to SOL:	(1)
a) Aggregate functions ig		(1)
	onsider NULL as zero or False	
c) Aggregate functions tre d) NULL can be written a	eat NULL as a blank string	
P:11: 41 11 1	is NOLL also.	
13. Fill in the blank:	col used to retrieve mail from a remote server to a local	(1)
email client.		
XX71 ('11.1 (1 1 C	e)POP3 (d)HTTP	
14. What will be the value of y v Python?	when following expression be evaluated in	(1)
x=10.0		
y=(x<100.0) and $x>=10$	(1)77	
(a)110 (b)False (c)Error	(d)Trueignore null values in their input collection.	(1)
15. All aggregate functions except _ (a) Count(attribute)		(1)
(b) Count(*)		
(c) Avg (d) Sum		
	od is used to create a connection between the MySQL	(1)
database and Python?		(1)
a) (a) connector () (b)) connect () (c) con () (d)cont()	

	Q 17 and 18 are ASSERTION AND REASONING based questions. Mark the correct choice as	
	 a) Both A and R are true and R is the correct explanation for A b) Both A and R are true and R is not the correct explanation for c) A is True but R is False d) A is false but R is True 	
17.	Assertion (A):-The default arguments can be skipped in the function call. Reason (R):-The function argument will take the default values even if the values are supplied in the function call	(1)
18.	Assertion(A):A tuple can be concatenated to a list, but a list cannot be concatenated to a tuple. Reason(R):Lists are mutable and tuples are immutable in Python.	(1)
	SECTION B	
19.	Ravi has written a function to print Fibonacci series for first 10 element. His code is having errors. Rewrite the correct code and underline the corrections made. Some initial elements of Fibonacci series are:	(2)
	def fibonacci() first=0 second=1 print(("first no. is ", first) print("secondno.is,second) for a in range (1,9): third=first+second print(third) first,second=second,third fibonacci()	
20.	What possible outputs (s) are expected to be displayed on screen at the time of execution of the program from the following code? Also specify the maximum values that can be assigned to each of the variables FROM and TO. import random AR=[20,30,40,50,60,70] FROM=random.randint(1,3) TO=random.randint(2,4) for K in range(FROM,TO+1): print(AR[K],end="#") (i)10#40#70# (ii)30#40#50# (iii)50#60#70# (iv)40#50#70#	(2)
21.	(a) Given is a Python string declaration: myexam="RussiaUkrain" Write the output of: print(myexam[-2:2:-2])	(1)
	(b) Write the output of the code given below: D1={"sname":"Aman","age":26} D1['age']=27 D1['address']="Delhi" print(D1.items())	(1)

```
Explain the use of 'Foreign Key' in a Relational Database. Give an example to support your (2)
22.
      answer.
      (a) Write the full forms of the following:
23.
                                                                                                  (1)
          (i) POP
                                                                (ii)HTTPS
                                                                                                  (1)
      (b) Write two points of difference between Circuit Switching and Packet Switching
    Predict the output of the Python code given below:
24.
                                                                                                  (2)
     value = 50
     def display(N):
          global value
           value = 25
           if N%7==0:
             value=value+N
          else:
             value=value-N
     print(value, end="#")
     display(20)
     print(value)
                                     OR
     def Display(str):
       m=""
       for i in range(0,len(str)):
         if(str[i].isupper()):
            m=m+str[i].lower()
         elif str[i].islower():
            m=m+str[i].upper()
         else:
            if i\% 2 == 0:
              m=m+str[i-1]
            else:
              m=m+"#"
     print(m)
     Display('Fun@World2.0')
```

- 25. Consider the following two commands with reference to a table, named Students, having a column named Section:
 - (a) Select count(Section) from Students;
 - (b) Select count(*)from Students;

If these two commands are producing different results,

- (i) What may be the possible reason?
- (ii) Which command,(a)or(b),might be giving higher value?

Name the aggregate functions which work only with numeric data, and those that work with any type of data.

SECTION C

(a)Consider the following tables— EMPLOYEES AND DEPARTMENT 26.

(1)

(2)

TABLE : EMPLOYEES

ENO	ENAME	DOJ	DNO
E1	NUSRAT	2001-11-21	D3
E2	KABIR	2005-10-25	D1

TABLE : DEPARTMENT

DNO	DNAME
D1	ACCOUNTS
D2	HR
D3	ADMIN

What will be the output of the following statement?

SELECT ENAME, DNAME FROM EMPLOYEES, DEPARTMENT WHERE EMPLOYEE.DNO=DEPARTMENT.DNO;

(2)

b)Write the output of the queries(i)to(iv) based on the tables given below

Table: ITEM

ID	Item Name	Manufacturer	Price
PC01	Personal Computer	ABC	35000
LC05	Laptop	ABC	55000
PC03	Personal Computer	XYZ	32000
PC06	Personal Computer	COMP	37000
LC03	Laptop	PQR	57000

Table: CUSTOMER

	1 abi	C. COCIONILIC	
C_ID	CName	City	ID
01	N Roy	Delhi	LC03
06	R Singh	Mumbai	PC03
12	R Pandey	Delhi	PC06
15	C Sharma	Delhi	LC03
16	K Agarwal	Bangalore	PC01

- i) SELECT ITEM_NAME, MAX(PRICE), COUNT(*) FROM ITEM GROUP BY ITEM_NAME;
- ii) SELECT CNAME, MANUFACTURER FROM ITEM, CUSTOMER WHERE ITEM.ID=CUSTOMER.ID;
- iii) SELECT ITEM_NAME, PRICE*100 FROM ITEM WHERE MANUFACTURER="ABC";
- (iv) SELECT DISTINCT CITY FROM CUSTOMER;

27. Write a method SHOWLINES() in Python to readlines from text file 'TESTFILE.TXT' and display the lines which do not contain 'ke'. Example: If the file content is as follows: An apple a day keeps the doctor away. We all pray for everyone's safety. A marked difference will come in our country. The SHOWLINES() function should display the output as: We all pray for everyone's safety. (3) OR Write a function in python to count the number of lines in a text file 'Country.txt' which are starting with an alphabet 'W' or 'H'. For example, If the file contents are as follows: Whose woods these are I think I know. His house is in the village though; He will not see me stopping here To watch his woods fill up with snow. The output of the function should be: W or w:1 H or h:2 Consider the following tables GAMES. Give outputs for SQL queries (i)to(iv). 28. (2+1) **Table: GAMES** GameName PrizeMoney ScheduleDate GCode Number 23-Jan-2004 101 CaromBoard 5000 2 102 Badminton 12000 12-Dec-2003 103 **TableTennis** 4 8000 14-Feb-2004 105 Chess 2 9000 01-Jan-2004 108 4 25000 LawnTennis 19-Mar-2004 (i) SELECT COUNT(DISTINCT Number) FROM GAMES: SELECT MAX(ScheduleDate), MIN(ScheduleDate) FROM (ii)**GAMES:** (iii) SELECT SUM(PrizeMoney) FROM GAMES; SELECT * FROM GAMES WHERE PrizeMoney>12000; (iv) (b) Write the command to view all the databases in an RDBMS. (3) 29. Write a function in PythonConvert() to replaces elements having even values with its half and elements having odd values with twice its value in a list. eg: if the list contains 3,4,5,16,9 then rearrange the list as 6,2,10,8,18 Write a function in Python PUSH_IN(L), where L is a list of numbers. From this (3) 30. list, push all numbers which are multiple of 3 into a stack which is implemented by using another list. OR Write a function in Python, Push(KItem), where KItem is a dictionary containing the details of Kitchen items— {Item:price}. The function should push the names of those items in a stack which have price less than 100. Also display the average price of elements pushed into the stack.

For example: If the dictionary contains the following data: {"Spoons":116,"Knife":50,"Plates":180,"Glass":60} The stack should contain Glass Knife The output should be: The average price of an item is 55.0 **SECTION D** Tushar is a Python programmer. He has written a code and created a binary file 31. record.dat with employeeid, ename and salary. The file contains 10 records. He now has to delete a record based on the employee id entered by the user. For this purpose, he creates a temporary file, named temp.dat, to store all the records other than the record to be deleted. If the employee id is not found, an appropriate message should to be displayed. As a Python expert, help him to complete the following code (by completing statements 1, 2, 3, and 4) based on the requirement given above: Complete Statement #1 to import the required module. (i) Write the correct statement required to open a temporary file named (ii) temp.dat. (#Statement 2) Which statement should Aman fill in Statement 3 to read the data (iii) from the binary file, record.dat (iv) What should be written in Statement4 to write there records in the file temp.dat? #Statement1 import def update_data(): rec={ } fin=open("record.dat","rb") fout=open(" ","") #Statement2 found=False eid=int(input("Enter employee id:")) while True: try: #Statement3 if rec["Employee id"]==eid: found=Tru e else: #Statement 4 except: break if found==True: print("Recorddeleted.") else: print("Employee with such id is notfound") fin.close() fout.close()

A departmental store MyStore is considering to maintain their inventory using 32.

SQL to store the data. As a database Administrator, Abhay has decided that:

4

Name of the database–mystore

Name of the table -STORE

The attributes of STORE are as follows

ItemNo -numeric

ItemName-character of size 20

Scode – numeric

Quantity-numeric

Table: STORE

ItemNo	ItemName	Scode	Quantity
2005	SharpnerClassic	23	60
2003	BallPen0.25	22	50
2002	GelPenPremium	21`	150
2006	GelPenClassic	21	250
2001	EraserSmall	22	110
2004	EraserBig	22	220
2009	BallPen0.5	21	180

- (a) Identify the attributes suitable to be declared as primary key
- (b) Write the query to add the row with following details (2010,"Notebook",23,155)

(c)


- Abhay wants to remove the table STORE from the database MyStore, Help i) Abhay in writingthe command for removing the table STORE from the database MyStore.
- ii) Now Abhay wants to display the structure of the table STOREi.e.name of the attributes and their respective data types that he has used in the table. Write the query to display the same.

- (i) Abhay wants to ADD a new column price with data type as decimal. Write the query to add the column..
- (ii) Now Abhay wants to remove a column price from the table STORE. Write the query.

SECTION E

A company ABC Enterprises has four blocks of buildings as shown:

33.



34	(a) Define the term Primary Key with respect to RDBMS. Give one example to support your answer	(1)
	(b) The code given below reads records from the table named student and displays only those records who have marks greater than 75. The structure of a record of table Student is: RollNo-integer; Name -string; Clas -integer; Marks- integer	(4)
	Note the following to establish connectivity between Python and MYSQL: (i) Username is root (ii) Password is abc (iii) The table exists in a MYSQL database named school. (iv) The details(RollNo,Name,Class and Marks) are to be accepted from the user. Write the following missing statements to complete the code: Statement 1 – to create the cursor object Statement 2 – to execute the query that extracts records of those students whose marks are greater than 75. Statement3-to read the complete result of the query(records whose marks are greater than 75) into the object named data, from the table student in the database. import mysql.connector as mysql def sql_data(): con1=mysql.connect(host="localhost",user="root",	
35.	 (i) Write one similarity and one difference between a+ and w+ (ii) A binary file "emp.dat" has structure (EID, Ename, designation, salary) Write a function Show() in Python that would read the details of employees from the file "emp.dat" and display the details of those employees whose designation is "Manager" (OR) (i) What is the difference between readline() and readlines()? (ii) A binary file "Book.dat" has structure [BookNo, Book_Name, Author, Price]. Write a function CountRec(Author) in Python which accepts the Author name as parameter and count and return number of books written by the given Author 	(2+3)

General Isnstructions:

This question paper is divided into 3 Sections - A, B and C.

- (i) Section A, consists of 7 questions (1-7). Each question carries 2 marks.
- (iii) Section B, consists of 3 questions (8-10). Each question carries
- 3 marks. (iv) Section C, consists of 3 questions (11-13). Each question carries
- 4 marks.
- Internal choices have been given for question numbers 7, 8 and 12.

SECTION - A

(Each question carries 2 marks)

"Stack is a linear data structure which follows a particular order in which ·1. the operations are performed."

2

What is the order in which the operations are performed in a Stack?

Name the List method/function available in Python which is used to remove the last element from a list implemented stack.

Also write an example using Python statements for removing the last element of the list.

****2. (i) Expand the following:

1

VoIP, PPP

Riya wants to transfer pictures from her mobile phone to her laptop. She uses Bluetooth technology to connect two devices. Which type of network (PAN/LAN/MAN/WAN) will be formed in this case?





3. Differentiate between the terms Attribute and Domain in the context of Relational Data Model.

2

*4. Consider the following SQL table MEMBER in a SQL Database CLUB:

2

Table : MEMBER

		the state of the s
M_ID	NAME	ACTIVITY
M1001	Amina	GYM
м1002	Pratik	GYM
M1003	Simon	SWIMMING
M1004	Rakesh	GYM
M1005	Avneet	SWIMMING

Assume that the required library for establishing the connection between Python and MYSQL is already imported in the given Python code. Also assume that DB is the name of the database connection for table MEMBER stored in the database CLUB.

Predict the output of the following code:

MYCUR = DB.cursor()

MYCUR.execute ("USE CLUB")

MYCUR.execute ("SELECT * FROM MEMBER WHERE ACTIVITY= 'GYM' ")

R=MYCUR.fetchone()

for i in range (2):

R=MYCUR.fetchone()

print (R[0], R[1], sep = "#")

 $\mathbf{2}$

Write the output of SQL queries (a) to (d) based on the table VACCINATION_DATA given below:

TABLE : VACCINATION_DATA

			Dose1	_	
	Name	Age	DOSEL	Dose2	City
VID	Jenny	27	2021-12-25	2022-01-31	Delhi
101	Harjot	55	2021-07-14	2021-10-14	Mumbai
102	Srikanth	43	2021-04-18	2021-07-20	Delhi
103	Gazala	75	2021-07-31	NULL	Kolkata
104	Shiksha	32	2022-01-01	NULL	Mumbai
105	011-				

- . (a) SELECT Name, Age FROM VACCINATION_DATA Dose2 IS NOT NULL AND Age > 40; WHERE
- · (b) SELECT City, COUNT(*) FROM VACCINATION_DATA GROUP BY City;
- .(c) SELECT DISTINCT City FROM VACCINATION_DATA;
- (d) SELECT MAX (Dosel), MIN (Dose2) FROM VACCINATION_DATA;
- Write the output of SQL queries (a) and (b) based on the following two -6. tables DOCTOR and PATIENT belonging to the same database:

Table : DOCTOR

DNO	DNAME	FEES
D1 .	AMITABH	1500
D2	ANIKET	1000
D3	NIKHIL	1500
D4	ANJANA	1500

Table : PATIENT

PNO	PNAME	ADMDATE	DNO
P1	NOOR	2021-12-25	D1
P2	ANNIE	2021-11-20	D2
Р3	PRAKASH	2020-12-10	NULL
P4	HARMEET	2019-12-20	.D1

- (a) SELECT DNAME, PNAME FROM DOCTOR NATURAL JOIN PATIENT;
- .(b) SELECT PNAME, ADMDATE, FEES
 FROM PATIENT P, DOCTOR D
 WHERE D.DNO = P.DNO AND FEES > 1000;
- 77. Differentiate between Candidate Key and Primary Key in the context of Relational Database Model.

OR

Consider the following table PLAYER:

Table : PLAYER

PNO	NAME	SCORE
P1	RISHABH	52
P2	HUSSAIN	45
Р3	ARNOLD	23
P4	ARNAV	18
P5	GURSHARAN	42

 $\mathbf{2}$

Identify and write the name of the most appropriate column from the Identity and Ident (b) Define the term Degree in relational data model. What is the Degree

of the given table PLAYER?

SECTION - B

(Each question carries 3 marks)

- Write the definition of a user defined function Pushnv (N) which · 8. accepts a list of strings in the parameter N and pushes all strings which have no vowels present in it, into a list named NoVowel.
 - Write a program in Python to input 5 words and push them one by one into a list named All.

3

The program should then use the function PushNV() to create a stack of words in the list NoVowel so that it stores only those words which do not have any vowel present in it, from the list All. Thereafter, pop each word from the list NoVowel and display the popped word. When the stack is empty display the message "EmptyStack".

For example:

If the Words accepted and pushed into the list All are

['DRY', 'LIKE', 'RHYTHM', 'WORK',

91

Page 6



Then the stack Novowel should store

['DRY', 'RHYTHM', 'GYM']

And the output should be displayed as

GYM RHYTHM DRY EmptyStack

OR

- Write the definition of a user defined function Push3_5(N) which accepts a list of integers in a parameter N and pushes all those integers which are divisible by 3 or divisible by 5 from the list N into a list named Only3_5.
- Write a program in Python to input 5 integers into a list named **NUM**.

 The program should then use the function **Push 3_5()** to create the stack of the list **Only3_5**. Thereafter **pop** each integer from the list **Only3_5** and display the popped value. When the list is empty, display the message "StackEmpty".

For example:

If the integers input into the list NUM are:

[10, 6, 14, 18, 30]

Then the stack Only3_5 should store

[10, 6, 18, 30]

And the output should be displayed as

30 18 6 10 StackEmpty



- 9. (i) A SQL table ITEMS contains the following columns:

3

- INO, INAME, QUANTITY, PRICE, DISCOUNT
 Write the SQL command to remove the column DISCOUNT from the table.
- (ii) Categorize the following SQL commands into **DDL** and **DML**: CREATE, UPDATE, INSERT, DROP
- 10. Rohan is learning to work upon Relational Database Management System (RDBMS) application. Help him to perform following tasks:
 - (a) To open the database named "LIBRARY".
 - (b) To display the names of all the tables stored in the opened database.
 - (c) To display the structure of the table "BOOKS" existing in the already opened database "LIBRARY".

SECTION - C

(Each question carries 4 marks)

11. Write SQL queries for (a) to (d) based on the tables PASSENGER and FLIGHT given below:

Table : PASSENGER

PNO	NAME	GENDER	FNO
1001	Suresh	MALE	F101
1002	Anita	FEMALE	F104
1003	Harjas	MALE	F102
1004	Nita	FEMALE	F103



Table : FLIGHT

		. LTICE	II.	
FNO	START	END	F DATE	FARE
F101	MUMBAI	CHENNAI	2021-12-25	4500
F102	MUMBAI	BENGALURU	2021-11-20	4000
F103	DELHI	CHENNAI	2021-12-10	5500
F104	KOLKATA	MUMBAI	2021-12-20	
F105	DELHI	BENGALURU		4500
,		DINGALORO	2021-01-15	5000

- (a) Write a query to change the fare to 6000 of the flight whose FNO is F104.
- (b) Write a query to display the total number of MALE and FEMALE PASSENGERS.
- of all PASSENGERS who have a flight to START from DELHI.
- (d) Write a query to delete the records of flights which end at Mumbai.
- 12. (i) Differentiate between Bus Topology and Tree Topology. Also, write one advantage of each of them.

OR

Differentiate between HTML and XML.

(ii) What is a web browser? Write the names of any two commonly used web browsers.


2

Galaxy Provider Ltd. is planning to connect its office in Texas, USA with its branch at Mumbai. The Mumbai branch has 3 Offices in three blocks located at some distance from each other for different operations – ADMIN, SALES and ACCOUNTS.

As a network consultant, you have to suggest the best network related solutions for the issues/problems raised in (a) to (d), keeping in mind the distances between various locations and other given parameters.

4

Layout of the Offices in the Mumbai branch:



Shortest distances between various locations:

DIIOI COU dibudii	
ADMIN Block to SALES Block	300 m
SALES Block to ACCOUNTS Block	175 m
	350 m
ADMIN Block to ACCOUNTS Block	14000 km
MUMBAI Branch to TEXAS Head Office	

Number of Computers installed at various locations are as follows:

ADMIN Block	255
ACCOUNTS Block	75
SALES Block	30
TEXAS Head Office	90

- (a) It is observed that there is a huge data loss during the process of data transfer from one block to another. Suggest the most appropriate networking device out of the following, which needs to be placed along the path of the wire connecting one block office with another to refresh the signal and forward it ahead.
 - (i) MODEM

(ii) ETHERNET CARD

(iii) REPEATER

- (iv) HUB
- (b) Which hardware networking device out of the following, will you suggest to connect all the computers within each block?
 - (i) SWITCH

(ii) MODEM

(iii) REPEATER

- (iv) ROUTER
- (c) Which service/protocol out of the following will be most helpful to conduct live interactions of employees from Mumbai Branch and their counterparts in Texas?
 - (i) FTP

(ii) PPP

(iii) SMTP

- (iv) VolP
- (d) Draw the cable layout (block to block) to efficiently connect the three offices of the Mumbai branch.

 \mathbf{SET}

Series EHEFG

प्रश्न-पत्र कोड Q.P. Code

रोल नं.

Roll No.


Candidates must write the Q.P. Code on the title page of the answer-book.

COMPUTER SCIENCE

Time allowed: 3 hours

Maximum Marks: 70

- Please check that this question paper contains 15 printed pages.
- Q.P. Code given on the right hand side of the question paper should be written on the title page of the answer-book by the candidate.
- Please check that this question paper contains 35 questions.
- Please write down the serial number of the question in the answerbook before attempting it.
- 15 minute time has been allotted to read this question paper. The question paper will be distributed at 10.15 a.m. From 10.15 a.m. to 10.30 a.m., the candidates will read the question paper only and will not write any answer on the answer-book during this period.



P.T.O.

	, ,			
Ger	neral Instructions:		• * * * * * * * * * * * * * * * * * * *	
	(i) This question paper contains fit (ii) All questions are compulsors		. G . A to F	
	(ii) All questions are compulsory.	ve se	ections, Section A to E.	
	(III) Section A have 19 and its			
	(iii) Section A have 18 questions ca (iv) Section B has 7 Very Short	rryii	ng 1 mark each. wer type questions carrying 2 m	arbe
	each.	Ansu	wer type questions carrying 2 m	lurks
	(b) Section Chas 5 Ct			
	(vi) Section D has 3 Long Answer to (vii) Section E has 2 questions come	type	questions carrying 3 marks each.	•
	(vii) Section E has 2 and i	ype o	questions carrying 5 marks each.	.1
	(vii) Section E has 2 questions carry given in Q. 34 and 35 against	ying	f 4 marks each. One internal choi	ice is
	given in Q. 34 and 35, against (viii) All programming	Part	t (iii) only.	
	(viii)All programming questions are only.	to b	be answered using Python Langu	uage
	,.			
1.	State True or False.	ON -	$-\mathbf{A}$	
	"Identifiers one			1
	"Identifiers are names used to identi	fyav	variable, function in a program".	
2.	The second secon			
	Which of the following is a valid keys (a) false	vord	l in Python?	1
		(b)	return	
	(c) non_local	(d)	none	
3.	Given the following Tuple			
υ.	Tup= (10, 20, 30, 50)			1
		11		
	Which of the following statements wi (a) print (Tup[0])			
		(b)	. 1 323 (2/3)	и
	(c) print(Tup[1:2])	(d)	<pre>print(len(Tup))</pre>	
	a widen the given even			
4.	Consider the given expression: 5<10 and 12>7 or not 7>4			
	Which of the following will be the			
	Which of the following will be the corevaluated?	rect	output, if the given expression is	
	(a) True		- 12 2 10 10 10 10 10 10 10 10 10 10 10 10 10	1
		(b)	False	- 1.
	(c) NONE	(d)	NULL	
	Select the correct output of the code:			
5.	Select the correct output of the code: S= "Amrit Mahotsav @ 75"			1
	A=S.partition (" ")			
	print. (a)			
	(a) ('Amrit Mahotsav','@','75			
	(b) [,'Amrit','Mahotsav','@',''5	')		
	(c) ('Amrit', 'Mahotsav @ 75')	/5 ']	le principal de la companya de la co	
	(d) ('Amrit', '', 'Mahotsay a)		
	(d) ('Amrit', '', 'Mahotsav @	75 '	')	7



. V	Whicl ile ?	n of the	following mo	de keeps th	e file	offset	positio	n at the	end of the	44
		r+		The Carlot of the	(h)	r				1
		W			(b)	_				
,	(0)	W			(d)	a			- 1	
,	म्याः	n the bla	nle							1
•	I 111 1.		n is used to a	rranga tha	alama	nts of	a list i	n ascend	ling order	1
	(a)	sort()	ii is useu to a	Trange the	(b)	arrar		ii ascend	ing order.	
	(c)	ascend	ling()		(d)	asort	-	100		
*	(0)	ascend	iriig ()		, (u)	asort	- ()			
8.	Whi	ch of the	following ope	arators will	retur	n eithe	r True	or False	2 2	1
.	(a)	·+=	tollowing op	erators will	(b)	!=	.i iiuc	or raise	•	•
	(c)	_		· · · · · ·	(d)	• *=				
1	(c)	_		, Near to	(α)	1		14 14	**	
9.	Whi	ich of th	e following s	tatamant(a)	woul	d miyo	on or	ror ofter	ovogiting	
9.		following	_	tatement(s)	woul	u give	an en	or arter	executing	1
	unc		g code: {"Murugan":	100. "Mit	thu":	95'} =	# Stat	tement	1	-
			(Stud[95])					ement	2	
		_	["Murugan"]		4		# Stat	tement	3	
		print	(Stud.pop())			# Stat	ement	4	
		print	(Stud)			9	# Stat	ement	5	
	(a)	Staten	nent 2		(b)	State	ment 3			
	(c)	Staten	nent 4		(d)	State	ments	2 and 4		
10.	Fil	l in the b	lank.							1
		is a n	umber of tupl	es in a relat	tion.	7 4				
	(a)	Attri	bute	1	(b)	Degr	ee	100	17	
	(c)	Domai	.n	- %	(d)	Card	inalit	ty	2	
	7.						110		. 51	
11.		_	x of seek (- 8	,				• *	1
			ect.seek(of							
	Wł	nat is the	e default valu	e of refere		oint	?			
	(a)	0			(b)	1		**** Y		•
	(c)	2 .	1, -		(d)	3				
•								¥	5	_
12	. Fil	ll in the l		ar cei eog	r etate	ment f	to diani	o. d	:	1
	<u>r</u>	cla	use is used w	ocified colu	mn.	inent (o aispi	ay data	ın a sorted	
			respect to a sp	Jecinea cora	(b)	ORDE	R BY			,
	(a)				(d)		INCT			
	(c)	HAVI	NG	_			11101			
91	s -		100	<	3				Р.Т	.O.

13.	Fill	in the blank:	muni	cation or unicast communication
	such	as radar and satellite.		A. A. C.
	(a)	INFRARED WAVES	(b)	BLUETOOTH
	(c)	MICROWAVES	(d)	RADIOWAVES
14.	Wha	at will the following expression b print (4+3*5/3-5%2)	e eval	uated to in Python?
	(a)	8.5	(b)	8.0
1	(c)	10.2	(d)	10.0
15.	Wh	ich function returns the sum of a	ll elen	nents of a list?
	(a)	count ()	(b)	sum()
	(c)	total()	(d)	add()
16.	feto	chall() method fetches all rows in	a resu	lt set and returns a :
	(a)	Tuple of lists	(b)	List of tuples
	(c)	List of strings	(d)	Tuple of strings
			R) is tl	
		(A).		e la
	(c) (d)	(A) is true but (R) is false.(A) is false but (R) is true.	, ·'	
17.	` ,	sertion (A): To use a function import the module.	from a	
	Re	ason (R): import statement can before using a function from the		
18.	As	sertion (A) : A stack is a LIFO st	ructui	'e. 1
		eason (R): Any new element positioned at the index after the	pushe	ed into the stack always gets

SECTION - B

```
19. Atharva is a Python programmer working on a program to find and return
    the maximum value from the list. The code written below has syntactical
                                                                                2
    errors. Rewrite the correct code and underline the corrections made.
         def max num (L) :
              \max=L(0)
               for a in L:
                 if a > max
                 max=a
               return max
                                                                                2
          Differentiate between wired and wireless transmission.
 20/ (a)
          Differentiate between URL and domain name with the help of an
     (b)
                                                                                2
          appropriate example.
                                                                                 1
          Given is a Python list declaration:
          Listofnames=["Aman", "Ankit", "Ashish", "Rajan", "Rajat"]
           Write the output of:
          write the output of:

print (Listofnames \begin{bmatrix} -1:-4:-1 \end{bmatrix})
                                                                                 1
           Consider the following tuple declaration:
           tup1=(10,20,30,(10,20,30),40)
           Write the output of:
           print(tupl,index(20))
       Explain the concept of "Alternate Key" in a Relational Database
       Management System with an appropriate example.
                                                                                 2
                                                                                 2
           Write the full forms of the following:
                HTML
            (i)
                TCP
            (ii)
            What is the need of Protocols?
            Write the output of the code given below:
                                                                                 2
       (a)
            def short sub (lst,n):
                for i in range (0,n):
                       if len (1st)>4:
                          lst [i]=lst [i]+lst[i]
                      else:
                           lst[i]=lst[i]
            subject=['CS','HINDI','PHYSICS','CHEMISTRY','MATHS']
            short sub(subject,5)
            print(subject)
                             \mathbf{OR}
   91
```

P.T.O.

(b) Write the output of the code given below:

$$a = 30$$

def call (x):

global a

if a%2 == 0:

x+=a

else:

x-=a

return x

x=20

print(call(35),end="#")

print(call(40),end= "@")

25. (a) Differentiate between CHAR and VARCHAR data types in SQL with appropriate example.

OR

(b) Name any two DDL and any two DML commands.

2

 $\mathbf{2}$

SECTION - C

26. (a) Consider the following tables - LOAN and BORROWER:

1 + 2

Table: LOAN

LOAN_NO	B_NAME	AMOUNT
L-170	DELHI	3000
L-230	KANPUR	4000

Table: BORROWER

CUST_NAME	LOAN_NO
JOHN	L-171
KRISH	L-230
RAVYA	L-170

How many rows and columns will be there in the natural join of these two tables?



(b) Write the output of the queries (i) to (iv) based on the table, WORKER given below:

TABLE: WORKER

TABLE:	WORKER			THE A COLO
W_{ID}	F NAME	L_NAME	CITY	STATE
102	SAHIL	KHAN	KANPUR	UTTAR PRADESH
104	CAMPED	PARIKH	ROOP NAGAR	PUNJAB
104	SAMEER			DELHI
105	MARY	JONES ·	DELHI	
	MAHIR	SHARMA	SONIPAT	HARYANA
106	MAHIK			DELHI
107	ATHARVA	BHARDWAJ	DELHI	
108	VEDA	SHARMA	KANPUR	UTTAR PRADESH
1				The second secon

- (i) SELECT F_NAME, CITY FROM WORKER ORDER BY STATE DESC;
- (ii) SELECT DISTINCT (CITY) FROM WORKER;
- (iii) SELECT F_NAME, STATE FROM WORKER WHERE L_NAME LIKE '_HA%';
- (iv) SELECT CITY, COUNT (*) FROM WORKER GROUP BY CITY;
- 27. (a) Write the definition of a Python function named LongLines () which reads the contents of a text file named 'LINES.TXT' and displays those lines from the file which have at least 10 words in it. For example, if the content of 'LINES.TXT' is as follows:

Once upon a time, there was a woodcutter

He lived in a little house in a beautiful, green wood.

One day, he was merrily chopping some wood.

He saw a little girl skipping through the woods, whistling happily.

The girl was followed by a big gray wolf.

Then the function should display output as:

He lived in a little house in a beautiful, green wood.

He saw a little girl skipping through the woods, whistling happily.

OR

(b) Write a function count_Dwords() in Python to count the words ending with a digit in a text file "Details.txt".

Example:

If the file content is as follows:

On seat2 VIP1 will sit and

On seat1 VVIP2 will be sitting

Output will be:

Number of words ending with a digit are 4

Write the outputs of the SQL queries (i) to (iv) based on the relations 28. (a) COMPUTER and SALES given below:

Table: COMPUTER

Table:	COMPUTER	1.82	COMPANY	TYPE
PROD_ID	PROD_NAME	PRICE		INPUT
P001	MOUSE	-200 Jali	LOGITECH	
P002	LASER PRINTER	4000	CANON	OUTPUT
P003	KEYBOARD	500	LOGITECH	INPUT
P004	JOYSTICK	1000	IBALL	INPUT
P005	SPEAKER	1200	CREATIVE	OUTPUT
	DESKJET PRINTER	4300	CANON	OUTPUT
P006	DESKSET FRINTER	4000	CANOIN	001101

Table: SALES

PROD_ID	QTY_SOLD	QUARTER
P002	4	1
P003	2	2
P001	3	2
P004	2	1
The second secon		

- (i) SELECT MIN(PRICE), MAX(PRICE) FROM COMPUTER;
- (ii) SELECT COMPANY, COUNT(*) FROM COMPUTER GROUP BY COMPANY HAVING COUNT (COMPANY) > 1;
- (iii) SELECT PROD_NAME, QTY_SOLD FROM COMPUTER C, SALES S WHERE C.PROD_ID=S.PROD_ID AND TYPE = 'INPUT';
- (iv) SELECT PROD NAME, COMPANY, QUARTER FROM COMPUTER C, SALES S WHERE C.PROD ID=S. PROD_ID;
- Write the command to view all databases.



29. Write a function EOReplace() in Python, which accepts a list L of numbers. Thereafter, it increments all even numbers by 1 and decrements all odd numbers by 1.

3

Example:

If Sample Input data of the list is:

L=[10,20,30,40,35,55]

Output will be:

L=[11,21,31,41,34,54]

30/(a) A list contains following record of customer:

[Customer_name, Room Type]

Write the following user defined functions to perform given operations on the stack named 'Hotel':

- (i) Push_Cust() To Push customers' names of those customers who are staying in 'Delux' Room Type.
- (ii) Pop_Cust() To Pop the names of customers from the stack and display them. Also, display "Underflow" when there are no customers in the stack.

For example:

If the lists with customer details are as follows:

["Siddarth", "Delux"]

["Rahul", "Standard"]

["Jerry", "Delux"]

The stack should contain

Jerry

Siddharth

The output should be:

Jerry

Siddharth ...

Underflow

OR

(b) Write a function in Python, Push (Vehicle) where, Vehicle is a dictionary containing details of vehicles — {Car_Name: Maker}.

The function should push the name of car manufactured by 'TATA' (including all the possible cases like Tata, TaTa, etc.) to the stack.

For example:

If the dictionary contains the following data:

Vehicle={"Santro":"Hyundai", "Nexon": "TATA", "Safari": "Tata"}

The stack should contain

Safari

Nexon



P.T.O.

3





SECTION - D

31. Quickdev, an IT based firm, located in Delhi is planning to set up a network for its four branches within a city with its Marketing department in Kanpur. As a network professional, give solutions to the questions (i) to in Kanpur through the branches locations and other details which are given below:

DELHI BRANCH

BRANCH A

BRANCH B

BRANCH C

BRANCH D

KANPUR BRANCH

MARKETING DEPT.

Distance between various branches is as follows:

Branch	Distance
Branch A to Branch B	40 m
Branch A to Branch C	80 m
Branch A to Branch D	65 m
Branch B to Branch C	30 m
Branch B to Branch D	35 m
Branch C to Branch D	15 m
Delhi Branch to Kanpur	300 km

Number of computers in each of the branches:

Branch	Number of Computers
Branch A	15
Branch B	25
Branch C	40
Branch D	115

(i) Suggest the most suitable place to install the server for the Delhi branch with a suitable reason.

- (ii) Suggest an ideal layout for connecting all these branches within Delhi.
- 1
- (iii) Which device will you suggest, that should be placed in each of these branches to efficiently connect all the computers within these branches?

(iv) Delhi firm is planning to connect to its Marketing department in Kanpur which is approximately 300 km away. Which type of network out of LAN, WAN or MAN will be formed? Justify your answer.

1

(v) Suggest a protocol that shall be needed to provide help for transferring of files between Delhi and Kanpur branch.

1

(a) What possible output(s) are expected to be displayed on screen at the time of execution of the following program:

import random

M=[5,10,15,20,25,30]

for i in range (1,3):

first=random.randint(2,5)-1

sec=random.randint(3,6)-2

third=random.randint(1,4)

print(M[first], M[sec], M[third], sep="#").

(i) 10#25#15

(ii) 5#25#20

20#25#25

25#20#15

(iii) 30#20#20

(iv) 10#15#25#

20#25#25

15#20#10#

(b) The code given below deletes the record from the table employee which contains the following record structure:

E_code - String

E_name - String

Sal - Integer

City - String

Note the following to establish connectivity between Python and MySQL:

- Username is root
- Password is root
- The table exists in a MySQL database named emp.
- The details (E_code, E_name, Sal, City) are the attributes of the table.

```
Statement 1 - to import the desired library.
    Statement 2 - to execute the command that deletes the record with
                E code as 'E101'.
    Statement 3 - to delete the record permanently from the database.
   import
                    as mysql # Statement 1
   def delete():
       mydb=mysql.connect(host="localhost", user="root",
       passwd="root", database="emp")
        mycursor=mydb.cursor()
                           # Statement 2
                           # Statement 3
        print ("Record deleted")
                           OR
(a) Predict the output of the code given below:
    def makenew(mystr):
        newstr=""
         count=0
         for i in mystr:
             if count%2!=0:
                  newstr=newstr+str(count)
             else:
                    if i.lower():
                      newstr=newstr+i.upper()
                    else:
                      newstr=newstr+i
              count+=1
          print(newstr)
    makenew("No@1")
```

Write the following statements to complete the code:

(b) The code given below reads the following records from the table employee and displays only those records who have employees coming from city 'Delhi':

E_code - String
E_name - String
Sal - Integer
City - String

Note the following to establish connectivity between Python and MySQL:

- Username is root
- Password is root
- The table exists in a MySQL database named emp.
- The details (E_code, E_name, Sal, City) are the attributes of the table.

Write the following statements to complete the code:

Statement 1 - to import the desired library.

Statement 2 – to execute the query that fetches records of the employees coming from city 'Delhi'.

Statement 3 - to read the complete data of the query (rows whose city is Delhi) into the object named details, from the table employee in the database.

13

- Write one difference between CSV and text files. Write a program in Python that defines and calls the following user defined functions:
 - COURIER ADD(): It takes the values from the user and adds the details to a csv file 'courier.csv'. Each record consists of a list with field elements as cid, s_name, Source, destination to store Courier ID, Sender name, Source and destination address respectively.
 - (ii) COURIER_SEARCH(): Takes the destination as the input and displays all the courier records going to that destination.

- Why it is important to close a file before exiting? Write a program in Python that defines and calls the following user
 - Add_Book(): Takes the details of the books and adds them to a csv file 'Book.csv'. Each record consists of a list with field elements as book_ID, B_name and pub to store book ID, book name and publisher respectively.
 - Search_Book(): Takes publisher name as input and counts and displays number of books published by them.

SECTION - E

The school has asked their estate manager Mr. Rahul to maintain the data of all the labs in a table LAB. Rahul has created a table and entered

	TADMO			a calla	$^{ m 010}$ and $^{ m en}$
	LABNO	LAB_NAME	TYTOTAL		
	L001	CILDAGO	INCHARGE	CADAGE	
	Tool	TOTALIDI KA	Daisy	CAPACITY	FILOOD
ŕ	1002	BIOLOGY		20	THOOK
1	L003	MATTER	Venky		1 1
1	Too	MATH	D	20	TT
1	L004	LANGUAGE	Preeti	15	11
1	L005	MINGUAGE	Daisy		ī
	2000	COMPITED	Daisy	36	-
a	sed on the de	COMPUTER ata given above	Mary Kom		Π
\	T.J	ata given above	J 220111	37	F

Based on the data given above answer the following questions:

Identify the columns which can be considered as Candidate keys. Write the degree and cardinality of the table.

(iii) Write the statements to

Insert a new row with appropriate data. (b)

Increase the capacity of all the labs by 10 students which are on

- (Option for part (iii) only) (iii) Write the statements to:

 - Add a constraint PRIMARY KEY to the column LABNO in the table. (b)



1

1 $\mathbf{2}$ 35. Shreyas is a programmer, who has recently been given a task to write a user defined function named write_bin() to create a binary file called Cust_file.dat containing customer information — customer number (c_no), name (c_name), quantity (qty), price (price) and amount (amt) of each customer.

The function accepts customer number, name, quantity and price. Thereafter, it displays the message 'Quantity less than 10..... Cannot SAVE', if quantity entered is less than 10. Otherwise the function calculates amount as price * quantity and then writes the record in the form of a list into the binary file.

```
import pickle
def write bin():
                 #Statement 1
 bin file=
while True:
                   1 1 1 1 1
 c no=int(input("enter customer number"))
   c name=input("enter customer name")
   qty=int(input("enter qty"))
   price=int(input("enter price"))
             #Statement 2
      print("Quantity less than 10..Cannot SAVE")
    else:
      amt=price * qty
      c_detail=[c_no,c name,qty,price,amt]
           #Statement 3
      ans=input("Do you wish to enter more records y/n")
      if ans.lower() == 'n':
            #Statement 4
                 #Statement 5
                #Statement 6
```

(i) Write the correct statement to open a file 'Cust_file.dat' for writing the data of the customer.

(ii) Which statement should Shreyas fill in Statement 2 to check whether quantity is less than 10.

(iii) Which statement should Shreyas fill in Statement 3 to write data to the binary file and in Statement 4 to stop further processing if the user does not wish to enter more records.

OK

(Option for part (iii) only)

(iii) What should Shreyas fill in Statement 5 to close the binary file named Cust_file.dat and in Statement 6 to call a function to write data in binary file?




1

1

2

Segies HFG	IT COCC V	(1)- Computer Science (+4) Camlin	23/3/23
riment Name / No:	Code-91 (Set	(1) - Camlin	Page No.
takey Syl		Date	1
Partes), WIH	SECTION-A	1 M × 18 Rs :	= 18M
1. Tone	7. A	13. C	
2. B	8. B	14. B	
3. B	9. D	15. B	
4. A	10. D	16. B	
5. D	11. A	17· A	Ŷ.
6. D	12. B	18. A	
	SECTION-B.	2m x7as=	14-M
A19) def m	ax-num(L):		
/	max = L[0]	# Essa	: 1
	fos a in L:		
THE RESERVE TO A STREET	if a > max &	# Exacs	_2
	max = a		
9	setuen max	wed the state	
	The Mark at Markey.		
ADD) @ Differ	ence wired & with xample: LAN -	reless transmission	14
E	xample: LAN -	> wifi	IM
ne			
(b) http://	www. cbse.mc.iu	, welcome, liter,	IM
Exam		Injelm Resource Le	reaties)
chie.	aic. in -> Dom	ain Name	
Differe	ince in words		IM
		Teacher's Signature:	



DDL: Greate, Alter, Drop IM DDL: Scleet, Insert, update, Delete IM SECTION-C Salx x 3M = 15M SECTION-C Salx x 3M = 15M ADE) @ Rows: 2 Columns: 4 IM (b) is F-NAME CITY is DISTINGT (CITY) SHHIL KANDUR KANDUR VEDA KANDUR ROOP NAGAR SAMCER ROPNAGAR DELHS MAHIR SONIPAT SONIPAT MARY DELHS ATHARVA DELHS SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROOPNAGAR L ATHARVA DELHS DELHS SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROOPNAGAR L ATHARVA DELHS DELHS VEDA UTTAR PRADEM SONIPAT 1
DDL: Greate, Altes, Drop DML: Selcet, Onsert, Updale, Delete IM SECTION-C SA/s x 3M = 15M SECTION-C SA/s x 3M = 15M A 26) @ Rows: 2 Columns: 4 IM (b) i) F-NAME CITY ii) DISTINCT (CITY) SIAHIL ICANDUR KANDUR VEDA KANDUR ROOP NAGAR SAMEER ROOP NAGAR DELHI MAHIR SONIPAT SONIPAT MARY DELHI ATHARVA DELHI SAHIL UTTAR PRADEM KANDUR MAHIR HARYANA ROOPNAGAR I ATHARVA DELHI DELHI ATHARVA DELHI DELHI ATHARVA DELHI DELHI ATHARVA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
DML: Select, 9nsext, update, Delete IM SECTION-C 58/6 x 3M = 15M A 26) @ ROWS: 2 Columns: 4 IM (b) if F-NOME CITY ii) DISTINCT (CITY) SHILL KANDUR KANDUR VEDA KANDUR ROOD NAGAR SAMEER ROOP NAGAR DELHS MAHIR SONIPAT SONIPAT MARY DELHS ATHARYA DELHS SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGAR I ATHARYA DELHS ATHARYA DELHS ATHARYA DELHS ONAHIR HARYANA ROODNAGAR I ATHARYA DELHS OEHS VEDA UTTAR PRADEM SONIPAT 1
SECTION-C 59/s x 3M = 15 M A 26) (a) Rows: 2 Columns: 4 IM (b) is F-NOME CITY ii) DISTINCT (CITY) SIGNIL ICANDUR KANDUR VEDA KANDUR ROOP NAGAR SAMEER ROOP NAGAR DELHI MAHIR SONIPAT SONIPAT MARY DELHI ATHARYA DELHI SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROOPNAGAR L ATHARYA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
A 26) @ RONE: 2 CORUMNS: 4 IM (B) if F-NOME CITY ii) DISTINCT (CITY) SIGNIL KANDUR KANDUR VEDA KANDUR ROOD NAGOR SAMEER ROOPNAGOR DELHI MAHIR SONIPAT SONIPAT MARY DELHI ATHARVA DELHI SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGOR I ATHARVA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT I
B is F-NAME CITY is DISTING (CITY) SHHIL KANDUR KANDUR VEDA KANDUR ROOP NAGAR SAMEER ROOP NAGAR DELHI MAHIR SONIPAT SONIPAT MARY DELHI ATHARVA DELHI SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGAR L ATHARVA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
B is F-NAME CITY is DISTING (CITY) SHHIL KANDUR KANDUR VEDA KANDUR ROOP NAGAR SAMEER ROOP NAGAR DELHI MAHIR SONIPAT SONIPAT MARY DELHI ATHARVA DELHI SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGAR L ATHARVA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
B i) F-NOME CITY ii) DISTINGT (CITY) SHHIL KANDUR KANDUR VEDA KANDUR ROOP NAGAR SAMEER ROOPNAGAR DELHI MAHIR SONIPAT SONIPAT MARY DELHI ATHARVA DELHI SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGAR L ATHARVA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
SMHIL KANDUR KANDUR VEDA KANDUR ROOF NAGAR SAMEER ROOPNAGAR DELHI MAHIR SONIPAT SONIPAT MARY DELHI ATHARYA DELHI SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROOPNAGAR L ATHARYA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
SMHIL KANDUR KANDUR VEDA KANDUR ROOF NAGAR SAMEER ROOPNAGAR DELHI MAHIR SONIPAT SONIPAT MARY DELHI ATHARYA DELHI SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROOPNAGAR L ATHARYA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
SAMEER ROPNAGE DELIE MAHIR SONIPAT SONIPAT MARY DELHE ATHARYA DELHE LI) F-NAME STATE IV) CITY COUNT(*) SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGAR L ATHARYA DELHE DELHE 2 VEDA UTTAR PRADEM SONIPAT 1
MAHIR SONIPAT SONIPAT MARY DELHI ATHARVA DELHI II) F_NAME STATE IV) CITY COUNT(*) SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGAR L ATHARVA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
MARY DELHI ATHARYA BELHI LL) F_NAME STATE IV) CITY COUNT(*) SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGAR L ATHARYA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
ATHARVA BELHI LIJ F_NAME STATE IV) CITY COUNT(*) SAHIL UTTAR PRADUM KANDUR 2 MAHIR HARYANA ROODNAGAR L ATHARVA DELHI DELHI 2 VEDA UTTAR PRADUM SONIPAT 1
ii) F-NAME STATE IV) CITY COUNT(*) SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGAR L ATHARYA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGAR L ATHARYA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
SAHIL UTTAR PRADEM KANDUR 2 MAHIR HARYANA ROODNAGAR L ATHARYA DELHI DELHI 2 VEDA UTTAR PRADEM SONIPAT 1
ATHARVA DELHI DELHI 2. VEDA UTTAR PRADEM SONIPAT 1
VEDA UTTAR PRADERY SONIPAT 1
1/m×4
1/m×4
12
Teacher's Signature:

```
ADT) @ def Longhines () :
             J= open ('LINES. TXT')
             date = f. Readline()
             while dates
                  w = data, split()
                  y len(w) > 103
                      paint (date)
                  date = f. Readlines)
             f, dose()
   b def count_Dwoeds():
                                              3M
              f = open ('Details, txt')
              date = f. Read()
              date = date. split()
              for w in data:
                   y w[-1]. iedigit:
                       ctr = ctr + 1
              f. close()
               print ('Number of woods ending
                    ust a digit are, ctr)
```


iment Name / No.: Camlin Page No. 428) of 1/2 M × 4 MIN (PRICE) MAX (PRICE) 200 4300 COMPANY COUNT(*) LOGITECH 2 CANON 2 iii) PROD_NAME QTY_SOLD MOUSE KEYBOARD JOYSTICK 2 11) PROD_NAME COMDANY QUARTER MOUSE LOGI TECH 2 1 LASER PRINTER CANON 2 KEYBOARD LOGITECH JOYSTICK 1 BALL (b) SHOW DATABASES; IM Teacher's Signature


```
3M
3M
```

def EOReplace (L): for i in large (leu(L)); N= L[i] y N% 2 = = 0: L(1) +=1 L(i) -= 1 # main-code Lot = [10, 20, 30, 40, 35, 55] prient ('OUTPUT') ED Replace (LSt) pant (det) def Puch-Cust (L): for date in Li

if date [1] = = 'Delux': Hotel. append (date [0]) def Pop- Cest(): y len (Hotel) = =0
peint ('Undeflow')

Use: part (Holel. pop()) # mash-code L = [['Soddarsh', 'Deluxi'], ['Rohul', 'Standard'], ['Jany', 'Deluxi'] Motel = [] Pust-Cest (L) Pop-Ceist (Hotal)





nent Name / No.:	amlin Page No.
Date	
A33) @ CSV: Commo Seperated value, only	date IM
Text ple: Contain all readely charact	
Used to story all kind of	
	12 2 2 2 A A A A A A A A A A A A A A A A
import CSV as c	1/2 M
dy courier-ADD();	
flenare = 'consier.csv'	1½M
cid = "uput ('Enter Courier ID')	
S-name = input ('Enter Sender Name	e')
Source = "uput ('Exter Source ')	
destination = input (Enter Destination))
L=[cid, s-nae, Source, destination	
with open (flener, 'w') as csuple	:
csvweste = c. wester (csvfole)	
CSVWerte. Western (L)	
def Couritor_Staron():	1½M
dest = "uput (Enter destination to Sec	mh')
with open ('Curier. (8v') as confile!	
cov-read = c. reader (carple, del	lineter = ',')
for date in csv-seed:	
If dato [3] = = dest:	
priv (deta)	
# main-codo	
COURIER_ADD()	2 1/2 M
COURIER_SEARCH())
Teacher's Signature:	

OR Part	<u> </u>
B) It is impostant to close a file before to that date may be preserved & other application can use that file. Otherw file will not be accepted to other	exity = ize that a apple.
Add-Book() & Search_Book() as psevior	e facetor
SECTION-E 20k + 4h	M = 8M
$A34$) i) CK: LABNO, LAB_NAME ii) D=5 C=5	IM
$D = 5 \qquad C = 5$	2m×2
iii) @ insert ent LAB values (1606', 'CS LAR', 'Himanshu', 50	
B update LAB Set capacity = capacity + 10 where fi	IM
OR	•
add Perimacy key (LABNO)	IM
6 delete from LAR;	14 6

eriment Name / N	No.:	Camlin Page No.	
A2-		Date	\exists
A35		12.1 -11.2	_
	i) bein-file = open ('custfile. dat	$(2, '\omega b')$	1/
i	i) gty < 10:	S ₂	IN
ù	ie) break	ail bûs-file) Isz	10
	break	ailg bûs-file) Sz	y 1N
	OR Pach		
3	So > bin-file. close(_
	So > write_ben()	IM	-
			
		a contract of the contract of	
20			
		Touchor's Signatures	
		Teacher's Signature:	

CBSE Additional Practice Question Paper Class: XII Session: 2023-24 Computer Science (083)

Time allowed: 3 Hours Maximum Marks: 70

General Instructions:

- Please check this question paper contains 35 questions.
- The paper is divided into 5 Sections- A, B, C, D and E.
- Section A, consists of 18 questions (1 to 18). Each question carries 1 Mark.
- Section B, consists of 7 questions (19 to 25). Each question carries 2 Marks.
- Section C, consists of 5 questions (26 to 30). Each question carries 3 Marks.
- Section D, consists of 2 questions (31 to 32). Each question carries 4 Marks.
- Section E, consists of 3 questions (33 to 35). Each question carries 5 Marks.
- All programming questions are to be answered using Python Language only.

Q No.	Questions Section-A (18 Marks)	Marks
1	Which of the following is an invalid identifier to be used in Python? a. per%marks bfor c. While d. true	1
2	What is the correct way to add an element to the end of a list in Python? a. list.add(element) b. list.append(element) c. list.insert(element) d. list.extend(element)	1
3	What will be the output of print("Welcome To My Blog"[2:6] + "Welcome To My Blog"[5:9]) a. Lcomme b. lcomme T c. lcomme To d. lcomme	1
4	 Which of the following statements is false? a. A try-except block can have more than one except statement b. One block of except statement cannot handle multiple exceptions c. The finally block is always executed d. When 1 == "1" is executed, no exception is raised 	1
5	Which of the following statement(s) would give an error during the execution of the following code? R = {'pno':52,'pname':'Virat', 'expert':['Badminton','Tennis'],'score':(77,44)} print(R) #Statement 1	1

	R['expert'][0]='Cricket' #Statement 2 R['score'][0]=50 #Statement 3 R['pno']=50 #Statement 4	
	 a. Statement 1 b. Statement 2 c. Statement 3 d. Statement 4 	
6	Which pickle module method is used to write a Python object to a binary file?	1
	a. save()b. serialize()c. store()d. dump()	
7	Given the following dictionaries dict_student = {"rno" : "53", "name" : 'Rajveer Singh'} dict_marks = {"Accts" : 87, "English" : 65} Which statement will append the contents of dict marks in	1
	Which statement will append the contents of dict_marks in dict_student? a. dict_student + dict_marks b. dict_student.add(dict_marks) c. dict_student.merge(dict_marks) d. dict_student.update(dict_marks)	
8	Which of the following is not a component of the math module in Python? a. ceil() b. mean()	1
	c. fabs() d. pi	
9	What will be the output of the following code? L=["One , Two", "Three", "Four"] print(len(L)/2*len(L[0]))	1
	a. 6.5 b. 13 c. 13.5 d. 6.0	
10	Expand the following terms: (i) PPP (ii) VoIP	1
11	Which SQL operator performs pattern matching?	1
	 a. BETWEEN operator b. LIKE operator c. EXISTS operator d. = 	

12	Which Python function is used for displaying only one result set from SQL table in a database?	1
	 a. fetch1() b. fetchno() c. fetchall() d. fetchone() 	
13	Which of the following file opening mode in Python, generates an error if the file does not exist?	1
	 a. a b. r c. w d. w+ 	
14	The correct syntax of seek() is: a. file_object.seek(offset [, reference_point]) b. seek(offset [, reference_point]) c. seek(offset, file_object) d. seek.file_object(offset)	1
15	Which of the following statements is false?	1
	 a. SMTP and POP protocols are used in email communication. b. URL of a page is not always the same as its domain name. c. HTTPS is safer than HTTP. d. Interlinking of collection of webpages is called Internet. 	
16	Fill in the blank: protocol provides access to services hosted on a remote computer.	1
	a. FTPb. PPPc. Telnetd. SMTP	
	Q17 and 18 are ASSERTION AND REASONING based questions. Mark the correct choice as (a) Both A and R are true and R is the correct explanation for A (b) Both A and R are true and R is not the correct explanation for A (c) A is True but R is False (d) A is false but R is True	
17	Assertion (A): For changes made to a variable defined within a function to be visible outside the function, it should be declared as global. Reasoning (R): Variables defined within a function are local to that function by default, unless explicitly specified with the global keyword.	1
18	Assertion (A): A binary file in python is used to store collection objects like lists and dictionaries that can be later retrieved in their original form using pickle module.	1

	Reasoning (A): Binary files are just like normal text files and can be read using a text editor like Notepad.						
Q No.	Questions Section-B (14 Marks)	Marks					
19	Write two advantages and two disadvantages of circuit switching. OR Differentiate between Web server and web browser. Write the names of any two web browsers.	2					
20	Rewrite the following code in Python after removing all the syntax errors. Underline each correction done in the code. num1, num2 = 10, 45 While num1 % num2 == 0 num1+= 20 num2+= 30 Else: print('hello')	2					
21	Write a function dispBook(BOOKS) in Python, that takes a dictionary BOOKS as an argument and displays the names in uppercase of those books whose name starts with a consonant. For example, Consider the following dictionary BOOKS = {1:"Python", 2:"Internet Fundamentals ", 3:"Networking ", 4:"Oracle sets", 5:"Understanding HTML"} The output should be: PYTHON NETWORKING OR Write a Python Program containing a function FindWord(STRING, SEARCH), that accepts two arguments: STRING and SEARCH, and prints the count of occurrence of SEARCH in STRING. Write appropriate statements to call the function. For example, if STRING = "Learning history helps to know about history with interest in history" and SEARCH = 'history', the function should display The word history occurs 3 times.	2					
22	<pre>What will be the output of the following code? L = [5,10,15,1] G = 4 def Change(X): global G N=len(X) for i in range(N): X[i] += G</pre> Change(L) for i in L: print(i,end='\$')	2					

23	Write a suitable Python statement for each of the following tasks using built-in functions/methods only: i To delete an element Mumbai:50 from Dictionary D. ii To display words in a string S in the form of a list OR Write a Python Program to display alternate characters of a string my_str.									
	For ex	ample, if		str="Comp c Cmue cec	outer	Science	"			
24	used w	ith the L	etwee	operator in S n DROP and	QL w O R	ith appi	copriate exa	e) characters amples. In SQL with	2	
25	named (a) Sei (b) Sei If these (i) Wh	Employ lect co lect co e two con nat may b	vee habunt (bunt (bun	ing two conving a colur Departmen (*) from Ends are produced possible rea (a) or (b) m	nn na it) i Emplo cing son?	med De From En Dyee; differen	partmenmployee; tresults,		2	
Q No				•	stion				Marks	
				Section-C	(15	Warks)			
26	TABLE F	: BOOK CODE 101 102 101 102	BNAM The pr Easy f Jumar	riest Python n Ji I Story	nd ME	TYF Fict	PE ion gramming iller ion	7:	3	
	Table	: MEMBE		MNAME	С	ODE I	SSUEDATE			
	M101 SNEH SINHA L102 2022-10-13 M103 SARTHAK F102 2021-02-23 M102 SARA KHAN C101 2022-06-12									
	What will be the output of the following statement? SELECT * FROM BOOK NATURAL JOIN MEMBER; (b) Write the output of the queries (i) to (iv) based on the table Table: Employee									
	EID	Name		DOB	DO	J	Salary	Project		
	E01	Ranjan	1	1990-07-12	201	5-01-21	150000	P01		
	E02	Akhtar		1992-06-21		5-02-01	125000	P04		
	E03	Munee	ra	1996-11-15	201	8-08-19	135000	P01	[
				1001 10 05	204	0 40 40	75000	DOO		
	E04 E05	Alex Satyan		1991-10-25 1993-12-16		8-10-19 8-10-19	75000 85000	P02 P04		

- i SELECT NAME, PROJECT FROM EMPLOYEE ORDER BY NAME DESC;
- ii SELECT NAME, SALARY FROM EMPLOYEE WHERE NAME LIKE 'A%';
- iii SELECT NAME, DOJ FROM EMPLOYEE WHERE SALARY BETWEEN 100000 AND 200000;
- iv SELECT * FROM EMPLOYEE WHERE PROJECT = 'P01';

27 (a) Consider the following tables – FACULTY and COURSES:

Table: FACULTY

FID	FNAME	LNAME	JOINDATE	SALARY
F01	Anishma	Garg	2000-12-14	32000
F03	Bhumi	Goel	2001-08-10	15000
F04	Neha	Verma	2000-05-17	27000
F05	Meenu	Sharma	2006-07-11	30000

Table: COURSES

C_ID	FID	CNAME	FEES
C11	F01	Grid Computing	40000
C12	F04	Python	17000
C13	F03	C++	8000
C14	F04	Computer Network	15000
C15	F01	HTML	12000
C16	F05	Data Science	NULL

What will be the output of the following statement?

- i SELECT FID, MIN(FEES), MAX(FEES) FROM COURSES GROUP BY
 FID;
- ii SELECT AVG(SALARY) FROM FACULTY WHERE FNAME LIKE '%a';
- iii SELECT FNAME, CNAME FROM FACULTY F, COURSES C WHERE F.FID=C.FID AND COURSES.FID='F04';
- iv SELECT FNAME, CNAME , FEES FROM FACULTY F , COURSES C
 WHERE F.FID = C.FID AND FEE>15000;
- (b) Write the name of the command to display the structure of a table in a database.

Write a function COUNT() in Python to read from a text file 'Gratitude.txt' and display the count of the letter 'e' in each line

Example: If the file content is as follows:

Gratitude is a humble heart's radiant glow,
A timeless gift that nurtures and bestows.
It's the appreciation for the love we're shown,
In moments big and small, it's truly known.

The COUNT() function should display the output as:

Line 1 : 3 Line 2 : 4 Line 3 : 6 Line 4 : 1

OR

Write a function Start_with_I() in Python, which should read a text file 'Gratitude.txt' and then display lines starting with 'I'. Example: If the file content is as follows:

Gratitude is a humble heart's radiant glow, A timeless gift that nurtures and bestows. It's the appreciation for the love we're shown, In moments big and small, it's truly known.

6

3

	Then the output should be								
	Then the output should be It's the appreciation for the love we're shown,								
	In moments big and small, it's truly known.								
	TU MOME	ents	big and	Small,	1τ ς τ	ruly K	nown.		
29	marks see	cured	d by studen	ts in Sem1	, Sem2, S	Sem3, an	ls to maintand their division of their division of their division of the state of t	sions.	3
	table.			,					
		NO	ROLLNO	SNAME	SEM1	SEM2	DIVISION	1	
	123		101	KARAN	366	410	1	1	
	245		102	NAMAN	300	350	1		
	128		103	ISHA	400	410	1		
	129		104	RENU	350	357	1		
	234		105	ARPIT	100	75	IV		
	187		106	SABINA	100	205	П		
	181		107	NEELAM	470	450	1		
		<u> </u>				·	•	_	
	 Based on the data given above answer the following questions: Identify the columns which can be considered as candidate keys? If 2 more columns are added and 3 rows are deleted from the table result, what will be the new degree and cardinality of the above table? Write a statement to increase the SEM2 marks by 3% for the students securing marks between 70 to 100. 								
30	test-serie Write a F	es in t Pytho	the form St	u_ID:(TS) with the fo	1, TS2, Tollowing	<i>S3)</i> as ke user-def	students for ey-value pai fined function tu_Stk	irs.	3
	 (i) Push_elements(Stu_Stk, Stu_dict): It allows pushing IDs of those students, from the dictionary Stu_dict into the stack Stu_Stk, who have scored more than or equal to 80 marks in the TS3 Test. (ii) Pop_elements(Stu_Stk): It removes all elements present inside the stack in LIFO order and prints them. Also, the function 								
	displays 'Stack Empty' when there are no elements in the stack. Call both functions to execute queries. For example:								
	If the dictionary Stu_dict contains the following data: Stu_dict ={5:(87,68,89), 10:(57,54,61), 12:(71,67,90), 14:(66,81,80), 18:(80,48,91)}								
	After ex [5,12,14,		ing Push_	_element	s(),	Stk_ID	should co	ontain	
	After exe 18 14 12	ecutir	ng Pop_el	ements()	, The ou	tput sho	uld be:		
	5								
	Stack Em	npty							
	5	npty							

Q No.		Questions Section-D (8 Marks)									
31	from an a of various	Create a function maxsalary() in Python to read all the records from an already existing file record.csv which stores the records of various employees working in a department. Data is stored under various fields as shown below:									
	various ii	E_code E_name Scale Salary									
		A01 Bijesh Mehra S4 65400									
		B02	Vikram Goel	S3	60000						
		C09	Suraj Mehta	S2	45300						
	_										
		-	olay the row when		-						
	Note: As	sume that	all employees ha	ve distinc	t salary.						
32	about pr Product expensi 'INVENT higher th count of s For exam (1, 'ABC' (2, 'DEF', (3, 'GHI', then the f Product	Consider a binary file 'INVENTORY.DAT' that stores information about products using tuple with the structure (ProductID, ProductName, Quantity, Price). Write a Python function expensiveProducts() to read the contents of 'INVENTORY.DAT' and display details of products with a price higher than Rs. 1000. Additionally, calculate and display the total count of such expensive products. For example: If the file stores the following data in binary format (1, 'ABC', 100, 5000) (2, 'DEF', 250, 1000) (3, 'GHI', 300, 2000) then the function should display Product ID: 1 Product ID: 3									
Q No.		.хрсз_тс	Questio	ns		Marks					
			Section-E (15	Marks)							
33	planning Delhi. T ADMIN, You as a solutions (i) to (t blocks/bu MUN A	Questions Section-E (15 Marks) Fun Media Services Ltd is an event planning organization. It is planning to set up its India campus in Mumbai with its head office in Delhi. The Mumbai campus will have four blocks/buildings -ADMIN, DECORATORS, FOOD, and MEDIA. You as a network expert need to suggest the best network-related solutions for them to resolve the issues/problems mentioned in points (i) to (v), keeping in mind the distances between various blocks/buildings and other given parameters. MUMBAI DELHI DECORATORS MEDIA DECORATORS									

Shortest distance between various buildings:

FROM – TO	DISTANCE
ADMIN TO DECORATORS	90 meters
ADMIN TO MEDIA	75 meters
ADMIN TO FOOD	50 meters
DECORATORS TO FOOD	65 meters
DECORATORS TO MEDIA	50 meters
FOOD TO MEDIA	45 meters
DELHI Head Office to MUMBAI	1475 KM
Campus	

The number of computers at various buildings is as follows:

BUILDING	NUMBER OF COMPUTERS
ADMIN	110
DECORATORS	75
MEDIA	12
FOOD	20

- i. Suggest the most appropriate location of the server inside the MUMBAI campus (out of the 4 buildings). Justify your answer.
- ii. Draw the cable layout to efficiently connect various buildings within the MUMBAI campus.
- iii. Which hardware device will you suggest to connect all the computers within each building?
- iv. Which of the following will you suggest to establish online face-to-face communication between the people in the Admin Office of the MUMBAI campus and the DELHI Head Office?
 - a. Cable TV
 - b. Email
 - c. Video Conferencing
 - d. Text Chat
- v. What type of network (out of PAN, LAN, MAN, WAN) will be set up in each of the following cases?
 - a. The Mumbai campus gets connected with the Head Quarter in Delhi
 - b. The computers connected in the MUMBAI campus

i. Mention any two differences between seek() and tell().

2+3=5

ii. Consider a file FLIGHT. DAT containing multiple records. The structure of each record is as shown below:

[Fno, FName, Fare, Source, Destination] Write a function COPY_REC() in Python that copies all those records from FLIGHT.DAT where the source is DELHI and the destination is MUMBAI, into a new file RECORD.DAT

OR

- i. Mention any two differences between binary files and csv files?
- ii. Consider a Binary file BOOK.DAT containing a dictionary having multiple elements. Each element is in the form BNO:[BNAME,BTYPE,PRICE] as key:value pair where

BNO – Book Number

BNAME - Book Name

BTYPE - Book Type

PRICE – Book price

Write a user-defined function, findBook(price), that accepts price as parameter and displays all those records from the binary file BOOK.DAT which has a book price more than or equal to the price value passed as a parameter.

5

35

- i. Define the term constraint with respect to RDBMS. Give a suitable example.
- ii. Sameera maintains a database named STORE which contains a table named ITEM with the structure given below:
 - Ino(Item number)- integer
 - Iname(Item Name) string
 - Price (Item Price) float
 - Discount (Discount) float

Note the following to establish connectivity between Python and MySQL:

- Username root
- Password tiger
- Host localhost

Help her to remove the record from the table ITEM for a particular value of item name input by the user.

```
import mysql.connector as mysql
con1= mysql.connect(host='localhost', user='root', password=
'__', database='STORE')  #Statement-1
mycursor = ____  #Statement-2
item_name = input("Enter the Item name to remove the record : ")
query = ____  #Statement-3
mycursor.execute(query)
con1.___  #Statement-4
print('Data Deleted successfully')
con1.close()
```

With reference to the above code, answer the following questions

- a) Complete statement 1 to establish the connection with the database.
- b) Write statement 2 to create the cursor object.
- c) Complete statement 3 to remove the record from the table ITEM based on the item name entered by the user
- d) Complete statement 4 to save the changes in the table.

OR

- i. Write one difference between the alternate key and the candidate key.
- ii. A table named ITEM is created in a database STORE. The table contains multiple columns whose details are as shown below:
 - Ino(Item number)- integer
 - Iname(Item Name) string
 - Price (Item Price) float
 - Discount (Discount) float

Note the following to establish connectivity between Python and MySQL:

- Username root
- Password tiger
- Host localhost

However, the table is to be interfaced with Python to perform certain tasks. The incomplete code is given below:

```
#Line 1
con1= mysql.connect(host='localhost', user = 'root', password =
'tiger', database='STORE')
mycursor = con1.____ #Line 2
query = 'SELECT * FROM ITEM where Price > {}'.format(___) #Line3
mycursor.execute(query)
data = mycursor.___ #Line 4
for rec in data:
      print(rec)
con1.close()
      Complete line 1 to import the appropriate module.
      Complete Line 2 to create the cursor object
 ii.
      Complete the query given in Line 3 to display details of all such
iii.
      items from the table ITEMS whose price is more than 5000.
      Complete Line 4 to extract all the records.
iv.
```

CBSE Additional Practice Question Paper Class: XII Session: 2023-24 Computer Science (083) Marking Scheme

Q No.	Answer	Total Marks
1	a. per%marks	1
2	b. list.append(element)	1
3	b. lcomme T	1
4	b. One block of except statement cannot handle multiple exceptions	1
5	c. Statement 3	1
6	d. dump	1
7	d. dict_student.update(dict_marks)	1
8	b. mean()	1
9	c. 13.5	1
10	PPP – Point to Point Protocol VoIP - Voice Over Internet Protocol	1
11	b. LIKE operator	1
12	d. fetchone	1
13	b. r	1
14	a. file_object.seek(offset [, reference_point])	1
15	d. Interlinking of collection of webpages is called Internet.	1
16	c. TelNet	1
17	a. Both A and R are true and R is the correct explanation for A	1
18	c. A is True but R is False	1
19	Advantages: 1) A dedicated communication channel increases the quality of communication. 2) Suitable for long continuous communication.	2
	Disadvantages: 1) Resources are not utilized fully. 2) The time required to establish the physical link between the two stations is too long.	
	½ mark for each advantage and disadvantage	
	OR	
	Web browser Purpose: Receives and displays web content.	

Function: Initiates requests to web servers, and receives and displays content for users. Web server Purpose: Delivers web content to clients. Function: Listens to incoming requests, processes them, and sends requested content to the client. Name of Web browsers: Google Chrome, Mozilla Firefox I mark for any one correct difference and I/2 mark for each two correct examples 20			
Web server Purpose: Delivers web content to clients. Function: Listens to incoming requests, processes them, and sends requested content to the client. Name of Web browsers: Google Chrome, Mozilla Firefox I mark for any one correct difference and 1/2 mark for each two correct examples 20		Function: Initiates requests to web servers, and receives and displays content	
Purpose: Delivers web content to clients. Function: Listens to incoming requests, processes them, and sends requested content to the client. Name of Web browsers: Google Chrome, Mozilla Firefox I mark for any one correct difference and 1/2 mark for each two correct examples 20		for users.	
Purpose: Delivers web content to clients. Function: Listens to incoming requests, processes them, and sends requested content to the client. Name of Web browsers: Google Chrome, Mozilla Firefox I mark for any one correct difference and 1/2 mark for each two correct examples 20		Web server	
Function: Listens to incoming requests, processes them, and sends requested content to the client. Name of Web browsers: Google Chrome, Mozilla Firefox 1 mark for any one correct difference and 1/2 mark for each two correct examples num1, num2 = 10, 45 while num1 % num2 == 0:			
content to the client. Name of Web browsers: Google Chrome, Mozilla Firefox 1 mark for any one correct difference and 1/2 mark for each two correct examples 20 num1, num2 = 10, 45 while num1 % num2 == 0: num2+= 30 else: print('hello') 1/2 mark for while 1/2 mark for correct indentation (inside the block of while) 1/2 mark for else 21 def dispBook(BOOKS):		-	
Name of Web browsers: Google Chrome, Mozilla Firefox I mark for any one correct difference and 1/2 mark for each two correct examples num1, num2 = 19, 45 while num1 % num2 == 9;			
I mark for any one correct difference and 1/2 mark for each two correct examples 20		content to the client.	
I mark for any one correct difference and 1/2 mark for each two correct examples 20			
examples 20 num1, num2 = 10, 45		Name of Web browsers: Google Chrome, Mozilla Firefox	
examples 20 num1, num2 = 10, 45		1 mark for any one correct difference and 1/2 mark for each two correct	
20 num1, num2 = 10, 45 while num1 % num2 == 9: num1+= 28 num2+= 30 else: print('hello') // mark for while // mark for else 21 def dispBook(BOOKS): for key in BOOKS: if BOOKS[key][0] not in "AEIOUaeiou":		· · · · · · · · · · · · · · · · · · ·	
while num1 % num2 == 0:		examples	
num1+= 20num2+= 30 else: print('hello') //* mark for while //* mark for correct indentation (inside the block of while) //* mark for else 21 def dispBook(BOOKS): for key in BOOKS: if BOOKS[key][0] not in "AEIOUaeiou":	20	num1, $num2 = 10$, 45	2
num2+= 30 else: print('hello') // mark for while // mark for correct indentation (inside the block of while) // mark for else 21 def dispBook(BOOKS): for key in BOOKS: if BOOKS[key][0] not in "AEIOUaeiou":		<pre>while num1 % num2 == 0:</pre>	
else: print('hello') //2 mark for while //2 mark for correct indentation (inside the block of while) //2 mark for else 21 def dispBook(BOOKS): for key in BOOKS: if BOOKS[key][0] not in "AEIOUaeiou":		num1+= 20	
print('hello') //2 mark for while //2 mark for correct indentation (inside the block of while) //2 mark for close 21		num2+= 30	
print('hello') //2 mark for while //2 mark for correct indentation (inside the block of while) //2 mark for close 21		else:	
//z mark for while //z mark for correct indentation (inside the block of while) //z mark for clse 21			
//z mark for correct indentation (inside the block of while) //z mark for else 21			
//z mark for correct indentation (inside the block of while) //z mark for else 21		½ mark for while	
//2 mark for correct indentation (inside the block of while) //2 mark for else 21		· ·	
def dispBook(BOOKS): for key in BOOKS: if BOOKS[key][0] not in "AEIOUaeiou": print(BOOKS[key].upper()) BOOKS = {1:"Python",2:"Internet Fundamentals ",3:"Networking ",4:"Oracle sets",5:"Understanding HTML"} dispBook(BOOKS) //2 mark for for loop I mark for if condition //2 mark for display in upper case		· ·	
def dispBook(BOOKS): for key in BOOKS: if BOOKS[key][0] not in "AEIOUaeiou":			
for key in BOOKS: if BOOKS[key][0] not in "AEIOUaeiou": print(BOOKS[key].upper()) BOOKS = {1:"Python",2:"Internet Fundamentals ",3:"Networking ",4:"Oracle sets",5:"Understanding HTML"} dispBook(BOOKS) //2 mark for for loop I mark for if condition //2 mark for display in upper case		42 mark for else	
<pre>if BOOKS[key][0] not in "AEIOUaeiou":</pre>	21	<pre>def dispBook(BOOKS):</pre>	2
<pre>if BOOKS[key][0] not in "AEIOUaeiou":</pre>		for key in BOOKS:	
BOOKS = {1:"Python", 2:"Internet Fundamentals ", 3:"Networking ", 4:"Oracle sets", 5: "Understanding HTML"} dispBook(BOOKS) //2 mark for for loop 1 mark for if condition //2 mark for display in upper case OR def FindWord(STRING, SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') //2 mark for input //2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 //2 mark for 14\$ //2 mark for 19\$ //2 mark for 19\$ //2 mark for 5\$ i. del D['Mumbai']			
",4:"Oracle sets",5:"Understanding HTML"} dispBook(BOOKS) //2 mark for for loop I mark for if condition //2 mark for display in upper case OR def FindWord(STRING,SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') //2 mark for input //2 mark for print statement I mark for counting the word and returning the value 22 9\$14\$19\$5\$		<pre>print(BOOKS[key].upper())</pre>	
",4:"Oracle sets",5:"Understanding HTML"} dispBook(BOOKS) //2 mark for for loop I mark for if condition //2 mark for display in upper case OR def FindWord(STRING,SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') //2 mark for input //2 mark for print statement I mark for counting the word and returning the value 22 9\$14\$19\$5\$			
dispBook(BOOKS) //2 mark for for loop I mark for if condition //2 mark for display in upper case OR def FindWord(STRING, SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') //2 mark for input //2 mark for input I mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 //2 mark for 14\$ //2 mark for 19\$ //2 mark for 19\$ //2 mark for 5\$ i. del D['Mumbai']		BOOKS = {1:"Python",2:"Internet Fundamentals ",3:"Networking	
//2 mark for for loop I mark for if condition //2 mark for display in upper case OR def FindWord(STRING, SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') //2 mark for input //2 mark for print statement I mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 //2 mark for 9\$ //2 mark for 14\$ //2 mark for 19\$ //2 mark for 5\$ i. del D['Mumbai']		",4:"Oracle sets",5:"Understanding HTML"}	
I mark for if condition ½ mark for display in upper case OR def FindWord(STRING, SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') ½ mark for input ½ mark for print statement I mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 ½ mark for 9\$ ½ mark for 14\$ ½ mark for 19\$ ½ mark for 5\$ i. del D['Mumbai']		dispBook(BOOKS)	
I mark for if condition ½ mark for display in upper case OR def FindWord(STRING, SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') ½ mark for input ½ mark for print statement I mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 ½ mark for 9\$ ½ mark for 14\$ ½ mark for 19\$ ½ mark for 5\$ i. del D['Mumbai']			
OR def FindWord(STRING, SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') 1/2 mark for input 1/2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 2 1. del D['Mumbai']		½ mark for for loop	
OR def FindWord(STRING, SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') 1/2 mark for input 1/2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 2 1. del D['Mumbai']			
def FindWord(STRING,SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') 1/2 mark for input 1/2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 2 1. del D['Mumbai']			
<pre>def FindWord(STRING, SEARCH): return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') //2 mark for input //2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 //2 mark for 9\$ //2 mark for 14\$ //2 mark for 19\$ //2 mark for 5\$ i. del D['Mumbai']</pre> 2			
return (STRING . count (SEARCH)) str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') 1/2 mark for input 1/2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 2 i. del D['Mumbai']			
str = input('Enter String : ') word = input('Enter word to search : ') print('The word', word, 'occurs', FindWord(str,word), 'times') 1/2 mark for input 1/2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 2 i. del D['Mumbai']			
word = input('Enter word to search: ') print('The word', word, 'occurs', FindWord(str,word), 'times') 1/2 mark for input 1/2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 2 i. del D['Mumbai']		Tecarin (Strizine Counce (Szimeni)	
word = input('Enter word to search: ') print('The word', word, 'occurs', FindWord(str,word), 'times') 1/2 mark for input 1/2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 2 i. del D['Mumbai']		<pre>str = input('Enter String : ')</pre>	
print('The word', word, 'occurs', FindWord(str,word), 'times') 1/2 mark for input 1/2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 2 2 i. del D['Mumbai']			
 ½ mark for input ½ mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ ½ mark for 9\$ ½ mark for 14\$ ½ mark for 19\$ ½ mark for 5\$ 23 i. del D['Mumbai'] 			
1/2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 23 i. del D['Mumbai']			
1/2 mark for print statement 1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 23 i. del D['Mumbai']		½ mark for input	
1 mark for counting the word and returning the value 22 9\$14\$19\$5\$ 2 ½ mark for 9\$ ½ mark for 14\$ ½ mark for 19\$ ½ mark for 5\$ 2 23 i. del D['Mumbai'] 2		· ·	
22 9\$14\$19\$5\$ 2		· -	
1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 23 i. del D['Mumbai']		1 mark for counting the word and returning the value	
1/2 mark for 9\$ 1/2 mark for 14\$ 1/2 mark for 19\$ 1/2 mark for 5\$ 23 i. del D['Mumbai']	22	9\$14\$19\$5\$	2
½ mark for 14\$ ½ mark for 19\$ ½ mark for 5\$ 23 i. del D['Mumbai'] 2			
½ mark for 14\$ ½ mark for 19\$ ½ mark for 5\$ 23 i. del D['Mumbai'] 2		1/2 mark for 9\$	
½ mark for 19\$ ½ mark for 5\$ 23 i. del D['Mumbai'] 2		· ·	
½ mark for 5\$ 23 i. del D['Mumbai'] 2		· ·	
23 i. del D['Mumbai'] 2		· ·	
		½ mark for 5\$	
	23	i. del D['Mumbai']	2
1 mark joi correct answer	23		
		1 mark joi correct answer	

	:: maint(C anlit())					
	<pre>ii. print(S.split()) 1 mark for correct answer</pre>					
	OR					
	my_str = "Computer Science"					
	alternate_chars = my_str[::2]					
	print(alternate_chars)					
	print(uncernate_cnars)					
	1.5 mark for logic of alternate characters					
	½ mark for printing alternate characters					
2.4		2				
24	% (Percentage):	2				
	Matches any sequence of characters (including empty sequence). The description of t					
	• Example: LIKE 'T%' matches all those strings starting with the letter 'T'.					
	The string with just 1 character 'T' will also be considered.					
	(III. dans a sur).					
	_ (Underscore):					
	Matches a single character. The standard of the standard					
	• Example: LIKE 'T' on the other hand will search for a three letter					
	string, whose 3rd letter is 'T'. At first two places any two character can					
	appear.					
	1 mark for an account difference of 1/2 mark and for account account of and					
	1 mark for one correct difference. 1/2 mark each for correct example of each. OR					
	OK					
	DROP is a DDL command in SQL and can be used to remove tables (or					
	database).					
	Example: 'DROP TABLE STUDENT;' will remove the table STUDENT from					
	the database.					
	the database.					
	DELETE is a DML command used to remove or delete rows/records from a					
	table.					
	Example: 'DELETE FROM STUDENT WHERE PER < 33;' will remove all					
	those records from the table STUDENT where the percentage is less than 33.					
	1 mark for one correct difference. 1/2 mark each for correct example of each.					
25	COUNT(*) returns the count of all rows in the table, whereas COUNT()	2				
20	is used with Column_Name passed as an argument and counts the number	_				
	of non-NULL values in a column that is given as an argument. Hence the					
	result may differ.					
	 The SQL command with COUNT(*) may have higher value as it count 					
	all rows in the table.					
	1 mark for suitable reason					
	1 mark for mentioning correct command					
26		3				
26	(a)	3				
	CODE BNAME TYPE MNO MNAME ISSUEDATE					
	L102 Easy Python Programming M101 SNEH SINHA 2022-10-13					
	F102 Untold Story Fiction M103 SARTHAK 2021-02-23					
	C101 Juman Ji Thriller M102 SARA KHAN 2022-06-12					
	1 mark for correct answer					

	(b)	
	(i)	
	NAME PROJECT	
	Satyansh P04	
	Ranjan P01	
	Muneera P01	
	Alex P02	
	Akhtar P04	
	½ mark for correct output	
	(ii) NAME SALARY	
	Akhtar 125000	
	Akmai 123000 Alex 75000	
	Alex 75000	
	½ mark for correct output	
	(iii)	
	NAME DOJ	
	Ranjan 2015-01-21	
	Akhtar 2015-02-01	
	Muneera 2018-08-19	
	½ mark for correct output	
	(iv)	
	Éid Name DOB DOJ Salary Project	
	E01 Rannja 1990-07-12 2015-01-21 150000 P01	
	E03 Muneera 1996-11-15 2018-08-19 135000 P01	
	½ mark for correct output	
27	(a)	3
21	(a)	3
	(i) FID MIN(FEES) MAX(FEES)	
	FID MIN(FEES) MAX(FEES) F01 12000 40000	
	F04 15000 17000	
	F03 8000 8000	
	F05 NULL NULL	
	103 INCEL	
	½ mark for correct answer	
	½ mark for correct answer	
	½ mark for correct answer (ii)	
	(ii)	
	(ii) AVG(SALARY)	
	(ii) AVG(SALARY) 29500 1/2 mark for correct answer	
	(ii) AVG(SALARY) 29500 1/2 mark for correct answer (iii)	
	(ii) AVG(SALARY) 29500 1/2 mark for correct answer (iii) FNAME CNAME	
	(ii) AVG(SALARY) 29500 1/2 mark for correct answer (iii) FNAME CNAME Neha Python	
	(ii) AVG(SALARY) 29500 1/2 mark for correct answer (iii) FNAME CNAME	
	(ii) AVG(SALARY) 29500 1/2 mark for correct answer (iii) FNAME CNAME Neha Python Neha Computer Network 1/2 mark for correct answer (iv)	
	(iii) AVG(SALARY) 29500 1/2 mark for correct answer (iii) FNAME CNAME Neha Python Neha Computer Network 1/2 mark for correct answer (iv) FNAME CNAME FEES	
	(iii) AVG(SALARY) 29500 1/2 mark for correct answer (iii) FNAME CNAME Neha Python Neha Computer Network 1/2 mark for correct answer (iv) FNAME CNAME FEES Anishma Grid Computing 40000	
	(iii) AVG(SALARY) 29500 1/2 mark for correct answer (iii) FNAME CNAME Neha Python Neha Computer Network 1/2 mark for correct answer (iv) FNAME CNAME FNAME FEES Anishma Grid Computing 40000 Neha Python 17000	
	(iii) AVG(SALARY) 29500 1/2 mark for correct answer (iii) FNAME CNAME Neha Python Neha Computer Network 1/2 mark for correct answer (iv) FNAME CNAME FEES Anishma Grid Computing 40000	

```
(b)
           DESC or DESCRIBE command
           1 mark for correct answer
     def Count():
28
                                                                                   3
          F=open('Gratitude.txt')
          T=F.readlines()
          X=1
          for i in T:
              print('Line',X,':',i.count('e'))
              X=X+1
          F.close()
     Count()
     ½ mark for function header
     ½ mark for opening and closing the file
     ½ mark for reading lines
     ½ mark for loop
     ½ mark for count function/or any other alternate correct statement(s)
     ½ mark for counter
                                        OR
     def Start_with_I():
          F=open('Gratitude.txt')
          T=F.readlines()
          for i in T:
             if i[0] in 'Ii':
                 print(i,end='')
          F.close()
     Start_with_I()
     ½ mark for function header
     ½ mark for opening and closing the file
     ½ mark for reading lines
     ½ mark for loop
     1/2 mark for if condition
     ½ mark for print statment
29
     (i) Candidate Keys: ADMNO, ROLLNO
                                                                                   3
     1 mark for correctly writing both names of candidate keys. OR ½ mark for
     specifying any one candidate key correctly.
     (ii) Degree-8, Cardinality=4
     ½ mark for degree and ½ mark for cardinality
     (iii) Update result set SEM2=SEM2+.03*SEM2 where SEM2 between 70
     and 100;
     ½ mark for writing Update result set part correctly
     ½ mark for writing SEM2=SEM2+.03*SEM2 where SEM2 between 70 and
     100; correctly.
     Stu_dict={5:(87,68,89), 10:(57,54,61), 12:(71,67,90),
30
                                                                                   3
     14:(66,81,80), 18:(80,48,91)}
```

```
Stu_Stk=[]
      def Push_elements(Stu_Stk, Stu_dict):
          for Stu_ID, marks in Stu_dict.items():
               if marks[2]>=80:
                   Stu_Stk.append(Stu_ID)
      def Pop_elements(Stu_Stk):
            while len(Stu_Stk)>0:
                print(Stu_Stk.pop())
            if not Stu_Stk:
                print('Stack Empty')
      Push_elements(Stu_Stk, Stu_dict)
      Pop elements(Stu Stk)
      1.5 marks for correct implementation of Push_elements()
      1.5 marks for correct implementation of Pop_elements()
      import csv
31
                                                                                      4
      def maxsalary():
          f=open('record.csv',
          reader=csv.reader(f)
          skip header = True
          max= 0
          for row in reader:
               if skip_header:
                   skip_header = False
              else:
                   if(int(row[3])>max):
                       max=int(row[3])
                        rec=row
          print('Row with the highest salary : ', rec)
          f.close()
      maxsalary()
      ½ mark for importing module
      ½ mark for function definition
      ½ mark for opening and closing file
      ½ for reader object
      ½ for skipping first row (i.e. header)
      1 mark for calculating maximum salary
      ½ mark for displaying record having maximum salary
      import pickle
32
                                                                                      4
      def expensiveProducts():
         with open('INVENTORY.DAT', 'rb') as file:
             expensive_count = 0
             while True:
                 try:
                     product_data = pickle.load(file)
                     product_id, product_name, quantity, price = product_data
                     if price > 1000:
                        print("Product ID:", product_id)
                        expensive_count += 1
                 except EOFError:
                     break
             print("Total expensive products: ", expensive_count)
      expensiveProducts()
      ½ mark for function definition
```

1/2 mark for opening and closing file
1/2 mark for correct try and except block
1.5 mark identifying and displaying details of expensive products
1 mark for displaying count of expensive products


i. The most appropriate location of the server inside the MUMBAI campus is ADMIN building due to the maximum number of computers in it.

5

5

½ mark for mentioning the branch and ½ mark for proper justification

ii. Cable Layout



1 mark for drawing any valid cable layout

iii. Switch or Hub

1mark for suggesting the correct device

iv. c. Video Conferencing

1 mark for correct answer

v.

- (a) WAN
- (b) LAN

½ mark for mentioning WAN and ½ mark for mentioning LAN

34 i.

	seek()	tell()
Purpose	Repositions the file pointer to a	Returns the current
	specific location within a file	position of the file
		pointer
Syntax	<pre>seek(offset [,reference point])</pre>	tell()
Parameters	Requires specifying the offset	Requires no
	and an optional reference point	parameters

2 marks for mentioning two correct differences.

OR

1 marks for mentioning only one correct differences.

ii.

```
import pickle
def COPY_REC():
    In_file = open('FLIGHT.DAT','rb')
    out_file = open('RECORD.DAT','wb')
    try:
```

```
while True:
             data = pickle.load(In_file)
             if data[3] == 'DELHI' and data[4] == 'MUMBAI':
                 pickle.dump(data,out_file)
    except:
        In_file.close()
        out_file.close()
COPY_REC()
½ mark for function definion
½ mark for correctly opening and closing file
½ mark for correct try and except block
1.5 marks for writing required data in RECORD.DAT
                                   OR
  i.
                                       CSV
        Binary
        1. pickle module to be used
                                       1. csv module is used
        2. Data is stored in binary
                                       2. Data is stored in tabular
        format(0s and 1s) and is not
                                       fashion and comma
        in human readable form using
                                       separated by default. The
                                       file can be read by any
        any plain text editor.
                                       spreadsheet software or text
                                       editor.
        3. File extension .dat/.pdf/.exe
                                       3. File extension .csv
        etc.
2 marks for mentioning two correct differences.
OR
1 marks for mentioning only one correct differences.
  ii.
import pickle
def findBook(price):
    with open('BOOK.DAT', 'rb') as file:
        while True:
             try:
                 book_record = pickle.load(file)
                 for item in book_record:
                      book_price = book_record[item][2]
                      if book_price >= price:
                          print(item, book_record[item])
             except EOFError:
                 break
```

½ mark for function definion

findBook(50)

½ mark for correctly opening and closing file

½ mark for correct try and except block

1.5 marks for displying required records

35 (i) 5

SQL constraints are used to specify rules for the data in a table. Constraints are used to limit the type of data that can go into a table.

Constraints -

NOT NULL - Ensures that a column cannot have a NULL value UNIQUE - Ensures that all values in a column are different PRIMARY KEY - A combination of a NOT NULL and UNIQUE. Uniquely identifies each row in a table

½ mark for correct definition, ½ mark for correct example (anyone) (ii)

- a) password='tiger'
- b) mycursor = con1.cursor()
- c) query = 'delete from ITEM where Iname = "{}" '.format.(item_name)
- d) con1.commit()

1 mark for each correct statement

OR

(i)

Candidate Key: A candidate key is a set of attributes in a relation that can uniquely identify each tuple (row). A relation can have multiple candidate keys, but only one of them is chosen as the primary key.

Alternate Key: An alternate key is a candidate key that is not selected as the primary key.

1 mark for any one correct difference.

(ii)

- a) import mysql.connector as mysql
- b) mycursor = con1.cursor()
- c) query = 'SELECT * FROM ITEM where Price > { }'.format(5000)
- d) data = mycursor.fetchall()

1 mark for each correct statement

Set-4

प्रश्न-पत्र कोड Q.P. Code



रोल नं. Roll No. 2 3 6 9 4 7 9 1

Candidates must write the Q.P. Code on the title page of the answer-book.



COMPUTER SCIENCE

Time allowed: 3 hours

Maximum Marks: 70

NOTE

- (I) Please check that this question paper contains 15 printed pages.
- (II) Please check that this question paper contains 35 questions.
- (III) Q.P. Code given on the right hand side of the question paper should be written on the title page of the answer-book by the candidate.
- (IV) Please write down the serial number of the question in the answer-book before attempting it.
- (V) 15 minute time has been allotted to read this question paper. The question paper will be distributed at 10.15 a.m. From 10.15 a.m. to 10.30 a.m., the candidates will read the question paper only and will not write any answer on the answer-book during this period.

2191 270

1

General Instructions:

- (i) Please check this question paper contains 35 questions.
- (ii) The paper is divided into 5 Sections A, B, C, D and E.
- (iii) Section A, consists of 18 questions (1 to 18). Each question carries 1 mark.
- (iv) Section B, consists of 7 questions (19 to 25). Each question carries 2 marks.
- (v) Section C, consists of 5 questions (26 to 30). Each question carries 3 marks.
- (vi) Section D, consists of 2 questions (31 to 32). Each question carries 4 marks.
- (vii) Section E, consists of 3 questions (33 to 35). Each question carries 5 marks.
- (viii) All programming questions are to be answered using Python Language only.

SECTION - A

- State True or False:
 While defining a function in Python, the positional parameters in the function header must always be written after the default parameters.
- 2. The SELECT statement when combined with _____ clause, returns records without repetition.
 - (a) DISTINCT

(b) DESCRIBE

(c) UNIQUE

- (d) NULL
- 3. What will be the output of the following statement:

print (16*5/4*2/5-8)

(a) -3.33

(b) 6.0

(c) 0.0

2191

- (d) -13.33
- 4. What possible output from the given options is expected to be displayed when the following Python code is executed?

import random

Signal = ['RED', 'YELLOW', 'GREEN']

for K in range (2, 0, -1) :

R = random.randrange(K)

print (Signal[R], end = '#')

(a) YELLOW # RED #

(b) RED # GREEN #

(c) GREEN # RED #

(d) YELLOW # GREEN #

2

1

1

1

5.		SQL, the aggregate function le is	n which	will display the cardinality of the	1
	(a)	sum()	(l	b) count(*)	
	(c)	avg()	(0	d) sum(*)	
	4				
6.		ich protocol out of the follow mputer network?	ing is us	sed to send and receive emails over	1
	(a)	PPP	(b	b) HTTP	
	(c)	FTP	(d)	d) SMTP	
7.	Iden	ntify the invalid Python state	ment fro	om the following:	1
	(a)	d = dict()	(b)) e = {}	
	(c)	f = []	(d)) g = dict{}	•
8.	from	sider the statements given be the given options : tr="MISSISSIPPI" nt (myStr[:4]+"#"+myStr		d then choose the correct output	1
	(a)	MISSI#SIPPI	(b)	MISS#SIPPI	
		MISS#IPPIS	(d)	MISSI#IPPIS	
9.	Ident	tify the statement from the fo	ollowing	which will raise an error:	L
	(a)	print("A"*3)	(b)	print(5*3)	
	(c)	print("15" + 3)	(d)	print("15" + "13")	
	event L=eve	t the correct output of the following the correct output of the		code: 1	
		G20'	(b)	['Presidency@2023']	
		'G20']	(d)	'Presidency@2023' P.T.O.	

		ch of the fo		the co	rrect unit of measurement for	1
	(a)	KB	tun.	(b)	Bit	
	(c)	Hz	(*) #Ws(i)	(d)	Km	
12.	Obs	erve the giv	en Python code care	fully :	racitist with the teachering of data in the contract of the co	1
	a=2	0	es, eggis,		495 (1)	
	def	convert ((a):			
		b=20			(2001년 1월 1일 1일 2일 4일 2일 등 1일	
		a=a+b	To the works and the	i suam	ourse stores billions soll-browning	
					tut dia dieta	
	con	vert(10)	Visosh m p Vi	본다고요		
	pri	.nt(a)			가는 사람이 이번 이번 때문에 되었다. 가다 있는 사람들은 사람들은 사람이 있는 것이 없는 것이 없다.	
	Sel	ect the corre	ect output from the g	given o	otions:	
	(a)	10		(b)	20	
	(c)	30		(d)	Error "1991821821M" = 13	
				([:Em	gerne (mySee[:4]+'#'+mySer!	
13.	Sta	te whether	the following statem	ent is	True or False :	1
	Wh	nile handlin npulsorily a	ng exceptions in Pytadded with except c	thon, n lause.	name of the exception has to be	
	1171	ich of the f	ollowing is not a DD	I. comr	nand in SQL ?	1
14.			onowing is not a bb	(b)	[Madel Policy] [125] 4 2012일 12 : 12 : 12 : 12 : 12 : 12 : 12 : 1	
	(a)				물론 얼마 다른 것 같아 없는 사람들이 되었다.	
	(c)	UPDATE		(d)	ALTER	
					evector Gio Presidency 62023	
15.	Fil	l in the bla	시 교육 회에서는 그 사회에 가장하는 경험을		The state of the second	1
			그 맛있는 그 얼마나는 것이 없어 없어요. 그런 그게 되었다. 그런 어머니?		be followed by the communicating	
	pa	rties in orde	er to have a successf	ul and	reliable data communication over	
	aı	network.	e Caramak Assault			
219	91			4		

Consider the following Python statement: F=open ('CONTENT.TXT') Which of the following is an invalid statement in Python? (a) F. seek (1,0) (b) F.seek(0,1) F. seek (0,-1) (c) (d) F.seek (0,2) Q. 17 and 18 are ASSERTION (A) and REASONING (R) based questions. Mark the correct choice as Both (A) and (R) are true and (R) is the correct explanation for (A). Both (A) and (R) are true and (R) is not the correct explanation for (b) (A). (c) (A) is true but (R) is false. (d) (A) is false but (R) is true. 17. Assertion (A): CSV file is a human readable text file where each line has a number of fields, separated by comma or some other delimiter. 1 : writerow() method is used to write a single row in a Reason (R) CSV file. sometod, dobb, part hamily hi nation than are conveyending grade obtained for 18. Assertion (A): The expression "HELLO".sort() in Python will give Average of Mac Math, Stagnos an error. 1 : sort() does not exist as a method/function for strings Reason (R) in Python. SECTION - B 19. (A) (i) Expand the following terms: 1 + 1 = 2XML, PPP Give one difference between circuit switching and packet (ii) switching. OR (B) (i) Define the term web hosting. Name any two web browsers. (ii)

2191

The code given below accepts five numbers and displays whether they are even or odd:

2

 $\mathbf{2}$

Observe the following code carefully and rewrite it after removing all syntax and logical errors:

Underline all the corrections made.

A CONTRACTOR OF THE STATE OF TH

```
def EvenOdd()
    for i in range (5):
        num=int(input("Enter a number")
        if num/2==0:
            print ("Even")
        else:
        print("Odd")
EvenOdd()
```

21. (A) Write a user defined function in Python named showGrades (S) which takes the dictionary S as an argument. The dictionary, S contains Name: [Eng, Math, Science] as key: value pairs. The function displays the corresponding grade obtained by the students according to the following grading rules:

Grade Average of Eng, Math, Science A >=90 В <90 but >=60 C <60

For example: Consider the following dictionary

S={"AMIT": [92,86,64], "NAGMA": [65,42,43], "DAVID": [92,90,88]}

The output should be:

AMIT - B

NAGMA - C

DAVID - A

OR

2191

(B) Write a user defined function in Python named Puzzle (W, N) which takes the argument W as an English word and N as an integer and returns the string where every Nth alphabet of the word W is replaced with an underscore ("_").

For example: if W contains the word "TELEVISION" and N is 3, then the function should return the string "TE_EV_SI_N". Likewise for the word "TELEVISION" if N is 4, then the function should return "TEL_VIS_ON".

Write the output displayed on execution of the following Python code:

LS=["HIMALAYA", "NILGIRI", "ALASKA", "ALPS"]

D={}

for S in LS :

if len(S) %4 == 0:

D[S] = len(S)

for K in D :

print(K,D[K], sep = "#")

- 23. (A) Write the Python statement for each of the following tasks using built-in functions/methods only: 1+1=2
 - (i) To remove the item whose key is "NISHA" from a dictionary named Students.

 For example, if the dictionary Students contains

{"ANITA":90, "NISHA":76, "ASHA":92}, then after removal the dictionary should contain {"ANITA":90, "ASHA":92}

(ii) To display the number of occurrences of the substring "is" in a string named message.

For example if the string message contains "This is his book", then the output will be 3.

OR

(B) A tuple named subject stores the names of different subjects. Write the Python commands to convert the given tuple to a list and thereafter delete the last element of the list.

 (A) Ms. Veda created a table named Sports in a MySQL database, containing columns Game_id, P_Age and G_name.

2

After creating the table, she realized that the attribute, Category has to be added. Help her to write a command to add the Category column. Thereafter, write the command to insert the following record in the table:

Game_id: G42

P Age: Above 18

G name : Chess

Category : Senior

OR

- (B) Write the SQL commands to perform the following tasks:
 - (i) View the list of tables in the database, Exam.
 - (ii) View the structure of the table, Term1.
- 25. Predict the output of the following code:

```
def callon(b=20,a=10):
```

b=b+a

a=b-a

print(b,"#",a)

return b

x=100

y=200

x=callon(x,y)

print(x,"@",y)

y=callon(y)

print(x,"@",y)

8

SECTION - C

Write the output on execution of the following Python code:

s="Racecar Car Radar"

L=S.split()

for W in L :

x=W.upper()

if x==x[::-1]:

for I in x:

print(I,end="*")

else:

for I in W:

print(I,end="#")

print()

27. Consider the table ORDERS given below and write the output of the SQL queries that follow: $1 \times 3 = 3$

ORDNO	ITEM	QTY	RATE	ORDATE
1001	RICE	23	120	2023-09-10
1002	PULSES	13	120	2023-10-18
1003	RICE	25	110	2023-11-17
1004	WHEAT	28	65	2023-12-25
1005	PULSES	16	110	2024-01-15
1006	WHEAT	27	55	2024-04-15
1007	WHEAT	25	60	2024-04-30

- (i) SELECT ITEM, SUM(QTY) FROM ORDERS GROUP BY ITEM;
- (ii) SELECT ITEM, QTY FROM ORDERS WHERE ORDATE BETWEEN '2023-11-01' AND '2023-12-31';
- (iii) SELECT ORDNO, ORDATE FROM ORDERS WHERE ITEM = 'WHEAT'
 AND RATE>=60;.

28. (A) Write a user defined function in Python named showInLines() which reads contents of a text file named STORY.TXT and displays every sentence in a separate line.

Assume that a sentence ends with a full stop (.), a question mark (?), or an exclamation mark (!).

For example, if the content of file STORY. TXT is as follows:

Our parents told us that we must eat vegetables to be healthy. And it turns out, our parents were right! So, what else did our parents tell?

Then the function should display the file's content as follows:

Our parents told us that we must eat vegetables to be healthy.

And it turns out, our parents were right! So, what else did our parents tell?

OR

- (B) Write a function, c_words() in Python that separately counts and displays the number of uppercase and lowercase alphabets in a text file, Words.txt.
- 29. Consider the table Projects given below:

 $1 \times 3 = 3$

3

Table : Projects

P_id	Pname	Language	Startdate	Enddate
P001	School Management System	Python	2023-01-12	2023-04-03
P002	Hotel Management System	C++	2022-12-01	2023-02-02
P003	Blood Bank	Python	2023-02-11	2023-03-02
P004	Payroll Management System	Python	2023-03-12	2023-06-02

Based on the given table, write SQL queries for the following:

- (i) Add the constraint, primary key to column P_id in the existing table Projects.
- (ii) To change the language to Python of the project whose id is P002.
- (iii) To delete the table Projects from MySQL database along with its data.

30. Consider a list named Nums which contains random integers.

Write the following user defined functions in Python and perform the specified operations on a stack named BigNums.

3

- (i) PushBig(): It checks every number from the list Nums and pushes all such numbers which have 5 or more digits into the stack, BigNums.
- (ii) PopBig(): It pops the numbers from the stack, BigNums and displays them. The function should also display "Stack Empty" when there are no more numbers left in the stack.

For example: If the list Nums contains the following data:

Nums = [213,10025,167,254923,14,1297653,31498,386,92765]

Then on execution of PushBig(), the stack BigNums should store:

[10025, 254923, 1297653, 31498, 92765]

And on execution of PopBig(), the following output should be displayed:

92765

31498

1297653

254923

10025

Stack Empty

SECTION - D

31. Consider the tables Admin and Transport given below:

 $1 \times 4 = 4$

Table : Admin

S_id	S_name	Address	S_type
S001	Sandhya	Rohini	Day Boarder
S002	Vedanshi	Rohtak	Day Scholar
8003	Vibhu	Raj Nagar	NULL
S004	Atharva	Rampur	Day Boarder

2191

Table : Transport

S_id	Bus_no	Stop_name
S002	TSS10	Sarai Kale Khan
S004	TSS12	Sainik Vihar
S005	TSS10	Kamla Nagar

Write SQL queries for the following:

- (i) Display the student name and their stop name from the tables

 Admin and Transport.
- (ii) Display the number of students whose S_type is not known.
- (iii) Display all details of the students whose name starts with 'V'.
- (iv) Display student id and address in alphabetical order of student name, from the table Admin.
- 32. Sangeeta is a Python programmer working in a computer hardware company. She has to maintain the records of the peripheral devices. She created a csv file named Peripheral.csv, to store the details. The structure of Peripheral.csv is:

[P_id,P_name,Price]

where

P_id is Peripheral device ID (integer)

P_name is Peripheral device name (String)

Price is Peripheral device price (integer)

Sangeeta wants to write the following user defined functions:

Add_Device(): to accept a record from the user and add it to a csv file, Peripheral.csv.

Count_Device(): To count and display number of peripheral devices whose price is less than 1000.


SECTION - E

3. Infotainment Ltd. is an event management company with its prime office located in Bengaluru. The company is planning to open its new division at three different locations in Chennai named as - Vajra, Trishula and Sudershana.

 $1 \times 5 = 5$

You, as a networking expert need to suggest solutions to the questions in part (i) to (v), keeping in mind the distances and other given parameters.

Bengaluru Office



Distances between various locations:

Vajra to Trishula	350 m
Trishula to Sudershana	415 m
Sudershana to Vajra	300m
Bengaluru Office to Chennai	2000 km

Number of computers installed at various locations:

Vajra	120
Sudershana	75
Trishula	. 65
Bengaluru Office	250

- Suggest and draw the cable layout to efficiently connect various (i) locations in Chennai division for connecting the digital devices.
- Which block in Chennai division should host the server? Justify your (ii) answer.
- (iii) Which fast and effective wired transmission medium should be used to connect the prime office at Bengaluru with the Chennai division?

- (iv) Which network device will be used to connect the digital devices within each location of Chennai division so that they may communicate with each other?
- A considerable amount of data loss is noticed between different locations of the Chennai division, which are connected in the network. Suggest a networking device that should be installed to refresh the data and reduce the data loss during transmission to and from different locations of Chennai division.
- 34. (A) (i) Differentiate between 'w' and 'a' file modes in Python.
 - Consider a binary file, items.dat, containing records stored in the given format:

{item_id: [item_name,amount]}

Write a function, Copy_new(), that copies all records whose amount is greater than 1000 from items.dat to new_items. dat.

OR

What is the advantage of using with clause while opening a data (B) (i) file in Python? Also give syntax of with clause.

14

A binary file, EMP.DAT has the following structure:

[Emp Id, Name, Salary]

where

Emp Id: Employee id

Name: Employee Name

Salary : Employee Salary

Write a user defined function, disp_Detail(), that would rea the contents of the file EMP.DAT and display the details of thos employees whose salary is below 25000.

- 35. (A) (i) Define cartesian product with respect to RDBMS.
- 1 + 4 = 5
- (ii) Sunil wants to write a program in Python to update the quantity to 20 of the records whose item code is 111 in the table named shop in MySQL database named Keeper.

The table shop in MySQL contains the following attributes:

- Item_code: Item code (Integer)
- Item name: Name of item (String)
- Qty: Quantity of item (Integer)
- Price: Price of item (Integer)

Consider the following to establish connectivity between Python and MySQL:

- Username: admin
- Password: Shopping
- Host:localhost

OR

- (B) (i) Give any two features of SQL.
 - (ii) Sumit wants to write a code in Python to display all the details of the passengers from the table flight in MySQL database, Travel. The table contains the following attributes:

F_code: Flight code (String)

F_name: Name of flight (String)

Source: Departure city of flight (String)

Destination: Destination city of flight (String)

Consider the following to establish connectivity between Python and MySQL:

- Username : root
- Password : airplane
- Host : localhost

CBSE Supp Exam 15/2/2024

Series &RQPS/S

Set-4

Q.P. Code

91/S

Roll No.		Candidat on the tit	tes must write the Q.P. Code le page of the answer-book.
	essions complete 3 o	g see V.S.T. v case of the	a Series Bas 7 Very B



COMPUTER SCIENCE

Time allowed: 3 hours

Maximum Marks: 70

NOTE

- (I) Please check that this question paper contains 15 printed pages.
- (II) Please check that this question paper contains 35 questions.
- (III) Q.P. Code given on the right hand side of the question paper should be written on the title page of the answer-book by the candidate.
- (IV) Please write down the serial number of the question in the answer-book before attempting it.
- (V) 15 minute time has been allotted to read this question paper. The question paper will be distributed at 10.15 a.m. From 10.15 a.m. to 10.30 a.m., the students will read the question paper only and will not write any answer on the answer-book during this period.

General Instructions:

Please read the instructions carefully.

- This question paper has 5 Sections: Sections A, B, C, D, E.
- All questions are compulsory. However, an internal choice of approximately 30% is provided.
- Section A has 18 questions carrying 1 mark each.
- Section B has 7 Very Short Answer (VSA) type questions carrying 2 marks each.
- Section C has 5 Short Answer (SA) type questions carrying 3 marks each.
- Section D has 2 Long Answer (LA) type question carrying 4 marks.
- Section E has 3 Source-based/Case-based/Passage-based questions carrying 5 marks each.

		SEC	TION .	An and the second of the	18×1=18
1.	Stat	e True or False :			1
	"In l	Python, tuple is a mutable data	a type".		
2.	The	primary key is selected from the	he set of		1
	(A)	composite keys	(B)	alternate keys	
	(C)	candidate keys	(D)	foreign keys	
3.		at will be the output of the follo	wing st	atement?	1
	(A)	-14.0	(B)	14.0	
	(C)	14	(D)	-14	
4.	Sele	ct the correct output of the code	e:	ari da angan a Pangan angan a	1
	s =	"text#next"			
	pri	nt(S.strip("t"))			
	(A)	ext#nex	(B)	ex#nex	
	(C)	text#nex	(D)	ext#next	
91/	S		2		

	(D)	18.57					
	(C)	10					
	(B)	20					
	(A)	30	and Brown III as				
9.	>>>:	import statistic s.mode ([10, 20,	s as s 10, 30, 10, 2	0, 30])	adragani 90. (25) atrod Imag		
0		lict the output of the	following Python	statements:		1	
	(C)	puC dlroW	. (D)	Error	(DE) dead		
	(A)	CdrW	(B)	ce o	a.e).Pulliq		
	pri	nt (Game [-6::-1])					
8.	from	sider the statements the given options : e="World Cup 202		then choose th	e correct ou	1	ii ii
Name of the Park	(C)	user_2		user 2		Krist Ki	
	(A)	2user	210 (01	user@2			
7.	Iden	tify the valid Python	identifier from th	ne following :		1	
	(C)	Long	(D)	Laser			
	(A)	Large	(B)	Language	alitud8		
6.	'L' ir	HTML stands for:	780		Shuffle	1	
		TALL TABLE		D weath it I			
	(D)	ALTER TABLE			Section of		
	(C)	INSERT					ě
	(B)	ADD			× ===		
	(A)	UPDATE	will be used to ad		enterez sus	nyai	
5.							

```
10. Which of the following output will never be obtained when the given code
    is executed?
                                                                      1
    import random
    Shuffle = random.randrange(10)+1
    Draw = 10*random.randrange(5)
    print ("Shuffle", Shuffle, end="#")
    print ("Draw", Draw)
    (A)
         Shuffle 1 # Draw 0
    (B)
         Shuffle 10 # Draw 10
    (\mathbf{C})
         Shuffle 10 # Draw 0
    (D)
          Shuffle 11 # Draw 50
11. Ethernet card is also known as:
    (A)
         LIC
                                     (B) MIC
    (C)
         NIC
                                     (D) OIC
12. What will be the output of the given code?
                                                                     1
            Opended the statements given below and then there is be entra
    a=10
    def convert(b=20):
         a = 30
         c=a+b
        print(a,c)
    convert (30)
    print(a)
13. For the following Python statement:
    N = (25)
    What shall be the type of N?
         Integer
    (A)
    (B)
         String
    (C)
         Tuple
         List
    (D)
```

91/S

201	7/	Ravi is creating a field that contains alphanumeric values and fixed	
14.	leng	ths. Which MySQL data type should he choose for the same?	1
	(A)	VARCHAR	
	(B)	CHAR and but the season of bandar and the season of the se	
	(C)	LONG	
	(D)	NUMBER (A) northern an northern axe over the	
		(d.) desertion (A. le true, but Neason: El le false:	
15.	Fill i	n the blank: girif ei (fi) noeann find , selad al (A) noirmea A (A)	1
	The f	full form of WWW is	
Him		full form of www is	-
16.	+1	files are stored in a computer in a sequence of bytes.	1
	(A)	Text	
200	(B)	Binary STR Lat MTR coorded composition and evid (ii)	
	(C)	CSV	
	(D)	Notepad owner of tragger dijw sababba II arret sait amile (i) (ii)	
		(ii) What is the main purpose of a Router?	
aana	icte of	No.17 and 18 are Assertion and Reason type questions. Each question f two statements, namely, Assertion (A) and Reason (R). Select the most ption considering the Assertion and Reason.	
17	Δοςοι	rtion (A): Global variables are accessible in the whole program.	1
2		on (R): Local variables are accessible only within a function or block in which it is declared.	
	(A)	Both Assertion (A) and Reason (R) are true and Reason (R) is the correct explanation of Assertion (A).	
	(B)	Both Assertion (A) and Reason (R) are true, but Reason (R) is not the correct explanation of Assertion (A).	
	(C)	Assertion (A) is true, but Reason (R) is false.	
	(D)	Assertion (A) is false, but Reason (R) is true.	
91/8		5 P.T	.0.

18.	Asse	ertion	(A): If numeric data are to be written to a text file, needs to be converted into a string before writing to	the d	ata ile.	1
	Reas	son (R	(3) 194(in-1: 'No. 1) "(2) [Physical Physical P			
	(A)	Both corre	Assertion (A) and Reason (R) are true and Reason (R) ect explanation of Assertion (A).	R) is 1	the	
	(B)	Both	Assertion (A) and Reason (R) are true, but Reason (R) is ect explanation of Assertion (A).	s not	the	
	(C)	Asse	ertion (A) is true, but Reason (R) is false.			
	(D)		-4: (A): C1 1 1 D		MH.	
			SECTION B	Huis	7×2=	14
19.	(a)	(i)	Expand the following terms:		1+1=	=2
			URL, XML			
		(ii)	Give one difference between HTTP and FTP.			
		(11)	OR		(-11)	
			the state of the s		152	
	(b)	(i)	Define the term IP address with respect to network.		(i,i)	
		(ii)	What is the main purpose of a Router?		1+1=	=2
			17 and 18 are Assertion and Reason Type quarters. Ec-	rs No	roites	
			arcicenents, manely, smeeting (A) and Reuson (P), selo a considering the Assertion and Reuson.		Ador.	
20.	Obs	erve synta	the following code carefully and rewrite it after rectical errors. Underline all the corrections made.		ng	2
	def	1fun	c():		-14	7200
		a=in	put("Enter a number"))			
		if a				
	10.7	New all	orint("Promoted to next class")			
		ELSE:	(A) polymer Assertion of Assertion (A)			
			orint("Repeat")			
		e e e e e	orint("Repeat")			
						1.60

6

91/S

21. (a) Write the definition of a method/function SearchOut (Teachers, TName) to search for TName from a list Teachers, and display the 2 position of its presence. For example: "Siddharth", If the Teachers contain ["Ankit", "Sangeeta", "rahul"] and TName contains "Rahul" The function should display Rahul at 2 rahul at 4 the table, student containing the RO must like b Chass and Stream, the has been acked by the P (b) Write the definition of a method/function Copy_Prime(lst) to copy all the prime numbers from the list 1st to another list 1st_prime. 2 2 22. Predict the output of the following code: d={"IND": "DEL", "SRI: "COL", "CHI": "BEI"} str1="" for i in d: str1=strl+str(d[i])+"@" str2=str1[:-1] print (str2) Write the Python statement for each of the following tasks using 23. (a) BUILT-IN functions/methods only: 1+1=2To delete an element 10 from the list 1st. (i) To replace the string "This" with "That" in the string str1. (ii) (b) A dictionary dict2 is copied into the dictionary dict1 such that the common key's value gets updated. Write the Python commands to do 2 the task and after that empty the dictionary dict1. P.T.O. 7

91/S

24. (a) Mr. Atharva is given a task to create a database, Admin. He has to create a table, users in the database with the following columns: 1+1=2

User_id - int

User_name - varchar(20)

Password - varchar(10)

Help him by writing SQL queries for both tasks.

OR

(b) Ms. Rita is a database administrator at a school. She is working on the table, student containing the columns like Stud_id, Name, Class and Stream. She has been asked by the Principal to strike off the record of a student named Rahul with student_id as 100 from the school records and add another student who has been admitted with the following details:
1+1=2

2

Stud_id - 123

Name - Rajeev

Class - 12

Stream - Science

Help her by writing SQL queries for both tasks.

25. Predict the output of the following code:

def Total (Num=10):

Sum=0

for C in range (1, Num+1):

if C%2!=0:

continue

Sum+=C

return Sum

print(Total(4),end="\$")

print(Total(),sep="0")

26. Predict the output of the Python code given below:

```
3
```

```
s="India Growing"
n = len(s)
m=""
for i in range (0, n) :
    if (s[i] >= 'a' and s[i] <= 'm') :
        m = m + s [i].upper()
    elif (s[i] >= '0' and s[i] <= 'z') :
        m = m +s [i-1]
    elif (s[i].isupper()):
        m = m + s[i].lower()
    else:
        m = m + '@'</pre>
```

27. Consider the table Stationery given below and write the output of the SQL queries that follow.

3

Table: Stationery

print (m)

ITEMNO	ITEM	DISTRIBUTOR	QTY	PRICE
401	Ball Pen 0.5	Reliable Stationers	100	16
402	Gel Pen Premium	Classic Plastics	150	20
403	Eraser Big	Clear Deals	210	10
404	Eraser Small	Clear Deals	200	5
405	Sharpener Classic	Classic Plastics	150	8
406	Gel Pen Classic	Classic Plastics	100	15

- (i) SELECT DISTRIBUTOR, SUM(QTY) FROM STATIONERY GROUP BY DISTRIBUTOR;
- (ii) SELECT ITEMNO, ITEM FROM STATIONERY WHERE DISTRIBUTOR = "Classic Plastics" AND PRICE > 10;
- (iii) SELCET ITEM, QTY * PRICE AS "AMOUNT" FROM STATIONERY WHERE ITEMNO = 402;

28. (a) Write a method/function COUNTWORDS () in Python to read contents from a text file DECODE. TXT, to count and return the occurrence of those words, which are having 5 or more characters.

3

OR

(b) Write a method/function COUNTLINES () in Python to read lines from a text file CONTENT.TXT, and display those lines, which have @ anywhere in the line.

3

For example:

If the content of the file is:

Had an amazing time at the concert last night with @MusicLoversCrew.

Excited to announce the launch of our new website!

G20 @ India

The method/function should display

Had an amazing time at the concert last night with @MusicLoversCrew
G20 @ India

29. Consider the table Rent_cab, given below:

Table : Rent_cab

Vcode	VName	Make	Color	Charges
101	Big car	Carus	White	15
102	Small car	Polestar	Silver	10
103	Family car	Windspeed	Black	20
104	Classic	Studio	White	30
105	Luxury	Trona	Red	9 Ualan

Based on the given table, write SQL queries for the following:

- (i) Add a primary key to a column name Vcode.
- (ii) Increase the charges of all the cabs by 10%.
- (iii) Delete all the cabs whose maker name is "Carus".

30. A dictionary, d_city contains the records in the following format: {state:city}

Define the following functions with the given specifications:

3

- (i) push_city(d_city): It takes the dictionary as an argument and pushes all the cities in the stack CITY whose states are of more than 4 characters.
- (ii) pop_city(): This function pops the cities and displays "Stack empty" when there are no more cities in the stack.

SECTION D

2×4=8

31. Consider the tables GAMES and PLAYERS given below:

Table: GAMES

GCode	GameName	Type	Number	PrizeMoney	
101	Carrom Board	Indoor	2	5000	
102	Badminton	Outdoor	2	12000	
103	Table Tennis	Indoor	4 0 1000	NULL	
104	Chess	Indoor	2	9000	Que en en
105	Lawn Tennis	Outdoor	4:0002	25000	

Table: PLAYERS

PCode	Name	GCode
1	Nabi Ahmad	101 alsomA
2	Ravi Sahai	108
3	Jatin	101
4	Nazneen	103

Write SQL queries for the following:

4

(i) Display the game type and average number of games played in each type.

contents evaluate has seen meitsellementes valuations

- (ii) Display prize money, name of the game, and name of the players from the tables Games and Players.
- (iii) Display the types of games without repetition.
- (iv) Display the name of the game and prize money of those games whose prize money is known.

32. Mr. Mahesh is a Python Programmer working in a school. He has to maintain the records of the sports students. He has created a csv file named sports.csv, to store the details. The structure of sports.csv is:

[sport_id, competition, prize_won]

where

sport_id, is Sport id (integer)

competition is competition name (string)

prize_won is ("Gold", "Silver", "Bronze")

Mr. Mahesh wants to write the following user-defined functions:

Add_detail(): to accept the detail of a student and add to a csv file, "sports.csv".

Count_Medal(): to display the name of competitions in which students have won "Gold" medal.


Help him in writing the code of both the functions.

1

SECTION E

 $3 \times 5 = 15$

33. Logistic Technologies Ltd. is a Delhi based organization which is expanding its office set-up to Ambala. At Ambala office campus, they are planning to have 3 different blocks for HR, Accounts and Logistics related work. Each block has a number of computers, which are required to be connected to a network for communication, data and resource sharing.



As a network consultant, you have to suggest the best network related solutions for them for issues/problems raised in (i) to (v), keeping in mind the distances between various block/locations and other given parameters.

Distances between various blocks/locations:

HR Block to Accounts Blocks	400 meters
Accounts Block to Logistics Block	200 meters
Logistics Block to HR Block	150 meters
Delhi Head Office to Ambala Office	220 Km

Number of computers installed at various blocks are as follows:

HR Block	a-4	ebox 70
Accounts Block	mw 1, 20 f	40
Logistics Block	in the true paint	30

- (i) Suggest the most appropriate block/location to house the SERVER in the Ambala office. Justify your answer.
- (ii) Suggest the best wired medium to efficiently connect various blocks within the Ambala office compound.
- (iii) Draw an ideal cable layout (Block to Block) for connecting these blocks for wired connectivity.
- (iv) The company wants to schedule an online conference between the managers of Delhi and Ambala offices. Which protocol will be used for effective voice communication over the Internet?
- (v) Which kind of network will it be between Delhi office and Ambala office?

- 34. (a) (i) What is the main purpose of seek() and tell() method?
 - (ii) Consider a binary file, Cinema.dat containing information in the following structure:

[Mno, Mname, Mtype]

Write a function, search_copy(), that reads the content from the file Cinema.dat and copies all the details of the "Comedy" movie type to file named movie.dat.

OR

- (b) (i) Give one difference between write() and writeline() function in text file.
 - (ii) A Binary file, "Items.dat" has the following structure:

 [Icode, Description, Price]

 Where

 Icode Item code

 Description Detail of item

Price - Price of item

Write a function Add_data(), that takes Icode,

Description and Price from the user and writes the information in the binary file "Items.dat".

- 35. (a) (i) Define the term foreign key with respect to RDBMS.
 - (ii) Sangeeta wants to write a program in Python to delete the record of a candidate "Raman" from the table named Placement in MySQL database, Agency:

The table Placement in MySQL contains the following attributes:

CName - String

Dept - String

Place - String

Salary - integer

Note the following to establish connectivity between Python and MySQL:

- Username root
- Password job
- Host localhost

Help Sangeeta to write the program in Python for the above mentioned task.

OR

5

5

- (b) (i) Give one difference between CHAR and VARCHAR datatype in MySQL.
 - (ii) Rahim wants to write a program in Python to insert the following record in the table named Bank_Account in MySQL database, Bank:
 - Accno integer
 - Cname string
 - Atype string
 - Amount float

Note the following to establish connectivity between Python and MySQL:

- Username admin
- Password root
- Host localhost

The values of fields Accno, Cname, Atype and Amount have to be accepted from the user. Help Rahim to write the program in Python.